




FEATURES

- Suitable for modem speeds up to V.90 (56 kbps).
- Total Harmonic Distortion rated -92 dB typ. @ 600 Hz, -10 dBm and -75 dB typ. @ 150 Hz, -3 dBm.
- Insertion Loss rated 2.45 dB typ. @ 2000 Hz.
- Complies with IEC60950 Reinforced safety norms.
- Matches 600 Ohm and complex impedance telephone lines.
- Uses minimal external components for impedance matching.
- Very small PCB footprint (19.2 mm x 15.0 mm).
- Very Low-Profile (11.3 mm).
- Industry-standard pin configuration.

DESCRIPTION


The REMtech Magnetics EMIT-3165 is a “Dry” Encapsulated Modem Isolation Transformer suitable for up to V.90 (56 kbps) consumer and internet analog modem applications compliant with International safety norms.

EMIT-3165 provides a popular smaller package alternative to other products such as EMIT-3020L. Due to exceptional distortion ratings, these are very high-performance modem couplers !


PRODUCT COMPLIANCE

- | | |
|-------------------------------------|---------|
| ■ UL / C-UL recognized file number: | Pending |
| ■ BSI certificate number(s): | Pending |
| ■ BABT certificate of recognition: | Pending |

NOMENCLATURE (Fig. 1)



MECHANICAL DIMENSIONS (Fig. 2)




Literature Number: DSA.EMIT-3165
© Copyright 2000, REMtech Corporation
All rights reserved. Printed in U.S.A.
7/00

ELECTRICAL PERFORMANCE SPECIFICATIONS

Electrical Performance Specifications ($T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETERS	CONDITIONS	MIN	TYP	MAX	UNITS
Impedance	Reflected on Primary With Load on Secondary	- -	600 360	- -	Ohms Ohms
Total Harmonic Distortion	@ 600 Hz, -10 dBm @ 150 Hz, -3 dBm	- -	-92 -75	-86 -70	dB dB
Insertion Loss	Per IEEE method; @ 2000 Hz	-	2.45	2.65	dB
Return Loss	200 Hz - 4000 Hz Per 600 Ohm Match (Fig. 3) Per CTR21 Pan-Euro Match (Fig. 10)	18 25	- -	- -	dB dB
Dielectric Breakdown Isolation Production methods applied:	Safety Standard tested 1 Min. HiPot Voltage Duration Trip Leakage Current	3000 3750 2 -	- - - -	- - - 200	Vrms Vrms Sec μA
Frequency Response	200 Hz - 4000 Hz	-	± 0.80	-	dB
Longitudinal Balance	Per FCC part 68.310 60 Hz - 1000 Hz 1000 Hz - 4000 Hz	60 40	- -	- -	dB dB
DC Resistance @ 20°C , $\pm 10\%$	Primary Winding Secondary Winding	- -	140 140	- -	Ohms Ohms
DC Current in Primary	-	-	0	-	mADC
Turns Ratio	Primary to Secondary; $\pm 2\%$	-	1:1	-	Turns
Operating Temperature	-	-40	-	105	$^\circ\text{C}$
Storage Temperature	-	-40	-	125	$^\circ\text{C}$
Soldering Temperature	10 Sec. Max.	-	-	260	$^\circ\text{C}$

600 OHM MATCH (Fig. 3)



SCHEMATIC EQUIVALENT (Fig. 4)


(Typical Transformer Model @ 1 V, 1 kHz)



REMtech Corporation makes no assertion or warranty that the circuitry and the uses thereof disclosed herein are non-infringing on any valid US or foreign patents. REMtech assumes no liability as a result of the use of said specifications and reserves the right to make changes to specifications without notice. REMtech does not authorize or warrant any REMtech device for use in life support devices and/or systems. Contact your nearest REMtech Sales Office for the latest specifications.

Literature Number: DSB.EMIT-3165
 © Copyright 2000, REMtech Corporation
 All rights reserved. Printed in U.S.A.
 7/00

STANDARD PACKAGING (Fig. 9)




Packaging

Material	Contents	#Transformers
Large Box	5 Small Boxes	1860
Small Box	12 Tubes	372
Tube	31 Transformers	31
---	Transformer	1

PAN-EUROPEAN CTR21 MATCH (Fig. 10)



(Application circuits available on request for specific national match requirements.)



Literature Number: DSC.EMIT-3165
 © Copyright 2000, REMtech Corporation
 All rights reserved. Printed in U.S.A.
 7/00

PERFORMANCE DATA


TOTAL HARMONIC DISTORTION (Fig. 5)





INSERTION LOSS (Fig. 6)



FREQUENCY RESPONSE (Fig. 7)



RETURN LOSS (Fig. 8)



REMtech Corporation makes no assertion or warranty that the circuitry and the uses thereof disclosed herein are non-infringing on any valid US or foreign patents. REMtech assumes no liability as a result of the use of said specifications and reserves the right to make changes to specifications without notice. REMtech does not authorize or warrant any REMtech device for use in life support devices and/or systems. Contact your nearest REMtech Sales Office for the latest specifications.

Literature Number: DSD.EMIT-3165
© Copyright 2000, REMtech Corporation
All rights reserved. Printed in U.S.A.
7/00