



Device Number : CDDE-406-004 REV: 1

## 0.4" Quadruple Digit Displays

PART NO. : ELF-406GWB ECN :            Page: 1/5

### ■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

### ■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

### ■ Descriptions :

- The ELF-406 series is a large 10.0 mm (0.4")high seven segment display designed for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These devices are made with white segments and black surface.

PART NO.	Chip	
	Material	Emitted Color
ELF-406GWB	GaP	Green

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936


FAX : 886-2-2267-6244,22676189,22676306

<http://www.everlight.com>

### 0.4" Quadruple Digit Displays

PART NO. :                      ELF-406GWB                      ECN :                      Page:                      2/5

■ Package Dimensions:



■ Notes:

- 1.All dimensions are in millimeters , tolerance is 0.25mm unless otherwise noted.  
2.Above specification may be changed without notice.  
Supplier will reserve authority on material change for above specification.



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDF-406-004 REV: 1

0.4" Quadruple Digit Displays

PART NO. : ELF-406GWB ECN :                      Page: 3/5

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	5	V
Forward Current	IF	30	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	100	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	IF(Peak)	160	mA

■ Electronic optical characteristics :

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Per segment	Iv	1.05	1.50	----	mcd	IF=10mA
	Per decimal point		0.45	0.7	----		
Peak Wavelength		λ p	----	565	----	nm	IF=10mA
Dominant Wavelength		λ d	----	570	----	nm	IF=10mA
Spectrum Radiation	Bandwidth	△ λ	----	30	----	nm	IF=10mA
Forward Voltage		VF	1.5	2.1	2.4	V	IF=10mA
Reverse Current		IR	----	----	10	μ A	VR=5V



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDF-406-004

REV: 1

0.4" Quadruple Digit Displays




PART NO. : ELF-406GWB

ECN :

Page: 4/5

## Typical Electro-Optical Characteristic Curves:

CHIP Material:Gap  
Emitted Color:Yellow Green





# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDF-406-004REV: 1

0.4" Quadruple Digit Displays

PART NO. : ELF-406GWBECN : Page: 5/5

## Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min └ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min └ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1