



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDF-415-001 REV: 1.0

0.4" Quadruple Digit Displays

MODEL NO : ELF-415VGWA ECN : Page: 1/5

■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

■ Descriptions :

- The ELF-415 series is a large 10.0mm (0.4")high seven segment display designed for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These devices are made with white segments and gray surface.

PART NO	Chip	
	Material	Emitted Color
ELF-415VGWA	GaP	Green

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306

<http://www.everlight.com>

B89051165


T00236



0.4" Quadruple Digit Displays


MODEL NO : ELF-415VGWA ECN : Page: 2/5

Package Dimensions:



COMMON CATHODE

- 1 COMMON CATHODE D1
- 2 COMMON CATHODE D2
- 3 ANODE D
- 4 COMMON CATHODE L1,L2
- 5 ANODE E
- 6 COMMON CATHODE D3
- 7 ANODE DP
- 8 COMMON CATHODE D4
- 9 ANODE L3
- 10 CATHODE L3
- 11 ANODE F
- 12 ANODE L1,L2
- 13 ANODE C
- 14 ANODE A
- 15 ANODE G
- 16 ANODE B



Notes:

- 1.All dimensions are in millimeters , tolerance is 0.25mm unless otherwise noted.
 - 2.Above specification may be changed without notice.
- Supplier will reserve authority on material change for above specification.



Device Number : DDF-415-001 REV: 1.0

0.4" Quadruple Digit Displays

MODEL NO : ELF-415VGWA ECN : Page: 3/5

■ Absolute maximum ratings at Ta = 25℃ :

Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	5	V
Forward Current	IF	30	mA
Operating Temperature	Topr	-40 to +85	℃
Storage Temperature	Tstg	-40 to +100	℃
Soldering Temperature	Tsol	260 ± 5	℃
Power Dissipation	Pd	100	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	IF(Peak)	160	mA

■ Electronic optical characteristics :

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Per segment	IV	1.05	1.40	----	mcd	IF=10mA
	Per decimal point		0.30	0.70	----		
Peak Wavelength		λ p	----	570	----	nm	IF=20mA
Dominant Wavelength		λ d	----	571	----	nm	IF=20mA
Spectrum Radiation Bandwidth		△ λ	----	30	----	nm	IF=20mA
Forward Voltage		VF	1.7	2.1	2.4	V	IF=20mA
Reverse Current		IR	----	----	10	μ A	VR=5V



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDF-415-001

REV: 1.0

0.4" Quadruple Digit Displays

MODEL NO : ELF-415VGWA

ECN :

Page: 4/5

■ Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min └ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min └ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1



0.4" Quadruple Digit Displays

MODEL NO: ELF-415VGWA

ECN :

Page: 5/5

■ Typical Electro-Optical Characteristic Curves:

