



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDM-211-009 REV: 1.0

2.3" 5*8 LED Lamp Dot Matrix Displays

MODEL NO : ELLM-2181WB/HRC-6/MS ECN : Page: 1/5

■ Features :

- Large emitting dot 0.264" diameter.
- Low power/high brightness.

■ Applications:

- Instrument panels
- Digital read out display

■ Description :

- The LM-2181 series are a large emitting area(6.7mm diameter)Lamp sources configured in a 40 dots 5*8 matrix array.
- These device is made with water clear dots and black surface.

PART NO	CHIP		C.C. or C.A.
	Material	Emitted Color	
ELLM-2181WB/HRC-6/MS	GaAlAs	Super Red	C.C.

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306


<http://www.everlight.com>



2.3" 5*8 LED Lamp Dot Matrix Displays

MODEL NO : ELLM-2181WB/HRC-6/MS ECN : Page: 2/5

■ Package Dimension:



■ NOTES:

- 1.All dimensions are millimeters , tolerance is 0.25mm unless otherwise noted.
 - 2.Above specification may be changed without notice.
- Supplier will reserve authority on material change for above specification.



2.3" 5*8 LED Lamp Dot Matrix Displays

MODEL NO : ELLM-2181WB/HRC-6/MS ECN : _____ Page: 3/5

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	V _r	5	V
Forward Current	I _f	40	mA
Operating Temperature	T _{opr}	-40 to +85	°C
Storage Temperature	T _{stg}	-40to+100	°C
Soldering Temperature	T _{sol}	260 ± 5	°C
Power Dissipation	P _d	110	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	I _f (Peak)	180	mA

■ Electronic optical characteristics :

Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous Intensity	I _v	250	600	----	mcd	I _f =20mA
Peak Wavelength	λ _p	----	660	----	nm	I _f =20mA
Dominant Wavelength	λ _d	----	643	----	nm	I _f =20mA
Spectrum Radiation Bandwidth	△λ	----	20	----	nm	I _f =20mA
Forward Voltage	V _f	1.5	1.7	2.4	V	I _f =20mA
Reverse Current	I _r	----	----	10	μA	V _r =5V



REV: 1.0

2.3" 5*8 LED Lamp Dot Matrix Displays

Page: 4/5

Reliability test item and condition:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 20 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1



2.3" 5*8 LED Lamp Dot Matrix Displays

MODEL NO: ELLM-2181WB/HRC-6/MSECN: Page: 5/5

Typical Electro-Optical Characteristic Curves:

