



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDM-218-015 REV: 1.0

2.3" 5*8 Dot Matrix Display

MODEL NO : ELM-2181SRCB ECN : _____ Page: 1/4

Features :

- Large emitting dot 0.2" diameter.
- Low power/high brightness.

Description :


- The ELM-2181 series are a large emitting area (5.0mm diameter) LED sources configured in a 40 dots 5*8 matrix array.
- These device is made with water clear dots and black surface.

Applications:

- Instrument panels
- Digital readout display

NOTES:

1. All dimensions are millimeters, tolerance is 0.25mm unless otherwise noted.
 2. Above specification may be changed without notice.
- Supplier will reserve authority on material change for above specification .



PART NO	CHIP		C.C. or C.A.
	Material	Emitted Color	
ELM-2181SRCB	GaAlAs	Super Red	C.C.

OFFICE : NO. 25, Lane 76, Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000, 2267-9936

FAX : 886-2-2267-6244, 22676189, 22676306

<http://www.everlight.com>



2.3" 5*8 Dot Matrix Display

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	Vr	5	V
Forward Current	If	40	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	110	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	180	mA

■ Electronic optical characteristics :

Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous Intensity	Iv	7.8	15.0	----	mcd	If=10mA
Peak Wavelength	λ p	----	660	----	nm	If=20mA
Dominant Wavelength	λ d	----	643	----	nm	If=20mA
Spectrum Radiation Bandwidth	△ λ	----	20	----	nm	If=20mA
Forward Voltage	Vf	1.5	1.7	2.4	V	If=20mA
Reverse Current	Ir	----	----	10	μ A	Vr=5V



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDM-218-015 REV: 1.0

2.3" 5*8 Dot Matrix Display

MODEL NO : ELM-2181SRCB ECN : _____ Page: 3/4

■ Reliability test item and condition:					
NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 20 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C /85% RH	1000 HRS	76 PCS	0/1



2.3" 5*8 Dot Matrix Display

