



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDS-815-003 REV: 1.1

0.8" Single Digit Displays

MODEL NO : ELS-815SRWA ECN : Page: 1/5

■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

■ Description :

- The ELS-815 series is a large 20.4mm (0.8")high seven segment display design for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light .
- These device is made with white segments and gray surface.

PART NO	CHIP		C.C. or C.A.
	Material	Emitted Color	
ELS-815SRWA	GaAlAs	Super Red	C.C.

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306



<http://www.everlight.com>





0.8" Single Digit Displays

MODEL NO : ELS-815SRWA ECN : Page: 2/5

■ Package Dimension:



COMMON CATHODE
1 ANODE A
2 ANODE F
3 COMMON CATHODE
4 ANODE E
5 COMMON CATHODE
6 ANODE LDP
7 NO PIN
8 NO PIN
9 ANODE RDP
10 ANODE D
11 COMMON CATHODE
12 ANODE C
13 ANODE G
14 ANODE B
15 NO PIN
16 COMMON CATHODE



■ NOTES:

- 1.All dimensions are millimeters ,tolerance is 0.25mm unless otherwise noted.
- 2.Above specification may be changed without notice.
Supplier will reserve authority on material change for above specification.



0.8" Single Digit Displays

MODEL NO : ELS-815SRWA ECN : Page: 3/5

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	Vr	5	V
Forward Current	If	40	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	110	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	180	mA

■ Electronic optical characteristics :

Parameter		Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous Intensity	Per segment	Iv	7.80	13.0	----	mcd	If=10mA
	Per decimal point		4.00	7.80	----	mcd	If=10mA
Peak Wavelength		λ_p	----	660	----	nm	If=20mA
Dominant Wavelength		λ_d	----	643	----	nm	If=20mA
Spectrum Radiation Bandwidth		$\Delta\lambda$	----	20	----	nm	If=20mA
Forward Voltage		Vf	1.5	1.7	2.4	V	If=20mA
Reverse Current		Ir	----	----	10	μA	Vr=5V



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDS-815-003 REV: 1.1

0.8" Single Digit Displays

MODEL NO : ELS-815SRWA ECN : Page: 4/5

■ Reliability test item and condition:					
NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260℃ ± 5 ℃	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85℃ 30min └ 5 min L : -55℃ 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100℃ 5min └ 10 sec L : -10℃ 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100℃	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55℃	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85℃/85% RH	1000 HRS	76 PCS	0/1



0.8" Single Digit Displays

MODEL NO: ELS-815SRWA

ECN :

Page:

5/5

Typical Electro-Optical Characteristic Curves:

SR

