

Features: Industry Standard, Custom Made-to-Order Available, 3rd Overtone, HC-49 Size Series

| PARAMETERS | EX121 | EX122 | EX123 | EX124 |
|------------------------------|---|-------|-------|-------|
| Package Part# | T120 | T180 | T170 | T240 |
| Frequency Range (MHz) | 15.0 ~ 100.0 | | | |
| Overtone | 3rd | | | |
| Frequency Calibration (ppm) | +/- 30 | | | |
| Frequency Stability (ppm) | +/- 50 | | | |
| Operating Temp. Range (C) | 0 ~ +70 | | | |
| Max. Resistance Level (ohms) | 15.0MHz~ 60, 30.0MHz~ 40 | | | |
| Resonance Type | Series or Parallel (Specify 10 ~ 50 pF) | | | |
| Maximum Drive Level (uW) | 1,000 | | | |
| Test Drive Level (uW) | 50 | | | |

STANDARD AVAILABLE OPTIONS

Frequency Calibration (ppm): +/- 5, 10, 15, 20, 25, 50

Frequency Stability (ppm): +/- 5, 10, 15, 20, 25, 50 (Frequency and Temp. Range Dependent)

Operating Temp. Range (C): Downward to -60 and upward to +150 (Frequency Range Dependent)

Max. Resistance Level (ohms): Lower values are available (Frequency Range Dependent)

Sleeves, Insulators, 3rd Leads, Cut & Crimped Leads available

