



E2O Communications, Inc.

## 3.3V SFP MTRJ Transceiver for InfiniBand™ 850nm VCSEL for Multimode Fiber

### EM250-MP3TA Preliminary Data Sheet



#### Features

- 850nm Vertical Cavity Surface Emitting Laser (VCSEL) Source Technology
- Designed for use in InfiniBand Architecture (IBA) IB-1X-SX at 2.5 Gbps applications
- Compliant with specifications for IEEE-802.3z Gigabit Ethernet (1000Base-SX) at 1.25 Gbps
- Compliant with Small Form-factor Pluggable (SFP) Multi-Source Agreement
- Compatible with Industry Standard RFT Electrical Connector & Cage
- MT-RJ Receptacle Compatible with Industry Standard MT-RJ Optical Connector
- Operates with 50  $\mu\text{m}$  and 62.5  $\mu\text{m}$  multimode optical fibers
- Class 1 Laser Safety Compliant
- Single +3.3V Power Supply
- Hot Pluggable
- EEPROM with Serial ID Functionality

#### Product Description

The EM250-MP3 from E2O Communications is a hot-pluggable 3.3V Small Form-Factor Pluggable transceiver designed for use in InfiniBand applications. The EM250-MP3 transceivers use the MT-RJ optical receptacle that is compatible with the industry standard MT-RJ connector. The transceiver is also compatible with industry standard RFT connector and cage. The transceiver conforms to the Small Form-factor Pluggable (SFP) multi-source agreement (MSA).

Each EM250-MP3 transceiver consists of an optical subassembly housing both the transmitter and the receiver, and an electrical subassembly. All are packaged together with a top metal cover and plastic bottom base. The transmitter consists of a high-performance 850-nm VCSEL and the receiver consists of a GaAs PIN and a pre-amplifier.

A serial EEPROM in the transceiver allows the user to access information. Details of the Serial Identification Protocol will be contained in the SFP Multi-Source Agreement.

All EM250-MP3 transceivers include a Loss-Of-Signal-Detect circuit, which provides a TTL logic high output when an unusable input optical signal level is detected.

#### Electromagnetic Interference (EMI) & Immunity


To assist the customer in managing the overall equipment EMI performance, the EM250-MP3 transceiver is designed to be compatible with the industry-standard RFT cage. The RFT cage is designed to provide protection for EMI emission and EMI susceptibility. All transceivers comply with the FCC Class B limits.

#### Eye Safety

The EM250-MP3 850-nm VCSEL-based transceivers have been designed to meet Class 1 eye safety and comply with FDA 21CFR 1040.10 and 1040.11 and the IEC 825-1.

#### Ordering Information

EM250-MP3 T A -zz



EB-SFP-A (Evaluation Board)



E2O Communications, Inc.

## 3.3V SFP MTRJ Transceiver for InfiniBand™ 850nm VCSEL for Multimode Fiber

### ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	NOTES
Storage Temperature	T <sub>S</sub>	-40		85	°C	
Supply Voltage	V <sub>CC</sub>			5.0	V	V <sub>CC</sub> – ground

### RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	NOTES
Ambient Operating Temperature	T <sub>A</sub>	0		70	°C	
Supply Voltage	V <sub>CC</sub>	3.1		3.5	V	
Transmitter Differential Input Voltage	V <sub>D</sub>	0.6		2.0	V	

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 0°C to 70°C, V<sub>CC</sub> = 3.15V to 3.45V)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	NOTES
<b>TRANSMITTER</b>						
Supply Current	I <sub>CCT</sub>		80	100	mA	
<b>RECEIVER</b>						
Supply Current	I <sub>CCR</sub>		100	200	mA	
Data Output Peak-to-Peak Differential Voltage	V <sub>O,P-P</sub>	0.5		1.9	V	
Data Output Rise & Fall Times	t <sub>r</sub> , t <sub>f</sub>			0.20	ns	20-80%
Loss Signal Detect Output – High	V <sub>oh</sub>	2.0		V <sub>CC</sub>	V	
Loss Signal Detect Output - Low	V <sub>ol</sub>	0.0		0.5	V	



E2O Communications, Inc.

## 3.3V SFP MTRJ Transceiver for InfiniBand™ 850nm VCSEL for Multimode Fiber

OPTICAL CHARACTERISTICS ( $T_A = 0^\circ\text{C}$  to  $70^\circ\text{C}$ ,  $V_{CC} = 3.15\text{V}$  to  $3.45\text{V}$ )

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	NOTES
<b>TRANSMITTER</b>						
Output Optical Power 50/125 $\mu\text{m}$ , NA = 0.20 fiber	$P_{\text{OUT}}$	-9.5		-4	dBm avg.	
Output Optical Power 62.5/125 $\mu\text{m}$ , NA = 0.275 fiber	$P_{\text{OUT}}$	-9.5		-4	dBm avg.	
Optical Extinction Ratio		9			dB	
Center Wavelength	$\lambda_c$	840	850	860	nm	
Spectral Width – rms	$\sigma$			0.85	nm	
Optical Rise/Fall Time	$t_r / t_f$			0.15	ns	20-80% note 1.
Relative Intensity Noise	RIN		-122	-117	dB/Hz	
Transmitter Optical Contributed Jitter (TOTAL)	TJ			150	ps	
<b>RECEIVER</b>						
Minimum Optical Input Power (Sensitivity)	$P_{\text{IN Min}}$			-17	dBm avg.	
Maximum Optical Input Power (Saturation)	$P_{\text{IN Max}}$	0			dBm avg.	
Operating Center Wavelength	$\lambda_c$	770		860	nm	
Return Loss		12			dB	
Signal Detect – Asserted	$P_A$			-17	dBm avg.	
Signal Detect – Deasserted	$P_D$	-30			dBm avg.	
Signal Detect – Hysteresis	$P_A - P_D$	0.5		5.0	dB	

Note 1. measured with the 4<sup>th</sup> order BT filter off.




# 3.3V SFP MTRJ Transceiver for InfiniBand™ 850nm VCSEL for Multimode Fiber

E2O Communications, Inc.

**Table 1: SFP Pin Definitions**

PIN	SYMBOL	DESCRIPTION OF FUNCTION	PIN	SYMBOL	DESCRIPTION OF FUNCTION
1	VeeT	Transmitter Signal Ground	11	VeeR	Receiver Signal Ground
2	TX Fault	Transmitter Fault Indication	12	RD-	Received Data Inverted Differential Output
3	TX Disable	Transmitter Disable	13	RD+	Received Data Non-Inverted Differential Output
4	MOD-DEF2	Module Definition 2	14	VeeR	Receiver Signal Ground
5	MOD-DEF1	Module Definition 1	15	VccR	+3.3V Receiver Power Supply
6	MOD-DEF0	Module Definition 0	16	VccT	+3.3V Transmitter Power Supply
7	Rate Select	Select between full or reduced receiver bandwidth	17	VeeT	Transmitter Signal Ground
8	LOS	Loss of Signal	18	TD+	Transmitter Data Non-Inverted Differential Input
9	VeeR	Receiver Signal Ground	19	TD-	Transmitter Data Inverted Differential Input
10	VeeR	Receiver Signal Ground	20	VeeT	Transmitter Signal Ground

**Figure 1: SFP Transceiver Package Outline in mm [inches].**



E2O Communications, Inc. reserves the right to make changes in product design, features, capabilities, function, or specifications at any time without notice. Information supplied by E2O Communications, Inc. is believed to be accurate and reliable at the time of release. No responsibility is assumed by E2O Communications, Inc. for its use nor for any infringements of third parties, which may result from its use. No license is granted by implication or otherwise under any patent right of E2O Communications, Inc.