



0.4" Quadruple Digit Displays

PART NO. : ELF-4K6SRWB ECN : Page: 1/5

■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

■ Descriptions :

- The ELF-4K6 series is a large 10.0 mm (0.4")high seven segment display designed for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These devices are made with white segments and black surface.

PART NO.	Chip	
	Material	Emitted Color
ELF-4K6SRWB	GaP(G)	Green
	GaAlAs(SR)	Super Red

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306

A0201014






<http://www.everlight.com>



0.4" Quadruple Digit Displays

PART NO. : ELF-4K6SRWBECN : Page: 2/5

■ Package Dimensions:



■ Notes:

1.All dimensions are in millimeters , tolerance is 0.25mm unless otherwise noted.

2.Above specification may be changed without notice.

Supplier will reserve authority on material change for above specification.



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDF-4K6-001 REV: 1

0.4" Quadruple Digit Displays

PART NO. : ELF-4K6SRWB ECN : Page: 3/5

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	5	V
Forward Current	IF (G)	30	mA
	IF(SR)	40	
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd (G)	100	mW
	Pd(SR)	110	
Peak Forward Current(Duty 1/10 @ 1KHz)	IF(Peak) (G)	160	mA
	IF(Peak) (SR)	180	

■ Electronic optical characteristics :

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Per segment	Iv	4.0	6.0	----	mcd	IF=10mA
	Per decimal point		1.0	2.0	----		
Peak Wavelength		λ p(G)	----	565		nm	IF=20mA
		λ p(SR)	----	660	----		
Dominant Wavelength		λ d(G)	----	570	----	nm	IF=20mA
		λ d(SR)	----	643	----		
Spectrum Radiation Bandwidth		△ λ (G)	----	30	----	nm	IF=20mA
		△ λ (SR)	----	20	----		
Forward Voltage		VF(G)	1.7	2.1	2.4	V	IF=20mA
		VF(SR)	1.5	1.7	2.4		
Reverse Current		IR	----	----	10	μ A	VR=5V



0.4" Quadruple Digit Displays




PART NO. : ELF-4K6SRWB

ECN :




Page: 4/5

■ Typical Electro-Optical Characteristic Curves:

SR



GHIP Material:Gap
Emitted Color:Yellow Green





EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDF-4K6-001

REV: 1

0.4" Quadruple Digit Displays

PART NO. : ELF-4K6SRWB

ECN :

Page: 5/5

Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min └ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min └ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1