

Surface Mount Type

Series: **FC** Type: **V**

- **Features** Endurance : 105°C 1000 h
 Low impedance (1/2 for HA series)
 5.4 mm height ($\leq \phi 6.3$)
 Vibration-proof product is available upon request. ($\phi 8 \leq$)

Country of Origin


Japan
 Malaysia ($\phi 4, \phi 5, \phi 6.3$)




■ Specifications

Category temp. range								-40 to +105°C
Rated W.V. Range								6.3 to 50 V .DC
Nominal Cap. Range								1 to 1500 μ F
Capacitance Tolerance								±20 % (120Hz/+20°C)
DC Leakage Current	I ≤ 0.01 CV or 3(μ A) after 2 minutes							(Whichever, greater)
tan δ	W.V. (V)	6.3	10	16	25	35	50	(120Hz/+20°C) (max.)
	tan δ	0.26	0.19	0.16	0.14	0.12	0.12	
Characteristics at Low Temperature	W.V. (V)	6.3	10	16	25	35	50	(Impedance ratio at 120 Hz)
	-25 / +20 °C	2	2	2	2	2	2	
	-40 / +20 °C	3	3	3	3	3	3	
Endurance	After applying rated working voltage for 1000 hours at +105±2°C and then being stabilized at +20°C, capacitors shall meet the following limits.							
	Capacitance change		±20% of initial measured value					
	tan δ		≤ 200 % of initial specified value					
	DC leakage current		≤ initial specified value					
Shelf Life	After storage for 1000 hours at +105±2°C with no voltage applied and then being stabilized at +20°C, capacitors shall meet the limits specified in Endurance.(With voltage treatment)							
Resistance to Soldering Heat	After reflow soldering (Refer to page 184 for recommendable temperature profile.) and then being stabilized at +20°C, capacitor shall meet the following limits.							
	Capacitance change		±10% of initial measured value					
	tan δ		≤ initial specified value					
	DC leakage current		≤ initial specified value					

■ Marking



■ Dimensions in mm (not to scale)



■ Case size

Cap. (μ F)	W.V.(V)	6.3 (0J)	10 (1A)	16 (1C)	25 (1E)	35 (1V)	50(1H)
1 to 3.3						B	B
4.7						B	C
6.8					B	C	
10				B		C	D
22	B		C	D	D	D	E
33		C		D	D	E	F
47	C		D	E	E	E	G
68	D		E	F			
100	D	E	E	F	G	G	
150		E					
220	E	F	G	G	G	G	
330	F		G	G	G		
470		G	G	G			
680							
1000	G	G					
1500	G						

■ Impedance (Ω) (100kHz/+20°C)

(6.3 to 35W.V)

Size Code	B	C	D	E	F	G
Impedance	3.0	1.8	1.0	0.4	0.3	0.15

(50W.V)

Size Code	B	C	D	E	F	G
Impedance	5.0	3.0	2.0	0.7	0.6	0.3

Design, and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and / or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

■ Standard Products

W.V. (V)	Cap. ($\pm 20\%$) (μF)	Case size			Specification		Part No.	Min. Packaging Q'ty
		Dia. (mm)	Length (mm)	Size Code	Ripple current (100kHz) (+105°C) (mA)	Impe- dance (100kHz) (+20°C) (Ω)		Taping (pcs)
6.3	22	4	5.4	B	60	3.00	EEVFC0J220R	2000
	47	5	5.4	C	95	1.80	EEVFC0J470R	1000
	68	6.3	5.4	D	140	1.00	EEVFC0J680P	1000
	100	6.3	5.4	D	140	1.00	EEVFC0J101P	1000
	220	8	6.2	E	230	0.40	EEVFC0J221P	1000
	330	8	10.2	F	450	0.30	EEVFC0J331P	500
	1000	10	10.2	G	670	0.15	EEVFC0J102P	500
	1500	10	10.2	G	670	0.15	EEVFC0J152P	500
10	33	5	5.4	C	95	1.80	EEVFC1A330R	1000
	100	8	6.2	E	230	0.40	EEVFC1A101P	1000
	150	8	6.2	E	230	0.40	EEVFC1A151P	1000
	220	8	10.2	F	450	0.30	EEVFC1A221P	500
	470	10	10.2	G	670	0.15	EEVFC1A471P	500
	1000	10	10.2	G	670	0.15	EEVFC1A102P	500
16	10	4	5.4	B	60	3.00	EEVFC1C100R	2000
	22	5	5.4	C	95	1.80	EEVFC1C220R	1000
	47	6.3	5.4	D	140	1.00	EEVFC1C470P	1000
	68	8	6.2	E	230	0.40	EEVFC1C680P	1000
	100	8	6.2	E	230	0.40	EEVFC1C101P	1000
	220	10	10.2	G	670	0.15	EEVFC1C221P	500
	330	10	10.2	G	670	0.15	EEVFC1C331P	500
	470	10	10.2	G	670	0.15	EEVFC1C471P	500
	680	10	10.2	G	670	0.15	EEVFC1C681P	500
25	6.8	4	5.4	B	60	3.00	EEVFC1E6R8R	2000
	22	6.3	5.4	D	140	1.00	EEVFC1E220P	1000
	33	6.3	5.4	D	140	1.00	EEVFC1E330P	1000
	47	8	6.2	E	230	0.40	EEVFC1E470P	1000
	68	8	10.2	F	450	0.30	EEVFC1E680P	500
	100	8	10.2	F	450	0.30	EEVFC1E101P	500
	220	10	10.2	G	670	0.15	EEVFC1E221P	500
	330	10	10.2	G	670	0.15	EEVFC1E331P	500
	470	10	10.2	G	670	0.15	EEVFC1E471P	500
35	1	4	5.4	B	60	3.00	EEVFC1V1R0R	2000
	2.2	4	5.4	B	60	3.00	EEVFC1V2R2R	2000
	3.3	4	5.4	B	60	3.00	EEVFC1V3R3R	2000
	4.7	4	5.4	B	60	3.00	EEVFC1V4R7R	2000
	6.8	5	5.4	C	95	1.80	EEVFC1V6R8R	1000
	10	5	5.4	C	95	1.80	EEVFC1V100R	1000
	22	6.3	5.4	D	140	1.00	EEVFC1V220P	1000
	33	8	6.2	E	230	0.40	EEVFC1V330P	1000
	47	8	6.2	E	230	0.40	EEVFC1V470P	1000
	100	10	10.2	G	670	0.15	EEVFC1V101P	500
	220	10	10.2	G	670	0.15	EEVFC1V221P	500

The taping dimension are explained on p.187 of our Catalog.
Please use it as a reference guide.
Endurance : 105°C 1000h

Design, and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and / or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

■ Standard Products

W.V. (V)	Cap. ($\pm 20\%$) (μF)	Case size			Specification		Part No.	Min. Packaging Qty
		Dia. (mm)	Length (mm)	Size Code	Ripple current (100kHz) (+105°C) (mA)	Impe- dance (100kHz) (+20°C) (Ω)		Taping (pcs)
35	330	10	10.2	G	670	0.15	EEVFC1V331P	500
50	1	4	5.4	B	30	5.00	EEVFC1H1R0R	2000
	2.2	4	5.4	B	30	5.00	EEVFC1H2R2R	2000
	3.3	4	5.4	B	30	5.00	EEVFC1H3R3R	2000
	4.7	5	5.4	C	50	3.00	EEVFC1H4R7R	1000
	10	6.3	5.4	D	70	2.00	EEVFC1H100P	1000
	22	8	6.2	E	120	0.70	EEVFC1H220P	1000
	33	8	10.2	F	300	0.60	EEVFC1H330P	500
	47	10	10.2	G	500	0.30	EEVFC1H470P	500
	100	10	10.2	G	500	0.30	EEVFC1H101P	500
	220	10	10.2	G	500	0.30	EEVFC1H221P	500

The taping dimension are explained on p.187 of our Catalog.
Please use it as a reference guide.
Endurance : 105°C 1000h