


Radial Lead Type

Series: KS Type : A


- Features Endurance:85°C 1000 h
5 mm height

Country of Origin
Japan
Malaysia

■ Specifications

Category temp. range	-40 to +85°C							
Rated W.V. Range	4 to 50 V.DC							
Nominal Cap. Range	0.1 to 330 μ F							
Capacitance Tolerance	$\pm 20\%$ (120Hz/+20°C)							
DC Leakage Current	$I \leq 0.01$ CV or $3(\mu A)$ after 2 minutes (Whichever, greater)							
$\tan \delta$	Please see the attached standard products list.							
Characteristics at Low Temperature	W.V. (V)	4	6.3	10	16	25	35	50
	Z(-25°C)/Z(+20°C)	7	4	3	2	2	2	2
Endurance	Z(-40°C)/Z(+20°C)	15	8	6	4	4	3	3
	After applying rated working voltage for 1000 hours at +85°C and then being stabilized at +20°C, capacitors shall meet the following limits.							
	Capacitance change	$\pm 20\%$ of initial measured value (4V. : $\pm 30\%$)						
Shelf Life	$\tan \delta$	$\leq 200\%$ of initial specified value						
	DC leakage current	\leq initial specified value						
	After storage for 1000 hours at $+85 \pm 2$ °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance.(With voltage treatment)							

■ Dimensions in mm (not to scale)



Body Dia.φD	3	4	5	6.3	8
Lead Dia.φd	0.4	0.45	0.45	0.45	0.45
Lead Space P	1.0	1.5	2.0	2.5	2.5

■ Standard Products

W.V. (V)	Cap. (±20%) (μF)	Case size		Specification		Lead Length			Part No.	Min. Packaging Q' ty	
		Dia. (mm)	Length (mm)	Ripple current (120Hz) (+85°C) (mA)	tan δ (120Hz) (+20°C)	Lead Dia. (mm)	Lead Space			Straight Leads (pcs)	Taping (pcs)
							Straight (mm)	Taping *B (mm)	Taping *i (mm)		
4	22	3	5	19	0.35	0.40	1.0	5.0	2.5	ECEA0GKK220()	200 2000
	33	4	5	26	0.35	0.45	1.5	5.0	2.5	ECEA0GKS330()	200 2000
	47	4	5	34	0.35	0.45	1.5	5.0	2.5	ECEA0GKS470()	200 2000
	100	5	5	61	0.35	0.45	2.0	5.0	2.5	ECEA0GKS101()	200 2000
	220	6.3	5	82	0.35	0.45	2.5	5.0	2.5	ECEA0GKS221()	200 2000
6.3	22	4	5	29	0.24	0.45	1.5	5.0	2.5	ECEA0JKS220()	200 2000
	33	5	5	38	0.24	0.45	2.0	5.0	2.5	ECEA0JKS330()	200 2000
	47	5	5	46	0.24	0.45	2.0	5.0	2.5	ECEA0JKS470()	200 2000
	100	6.3	5	71	0.24	0.45	2.5	5.0	2.5	ECEA0JKS101()	200 2000
	330	8	5	130	0.24	0.45	2.5		2.5	ECEA0JKS331()	200 1000
		8	5	130	0.24	0.45		5.0		ECEA0JKS331Q	1000
10	22	5	5	35	0.20	0.45	2.0	5.0	2.5	ECEA1AKS220()	200 2000
	33	5	5	43	0.20	0.45	2.0	5.0	2.5	ECEA1AKS330()	200 2000
	47	6.3	5	65	0.20	0.45	2.5	5.0	2.5	ECEA1AKS470()	200 2000
	100	6.3	5	80	0.20	0.45	2.5	5.0	2.5	ECEA1AKS101()	200 2000
	220	8	5	120	0.20	0.45	2.5		2.5	ECEA1AKS221()	200 1000
		8	5	120	0.20	0.45		5.0		ECEA1AKS221Q	1000
16	10	3	5	20	0.16	0.40	1.0	5.0	2.5	ECEA1CKK100()	200 2000
		4	5	28	0.16	0.45	1.5	5.0	2.5	ECEA1CKS100()	200 2000
	22	5	5	39	0.16	0.45	2.0	5.0	2.5	ECEA1CKS220()	200 2000
	33	6.3	5	60	0.16	0.45	2.5	5.0	2.5	ECEA1CKS330()	200 2000
	47	6.3	5	70	0.16	0.45	2.5	5.0	2.5	ECEA1CKS470()	200 2000
	100	8	5	91	0.16	0.45	2.5		2.5	ECEA1CKS101()	200 1000
		8	5	91	0.16	0.45		5.0		ECEA1CKS101Q	1000
25	2.2	3	5	8	0.14	0.40	1.0	5.0	2.5	ECEA1EKK2R2()	200 2000
	3.3	3	5	10	0.14	0.40	1.0	5.0	2.5	ECEA1EKK3R3()	200 2000
	4.7	3	5	12	0.14	0.40	1.0	5.0	2.5	ECEA1EKK4R7()	200 2000
		4	5	22	0.14	0.45	1.5	5.0	2.5	ECEA1EKS4R7()	200 2000
	10	5	5	28	0.14	0.45	2.0	5.0	2.5	ECEA1EKS100()	200 2000
	22	6.3	5	55	0.14	0.45	2.5	5.0	2.5	ECEA1EKS220()	200 2000
	33	6.3	5	65	0.14	0.45	2.5	5.0	2.5	ECEA1EKS330()	200 2000
	100	8	5	85	0.14	0.45	2.5		2.5	ECEA1EKS101()	200 2000
		8	5	85	0.14	0.45		5.0		ECEA1EKS101Q	1000
35	3.3	4	5	16	0.12	0.45	1.5	5.0	2.5	ECEA1VKS3R3()	200 2000
	4.7	4	5	22	0.12	0.45	1.5	5.0	2.5	ECEA1VKS4R7()	200 2000
	10	5	5	30	0.12	0.45	2.0	5.0	2.5	ECEA1VKS100()	200 2000
	22	6.3	5	60	0.12	0.45	2.5	5.0	2.5	ECEA1VKS220()	200 2000
	33	8	5	65	0.12	0.45	2.5		2.5	ECEA1VKS330()	200 1000
		8	5	65	0.12	0.45		5.0		ECEA1VKS330Q	1000
	47	8	5	85	0.12	0.45	2.5		2.5	ECEA1VKS470()	200 1000
		8	5	85	0.12	0.45		5.0		ECEA1VKS470Q	1000
50	0.1	3	5	1	0.10	0.40	1.0	5.0	2.5	ECEA1HKK0R1()	200 2000
		4	5	1	0.10	0.45	1.5	5.0	2.5	ECEA1HKS0R1()	200 2000

When requesting taped product, please put the letter "B" or "i" between the "()". Lead wire pitch B=5mm, i=2.5mm.
The taping dimensions are explained on p.188 of our Catalog. Please use it as a reference guide.
Endurance : 85°C 1000h

Design, and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and / or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

■ Standard Products

W.V. (V)	Cap. (±20%) (μF)	Case size		Specification		Lead Length			Part No.	Min. Packaging Q'ty	
		Dia. (mm)	Length (mm)	Ripple current (120Hz) (+85°C) (mA)	tan δ (120Hz) (+20°C)	Lead Dia. (mm)	Lead Space			Straight Leads (pcs)	Taping (pcs)
							Straight	Taping ※B	Taping ※i		
50	0.22	3	5	2	0.10	0.40	1.0	5.0	2.5	ECEA1HKKR22()	200 2000
		4	5	2	0.10	0.45	1.5	5.0	2.5	ECEA1HKSR22()	200 2000
	0.33	3	5	3	0.10	0.40	1.0	5.0	2.5	ECEA1HKKR33()	200 2000
		4	5	3	0.10	0.45	1.5	5.0	2.5	ECEA1HKSR33()	200 2000
	0.47	3	5	5	0.10	0.40	1.0	5.0	2.5	ECEA1HKKR47()	200 2000
		4	5	5	0.10	0.45	1.5	5.0	2.5	ECEA1HKSR47()	200 2000
	1	3	5	8	0.10	0.40	1.0	5.0	2.5	ECEA1HKK010()	200 2000
		4	5	10	0.10	0.45	1.5	5.0	2.5	ECEA1HKS010()	200 2000
	2.2	4	5	16	0.10	0.45	1.5	5.0	2.5	ECEA1HKS2R2()	200 2000
	3.3	4	5	16	0.10	0.45	1.5	5.0	2.5	ECEA1HKS3R3()	200 2000
	4.7	5	5	23	0.10	0.45	2.0	5.0	2.5	ECEA1HKS4R7()	200 2000
	10	6.3	5	35	0.10	0.45	2.5	5.0	2.5	ECEA1HKS100()	200 2000
	22	8	5	60	0.10	0.45	2.5		2.5	ECEA1HKS220()	200 1000
		8	5	60	0.10	0.45		5.0		ECEA1HKS220Q	1000

When requesting taped product, please put the letter "B" or "i" between the "()". Lead wire pitch B=5mm, i=2.5mm.
 The taping dimentions are explained on p.188 of our Catalog. Please use it as a reference guide.
 Endurance : 85°C 1000h