


EP13 Series

- EPO™ Programmable Oscillators
- 3.3V supply voltage
- 8 pin DIP package
- HCMOS output
- Stability to 50ppm
- Custom lead length, gull wing options available



NOTES

ELECTRICAL SPECIFICATIONS

Frequency Range		1.000MHz to 106.250MHz
Operating Temperature Range		-20°C to 70°C or -40°C to 85°C
Storage Temperature Range		-55°C to 125°C
Supply Voltage (V_{DD})		3.3V _{DC} ±0.3V _{DC}
Input Current		28mA Maximum (Unloaded)
Disable Current (TS Option)		16mA Maximum (Pin 1=Ground)
Standby Current (PD Option)		20uA Maximum (Pin 1=Ground)
Frequency Tolerance / Stability	Inclusive of Operating Temp Range, Supply Voltage, and Load	±100ppm or ±50ppm Maximum
Output Voltage Logic High (V_{OH})	w/HCMOS Load	V_{DD} -0.4V _{DC} Minimum I_{OH} =-8mA
Output Voltage Logic Low (V_{OL})	w/HCMOS Load	0.4V _{DC} Maximum I_{OL} =+8mA
Rise Time / Fall Time	20% to 80% of waveform w/HCMOS Load	4 nSeconds Maximum
Duty Cycle	at 50% of waveform w/HCMOS Load	50 ±10% (Standard)
	at 50% of waveform w/HCMOS Load (≤50.000MHz Only)	50 ±5% (Optional)
Load Drive Capability	≤50.000MHz	30pF HCMOS Load Maximum
	>50.000MHz	15pF HCMOS Load Maximum
Pin 1 Connection	TS	Tri-State
	PD	Power Down
Pin 1 Input Voltage	V_{IH} : No Connection or ≥70% of V_{DD}	Enables Output
	V_{IL} : (TS Option) ≤20% of V_{DD}	Disable Output: High Impedance
	V_{IL} : (PD Option) ≤20% of V_{DD}	Disable Output: Logic Low
Aging (at 25°C)		±5ppm / year Maximum
Start Up Time		10 mSeconds Maximum
Period Jitter: Absolute	≤33.000MHz	±250pSec Max, ±100pSec Typical
	>33.000MHz	±125pSec Max, ±75pSec Typical
Period Jitter: One Sigma	≤33.000MHz	±50pSeconds Maximum
	>33.000MHz	±40pSeconds Maximum

MANUFACTURER
ECLIPTEK CORP.

CATEGORY
OSCILLATOR

SERIES
EP13

PACKAGE
8 pin DIP

VOLTAGE
3.3V

CLASS
OS45

REV. DATE
06/00

PART NUMBERING GUIDE

EP13 00 HS ET TS - 24.000M - CL125 TR

FREQUENCY TOLERANCE / STABILITY

00=±100ppm Maximum (Standard)
45=±50ppm Maximum

PACKAGE

HS=Half Size 8 Pin DIP

OPERATING TEMP. RANGE

Blank=-20°C to 70°C or ET=-40°C to 85°C

DUTY CYCLE

Blank=50 ±10(%) (Standard), T=50 ±5(%)

PACKAGING OPTIONS

Blank=Bulk (Standard)
TR=Tape & Reel (only offered with
Half Size G and Half Size G2 options)

AVAILABLE OPTIONS


Blank=None (Standard)
CLXXX=Custom Lead Length (See Page 123)
G=Half Size Gull Wing (See Page 122)
G2=Half Size Gull Wing (See Page 122)

FREQUENCY


PIN 1 CONNECTION

TS=Tri-State, PD=Power Down

MECHANICAL DIMENSIONS ALL DIMENSIONS IN MILLIMETERS



TAPE AND REEL DIMENSIONS ALL DIMENSIONS IN MILLIMETERS



MARKING SPECIFICATIONS

Line 1: ECLIPTEK

Line 2: EP13 TS

Pin 1 Connection
PD = Power Down
TS = Tri-State Enable High
Series Designator

Line 3: XX.XXX M

Frequency in MHz
(5 Digits Maximum + Decimal)

Line 4: XX Y ZZ

Week of Year
Last Digit of Year
Eclipse Manufacturing Identifier

Note: Pin 1 shall be designated with a dot

ENVIRONMENTAL/MECHANICAL SPECIFICATIONS

Characteristic	Specification
Seal Integrity	Bubble test in Perfluorocarbon at +125°C ±5°C for 60 seconds minimum.
Solderability	Sn63 Solder dip at +230°C ±5°C for 5 seconds/95% coverage.
Marking Permanency	10 Strokes with brush after 1 minute soak in solvent, 3 times.
Shock	Random drop on hard wooden plate 3 times from a height of 20cm.
Vibration	Frequency with an amplitude of 1.5mm sweeping between 10Hz to 55Hz within 1 minute (approximately) for 2 hours minimum on each axis (X, Y and Z) for a total of 6 hours.

MANUFACTURER
ECLIPTEK CORP.

CATEGORY
OSCILLATOR

SERIES
EP13

PACKAGE
8 pin DIP

VOLTAGE
3.3V

CLASS
OS45

REV. DATE
06/00