

15 W DC-DC CONVERTER FOR ECL

Type	V _{in}	V _{out}	I _{out}
GS15T5-5.2	5 V	5,2 V	3 A

DESCRIPTION

The GS15T5-5.2 is a 15W DC-DC converter designed to provide a 5.2V isolated output from a 5V input.

The device can operate with an output current in the range of 0.0 to 3.0A without any intermittent operation (packet switching).


It offers short-circuit protection and input-output isolation of 750V_{DC} minimum. The integral heatsink allows a large power handling capability and it provides also an effective shielding to minimize EMI.



ELECTRICAL CHARACTERISTICS (T_{amb.} = 25° C unless otherwise specified)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V _i	Input Voltage	V _o = 5.2V I _o = 0.0 to 3.0A	4.75	5.0	5.35	V
I _{ir}	Input Reflected Current	V _i = 5.0V V _o = 5.2V I _o = 3.0A		40	50	mApp
I _{iq}	Input Quiescent Current	V _i = 5.0V V _o = 5.2V I _o = 0.0A		87	95	mA
V _o	Output Voltage	V _i = 4.75 to 5.25V I _o = 0.0 to 3.0A	5.04	5.2	5.36	V
I _o	Output Current	V _i = 4.75 to 5.25V	0.0		3.0	A
ΔV _{OL}	Line Regulation	V _i = 4.75 to 5.25V I _o = 3.0A		1	10	mV
ΔV _{OO}	Load Regulation	V _i = 5.0V I _o = 0.0 to 3.0A		10	15	mV
V _{or}	Output Ripple Voltage	V _i = 5.0V I _o = 3.0A		20	30	mVpp
V _{or}	Output Ripple Voltage	V _i = 5.0V I _o = 3.0A		8		mV _{RMS}
I _{osc}	Output Short-circuit Current	V _i = 5.0V			4.75	A
V _{is}	Isolation Voltage		750			V _{DC}
f _s	Switching Frequency	V _i = 4.75 to 5.25V I _o = 0.0 to 3.0A		100		kHz
η	Efficiency	V _i = 5.0V I _o = 3.0A	77	79		%
R _{thc}	Thermal Resistance Case to Ambient	T _{amb.} = 25°C V _i = 5.0V I _o = 3.0A		8		°C/W
T _c	Maximum Case Temperature				90	°C
T _{stg}	Storage Temperature Range		- 40		+105	°C

CONNECTION DIAGRAM AND MECHANICAL DATA



USER NOTES

Thermal Characteristics

Worst case power dissipation at full load is less than 5W.

To operate the device at an ambient temperature of 60 °C the thermal resistance case-to-ambient must be lower than 6.5 °C/W.

This can be accomplished by adding an external heatsink or by forced ventilation with air speed of about 100 linear feet/minute.

MTBF Calculations

The MTBF according to MIL HDBK-217E calculation for a ground benign environment is:

- 216k hours for a case temperature of 91 °C.
- 379k hours for a case temperature of 60 °C.

This last condition can be obtained at T_{amb.} = 40 °C and forced ventilation of 100 feet/minute.

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics – All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.