



(16 characters X 1 line)

1.0 DIMENSIONAL DRAWING**2.0 BLOCK DIAGRAM****3.0 MECHANICAL SPECIFICATIONS**

Item	Nominal Dimensions	Unit
Module Size (W X H X T)	80.0 X 36.0 X 14.5(Max.)	mm
Viewing Area (W X H)	64.5 X 13.8	mm
Character Pitch (W)	3.77	mm
Character Size (W X H)	3.07 X 6.56	mm
Character Font	5 X 8 DOTS	-
Dot Pitch (W X H)	0.63 X 0.83	mm
Dot Size (W X H)	0.55 X 0.75	mm

4.0 ELECTRICAL CHARACTERISTICS(T_a=25 °C, V_{DD} = 5.0V±0.25V)

Item	Symbol	Test Condition		Standard Value			Unit
				Min.	Typ.	Max.	
Input High Voltage	V _{IH}	—		2.2	—	V _{DD}	V
Input Low Voltage	V _{IL}	—		−0.3	—	0.6	V
Output High Voltage	V _{OH}	−I _{OH} = 0.2mA		2.4	—	—	V
Output Low Voltage	V _{OL}	I _{OL} = 1.2mA		—	—	0.4	V
Supply Current	I _{DD}	V _{DD} = 5.0V		—	2.0	3.0	mA
Operating Voltage for LCD	V _{DD} − V _O	T _a = 25 °C	(STN)	—	5.0	—	V
			(TN)	—	4.5	—	V