
HD151005

Octal Inverter Buffers/Drivers With Open Drain High Voltage Outputs

HITACHI

ADE-205-594 (Z)
1st. Edition
Dec. 2000


Description

The HD151005 features octal inverter buffers and drivers with open drain high voltage outputs with N channel power MOSFET.

Features

- Wired connection available with open drain outputs
- Output voltage: 30 V Max
- Output current: 100 mA Max
- Ensures V_{OL} 0.4 V when the output current is 48 mA
- Low power dissipation: 10 μ A

Pin Arrangement



Function Table

Inputs		Outputs		Inputs		Outputs	
OEA	A	YA		OEB	B	YB	
H	L	Z		H	L	Z	
H	H	L		H	H	L	
L	X	Z		L	X	Z	

H : High level
L : Low level
Z : High impedance
X : Irrelevant

Absolute Maximum Ratings ($T_a = 25^{\circ}\text{C}$)

Item	Symbol	Ratings	Unit
Supply voltage	V_{CC}	0.5 to 7.0	V
Input voltage	V_{IN}	-0.5 to $V_{CC} + 0.5$	V
Input Current	I_{IN}	-10 to $+0.1$	mA
Output voltage	V_{OUT}	-0.5 to $+30$	V
Output Current	I_{OUT}	$+100$	mA/Unit
Power Dissipation	P_T	835 (FP), 1375 (DP)	mW
Storage Temperature Range	Tstg	-65 to $+150$	$^{\circ}\text{C}$

Note: 1. The absolute maximum ratings are values which must not individually be exceeded, and furthermore, no two of which may be realized at the same time.

Recommended Operating Conditions

Item	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	4.5	5.0	5.5	V
Input Voltage	V_{IN}	0	—	V_{CC}	V
Output Voltage	V_{OUT}	—	—	24	V
Output Current	I_{OL}	0	48	100	mA
Operating Temperature	Topr	0	25	70	$^{\circ}\text{C}$
Input Voltage	V_{IH}	$0.7 \times V_{CC}$	—	—	V
	V_{IL}	—	—	$0.3 \times V_{CC}$	V
Input Rise and Fall Time *1	t_r, t_f	0	—	500	ns

Note: 1. This item guarantees maximum limit when one input switches.
Waveform: Refer to test circuit of switching characteristics.


Electrical Characteristics (Ta = 0 to +70°C)

Item	Symbol	V _{CC} (V)	Min	Max	Unit	Conditions
Output voltage	V _{OL1}	4.5	—	0.2	V	I _{OL} = 24 mA, V _I = V _{IH}
	V _{OL2}	4.5	—	0.4	V	I _{OL} = 48 mA, V _I = V _{IH}
	V _{OL3}	4.5	—	0.8	V	I _{OL} = 100 mA, V _I = V _{IH}
Output Current	I _O	5.5	—	5	μA	V _O = 30 V, V _I = 0 V
	I _{O(off)}	0	—	5	μA	V _O = 30 V
Input voltage	V _{IH}	5.0	3.5	—	V	V _O = 0.4 V, I _O ≥ 48 mA
	V _{IL}	5.0	—	1.5	V	V _O = 30 V, I _O ≤ 5 mA
Input Current	I _I	5.5	—	±1	μA	V _I = 0 V or V _{CC}
	I _{I(off)}	0	—	±1	μA	V _I = 5.5 V
Power Supply Current	I _{CC}	5.5	—	10	μA	V _I = 0 V or V _{CC} , No Load


Switching Characteristics (Ta = 25°C, V_{CC} = 5 V)

Item	Symbol	Min	Typ	Max	Unit	Conditions
Propagation Delay Time	t _{ZL}	—	15	30	ns	See next page
	t _{LZ}	—	20	30	ns	See next page
Transition Time	t _{THL}	—	10	30	ns	See next page
	t _{TLH}	—	15	30	ns	See next page
Input Capacitance	C _{IN}	—	7	15	pF	See next page
Power Dissipation Capacitance	C _{PD}	—	30	—	pF	See next page

Test Circuit




Waveforms-1




Package Dimensions

Unit: mm



Hitachi Code	DP-20N
JEDEC	—
EIAJ	Conforms
Mass (reference value)	1.26 g

Unit: mm



*Dimension including the plating thickness
Base material dimension

Hitachi Code	FP-20DA
JEDEC	—
EIAJ	Conforms
Mass (reference value)	0.31 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohite-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL	North America	: http://semiconductor.hitachi.com/
	Europe	: http://www.hitachi-eu.com/hel/ecg
	Asia	: http://sicapac.hitachi-asia.com
	Japan	: http://www.hitachi.co.jp/Sicd/indx.htm

For further information write to:

Hitachi Semiconductor (America) Inc. 179 East Tasman Drive, San Jose, CA 95134 Tel: <1> (408) 433-1990 Fax: <1> (408) 433-0223	Hitachi Europe GmbH Electronic Components Group Dornacher Straße 3 D-85622 Feldkirchen, Munich Germany Tel: <49> (89) 9 9180-0 Fax: <49> (89) 9 29 30 00
	Hitachi Europe Ltd. Electronic Components Group. Whitebrook Park Lower Cookham Road Maidenhead Berkshire SL6 8YA, United Kingdom Tel: <44> (1628) 585000 Fax: <44> (1628) 585160

Hitachi Asia Ltd. Hitachi Tower 16 Collyer Quay #20-00, Singapore 049318 Tel: <65>-538-6533/538-8577 Fax: <65>-538-6933/538-3877 URL: http://www.hitachi.com.sg	Hitachi Asia Ltd. (Taipei Branch Office) 4/F, No. 167, Tun Hwa North Road, Hung-Kuo Building, Taipei (105), Taiwan Tel: <886>-(2)-2718-3666 Fax: <886>-(2)-2718-8180 Telex: 23222 HAS-TP URL: http://www.hitachi.com.tw
---	---

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon,
Hong Kong
Tel: <852>-(2)-735-9218
Fax: <852>-(2)-730-0281
URL: <http://www.hitachi.com.hk>

Copyright © Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.
Colophon 2.0

HITACHI