




HBT134I

TRIAC

Description

Passivated, sensitive gate triacs in a plastic envelope, intended for use in general purpose bidirectional switching and phase control applications, where high sensitivity is required in all four quadrants.



Quick Reference Data

Symbol	Parameter	Max.	Unit
V_{DRM}	Repetitive peak off-state voltages	600	V
$I_{T(RMS)}$	RMS on-state current	4	A
I_{TSM}	Non-repetitive peak on-state current	25	A

Pin Configuration

Pin	Description	tab	Symbol
1	Main terminal 1		
2	Main terminal 2		
3	Gate		
tab	Main terminal 2		

Limiting Values

Symbol	Parameter	Min.	Max.	Units
V_{DRM}	Repetitive peak off-state voltages	-	600	V
$I_{T(RMS)}$	RMS on-state current	-	4	A
I_{TSM}	Non-repetitive peak on-state current	-	25	A
I^2t	I^2t for fusing	-	3.1	A ² S
dI_T/dt	Repetitive rate of rise of on-state current after triggering T2+ G+	-	50	A/us
	T2+ G-	-	50	A/us
	T2- G-	-	50	A/us
	T2- G+	-	10	A/us
I_{GM}	Peak gate current	-	2	A
V_{GM}	Peak gate voltage	-	5	V
P_{GM}	Peak gate power	-	5	W
$P_{G(AV)}$	Average gate power	-	0.5	W
T_{stg}	Storage Temperature Range	-	150	°C
T_j	Operating junction temperature	-	125	°C



Static Characteristics (Ta=25°C)

Symbol	Parameter	Conditions	HBT134I			Unit
			Min.	Typ.	Max.	
I_{GT}	Gate Trigger Current	$V_D=12V, I_G=0.1A, T2+ G+$	-	5	10	mA
		$V_D=12V, I_G=0.1A, T2+ G-$	-	6	10	mA
		$V_D=12V, I_G=0.1A, T2- G-$	-	6	10	mA
		$V_D=12V, I_G=0.1A, T2- G+$	-	18	25	mA
I_L	Latching Current	$V_D=12V, I_{GT}=0.1A, T2+ G+$	-	-	15	mA
		$V_D=12V, I_{GT}=0.1A, T2+ G-$	-	-	20	mA
		$V_D=12V, I_{GT}=0.1A, T2- G-$	-	-	15	mA
		$V_D=12V, I_{GT}=0.1A, T2- G+$	-	-	20	mA
I_H	Holding Current	$V_D=12V, I_{GT}=0.1A$	-	6	15	mA
V_T	On-state Voltage	$I_T=5A$	-	1.4	1.70	V
V_{GT}	Gate Trigger Voltage	$V_D=12V, I_T=0.1A$	-	0.8	1.5	V
I_D	Off-state Leakage Current	$V_D=V_{DRM}$	-	-	200	uA

Static Characteristics







Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
dV_D/dt	Critical rate of rise of off-state voltage	$V_{DM}=67\% V_{DRM(max)}$; $T_j=125^\circ C$; exponential waveform; gate open circuit	-	50	-	V/us
t_{gt}	Gate controlled turn-on time	$I_{TM}=6A$; $V_D=V_{DRM(max)}$; $I_G=0.1A$; $dI_G/dt=5A/us$	-	2	-	us

Thermal Resistances

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
R th j-mb	Thermal resistance junction to mounting base	Full cycle	-	-	3.0	K/W
R th j-a	Thermal resistance junction to ambient	Half cycle	-	-	3.7	K/W
		In free air	-	60	-	K/W




Characteristics Curve






TO-251 Dimension



3-Lead TO-251 Plastic Package
HSMC Package Code: I

Marking:



Style: Pin 1. Main terminal 1
2. Main terminal 2

3. Gate

Tab connected to main terminal 2

*: Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.0177	0.0217	0.45	0.55	G	0.2559	-	6.50	-
B	0.0354	0.0591	0.90	1.50	H	-	*0.1811	-	*4.60
C	0.0177	0.0236	0.45	0.60	I	-	0.0354	-	0.90
D	0.0866	0.0945	2.20	2.40	J	-	0.0315	-	0.80
E	0.2520	0.2677	6.40	6.80	K	0.2047	0.2165	5.20	5.50
F	0.2677	0.2835	6.80	7.20					

Notes: 1.Dimension and tolerance based on our Spec. dated May. 24,1995.
2.Controlling dimension: millimeters.
3.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
4.If there is any question with packing specification or packing method, please contact your local HSMC sales office.

Material:

- Lead: 42 Alloy ; solder plating
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of HSMC.
- HSMC reserves the right to make changes to its products without notice.
- **HSMC semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- HSMC assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory :

- **Head Office** (Hi-Sincerity Microelectronics Corp.): 10F.,No. 61, Sec. 2, Chung-Shan N. Rd. Taipei Taiwan R.O.C.
Tel: 886-2-25212056 Fax: 886-2-25632712, 25368454
- **Factory 1** : No. 38, Kuang Fu S. Rd., Fu-Kou Hsin-Chu Industrial Park Hsin-Chu Taiwan. R.O.C
Tel: 886-3-5983621~5 Fax: 886-3-5982931