
HM5164805 Series

HM5165805 Series

64 M EDO DRAM (8-Mword $\times$ 8-bit)
8 k Refresh/4 k Refresh

HITACHI

ADE-203-808B (Z)
Rev. 1.0
Feb. 27, 1998

Description

The Hitachi HM5164805 Series, HM5165805 Series are 64M-bit dynamic RAMs organized as 8,388,608-word $\times$ 8-bit. They have realized high performance and low power by employing CMOS process technology. HM5164805 Series, HM5165805 Series offer Extended Data Out (EDO) Page Mode as a high speed access mode. They have the package variation of standard 32-pin plastic SOJ and standard 32-pin plastic TSOPII.

Features

- Single 3.3 V supply: 3.3 V $\pm$ 0.3 V
- Access time: 50 ns/60 ns (max)
- Power dissipation
 - Active: 414 mW/378 mW (max) (HM5164805 Series)
: 486 mW/414 mW (max) (HM5165805 Series)
 - Standby: 1.8 mW (max) (CMOS interface)
: 0.54 mW (max) (L-version)
- EDO page mode capability
- Refresh cycles
 - $\overline{\text{RAS}}$ -only refresh
 - 8192 cycles /64 ms (HM5164805)
/128 ms (HM5164805L) (L-version)
 - 4096 cycles /64 ms (HM5165805)
/128 ms (HM5165805L) (L-version)

HM5164805 Series, HM5165805 Series


- CBR/Hidden refresh
4096 cycles /64 ms (HM5164805, HM5165805)
/128 ms (HM5164805L, HM5165805L) (L-version)
- 4 variations of refresh
 - $\overline{\text{RAS}}$ -only refresh
 - $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh
 - Hidden refresh
 - Self refresh (L-version)
- Battery backup operation (L-version)

Ordering Information

Type No.	Access time	Package
HM5164805J-5	50 ns	400-mil 32-pin plastic SOJ (CP-32DC)
HM5164805J-6	60 ns	
HM5164805LJ-5	50 ns	
HM5164805LJ-6	60 ns	
HM5165805J-5	50 ns	
HM5165805J-6	60 ns	
HM5165805LJ-5	50 ns	
HM5165805LJ-6	60 ns	
HM5164805TT-5	50 ns	400-mil 32-pin plastic TSOP II (TTP-32DC)
HM5164805TT-6	60 ns	
HM5164805LTT-5	50 ns	
HM5164805LTT-6	60 ns	
HM5165805TT-5	50 ns	
HM5165805TT-6	60 ns	
HM5165805LTT-5	50 ns	
HM5165805LTT-6	60 ns	

HM5164805 Series, HM5165805 Series

Pin Arrangement (HM5164805 Series)




Pin Description

Pin name	Function
A0 to A12	Address input - Row/Refresh address A0 to A12 - Column address A0 to A9
I/O0 to I/O7	Data input/output
$\overline{\text{RAS}}$	Row address strobe
$\overline{\text{CAS}}$	Column address strobe
$\overline{\text{WE}}$	Write enable
$\overline{\text{OE}}$	Output enable
V _{CC}	Power supply
V _{SS}	Ground
NC	No connection

HM5164805 Series, HM5165805 Series


Pin Arrangement (HM5165805 Series)



Pin Description


Pin name	Function
A0 to A11	Address input - Row/Refresh address A0 to A11 - Column address A0 to A10
I/O0 to I/O7	Data input/output
$\overline{\text{RAS}}$	Row address strobe
$\overline{\text{CAS}}$	Column address strobe
$\overline{\text{WE}}$	Write enable
$\overline{\text{OE}}$	Output enable
V _{CC}	Power supply
V _{SS}	Ground
NC	No connection

Block Diagram (HM5164805 Series)



HM5164805 Series, HM5165805 Series

Block Diagram (HM5165805 Series)



HM5164805 Series, HM5165805 Series

Operation Table

$\overline{RAS}$	$\overline{CAS}$	$\overline{WE}$	$\overline{OE}$	I/O 0 to I/O 7	Operation
H	×	×	×	High-Z	Standby
L	L	H	L	Dout	Read cycle
L	L	L^{*2}	×	Din	Early write cycle
L	L	L^{*2}	H	Din	Delayed write cycle
L	L	H to L	L to H	Dout/Din	Read-modify-write cycle
L	H	×	×	High-Z	$\overline{RAS}$ -only refresh cycle
H to L	L	H	×	High-Z	$\overline{CAS}$ -before- $\overline{RAS}$ refresh cycle or Self refresh cycle (L-version)
L	L	H	H	High-Z	Read cycle (Output disabled)

Notes: 1. H: V_{IH} (inactive), L: V_{IL} (active), ×: V_{IH} or V_{IL}

2. $t_{WCS} \geq 0$ ns: Early write cycle

$t_{WCS} < 0$ ns: Delayed write cycle

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Terminal voltage on any pin relative to V_{SS}	V_T	-0.5 to $V_{CC} + 0.5$ (≤ 4.6 V (max))	V
Power supply voltage relative to V_{SS}	V_{CC}	-0.5 to $+4.6$	V
Short circuit output current	I_{out}	50	mA
Power dissipation	P_T	1.0	W
Storage temperature	Tstg	-55 to $+125$	°C

DC Operating Conditions

Parameter	Symbol	Min	Typ	Max	Unit	Notes
Supply voltage	V_{CC}	3.0	3.3	3.6	V	1, 2
	V_{SS}	0	0	0	V	2
Input high voltage	V_{IH}	2.0	—	$V_{CC} + 0.3$	V	1
Input low voltage	V_{IL}	-0.3	—	0.8	V	1
Ambient temperature range	Ta	0	—	70	°C	

Notes: 1. All voltage referred to V_{SS} .

2. The supply voltage with all V_{CC} pins must be on the same level. The supply voltage with all V_{SS} pins must be on the same level.

HM5164805 Series, HM5165805 Series

DC Characteristics (HM5164805 Series)

		HM5164805					
		-5		-6			
Parameter	Symbol	Min	Max	Min	Max	Unit	Test conditions
Operating current ^{*1, *2}	I _{CC1}	—	115	—	105	mA	t _{RC} = min
Standby current	I _{CC2}	—	2	—	2	mA	TTL interface RAS, CAS = V _{IH} Dout = High-Z
		—	0.5	—	0.5	mA	CMOS interface RAS, CAS ≥ V _{CC} − 0.2 V Dout = High-Z
Standby current (L-version)	I _{CC2}	—	150	—	150	μA	CMOS interface RAS, CAS ≥ V _{CC} − 0.2 V Dout = High-Z
RAS-only refresh current ^{*2}	I _{CC3}	—	115	—	105	mA	t _{RC} = min
Standby current ^{*1}	I _{CC5}	—	5	—	5	mA	RAS = V _{IH} , CAS = V _{IL} Dout = enable
CAS-before-RAS refresh current	I _{CC6}	—	115	—	105	mA	t _{RC} = min
EDO page mode current ^{*1, *3}	I _{CC7}	—	110	—	100	mA	RAS = V _{IL} , CAS cycle, t _{HPC} = t _{HPC} min
Battery backup current ^{*4} (Standby with CBR refresh) (L-version)	I _{CC10}	—	500	—	500	μA	CMOS interface Dout = High-Z CBR refresh: t _{RC} = 31.3 μs t _{RAS} ≥ 0.3 μs
Self refresh mode current (L-version)	I _{CC11}	—	400	—	400	μA	CMOS interface RAS, CAS ≤ 0.2 V Dout = High-Z
Input leakage current	I _{LI}	−5	5	−5	5	μA	0 V ≤ Vin ≤ V _{CC} + 0.3 V
Output leakage current	I _{LO}	−5	5	−5	5	μA	0 V ≤ Vout ≤ V _{CC} Dout = disable
Output high voltage	V _{OH}	2.4	V _{CC}	2.4	V _{CC}	V	High Iout = −2 mA
Output low voltage	V _{OL}	0	0.4	0	0.4	V	Low Iout = 2 mA

Notes: 1. I_{CC} depends on output load condition when the device is selected. I_{CC} max is specified at the output open condition.

2. Address can be changed once or less while $\overline{RAS} = V_{IL}$.

3. Measured with one sequential address change per EDO cycle, t_{HPC} .

4. $V_{IH} \geq V_{CC} - 0.2 V$, $0 V \leq V_{IL} \leq 0.2 V$.

HM5164805 Series, HM5165805 Series

DC Characteristics (HM5165805 Series)

		HM5165805					
		-5		-6			
Parameter	Symbol	Min	Max	Min	Max	Unit	Test conditions
Operating current ^{*1, *2}	I _{CC1}	—	135	—	115	mA	t _{RC} = min
Standby current	I _{CC2}	—	2	—	2	mA	TTL interface RAS, CAS = V _{IH} Dout = High-Z
		—	0.5	—	0.5	mA	CMOS interface RAS, CAS ≥ V _{CC} − 0.2 V Dout = High-Z
Standby current (L-version)	I _{CC2}	—	150	—	150	μA	CMOS interface RAS, CAS ≥ V _{CC} − 0.2 V Dout = High-Z
RAS-only refresh current ^{*2}	I _{CC3}	—	135	—	115	mA	t _{RC} = min
Standby current ^{*1}	I _{CC5}	—	5	—	5	mA	RAS = V _{IH} , CAS = V _{IL} Dout = enable
CAS-before-RAS refresh current	I _{CC6}	—	135	—	115	mA	t _{RC} = min
EDO page mode current ^{*1, *3}	I _{CC7}	—	110	—	100	mA	RAS = V _{IL} , CAS cycle, t _{HPC} = t _{HPC} min
Battery backup current ^{*4} (Standby with CBR refresh) (L-version)	I _{CC10}	—	500	—	500	μA	CMOS interface Dout = High-Z CBR refresh: t _{RC} = 31.3 μs t _{RAS} ≤ 0.3 μs
Self refresh mode current (L-version)	I _{CC11}	—	400	—	400	μA	CMOS interface RAS, CAS ≤ 0.2 V Dout = High-Z
Input leakage current	I _{LI}	−5	5	−5	5	μA	0 V ≤ Vin ≤ V _{CC} + 0.3 V
Output leakage current	I _{LO}	−5	5	−5	5	μA	0 V ≤ Vout ≤ V _{CC} Dout = disable
Output high voltage	V _{OH}	2.4	V _{CC}	2.4	V _{CC}	V	High Iout = −2 mA
Output low voltage	V _{OL}	0	0.4	0	0.4	V	Low Iout = 2 mA

Notes: 1. I_{CC} depends on output load condition when the device is selected. I_{CC} max is specified at the output open condition.

2. Address can be changed once or less while $\overline{RAS} = V_{IL}$.

3. Measured with one sequential address change per EDO cycle, t_{HPC} .

4. $V_{IH} \geq V_{CC} - 0.2 V$, $0 V \leq V_{IL} \leq 0.2 V$.

HM5164805 Series, HM5165805 Series

Capacitance ($T_a = 25^\circ\text{C}$, $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$)

Parameter	Symbol	Typ	Max	Unit	Notes
Input capacitance (Address)	C_{i1}	—	5	pF	1
Input capacitance (Clocks)	C_{i2}	—	7	pF	1
Output capacitance (Data-in, Data-out)	$C_{i/o}$	—	7	pF	1, 2

Notes : 1. Capacitance measured with Boonton Meter or effective capacitance measuring method.

2. $\overline{\text{RAS}}$ and $\overline{\text{CAS}} = V_{IH}$ to disable Dout.

HM5164805 Series, HM5165805 Series

AC Characteristics ($T_a = 0$ to $+70^\circ\text{C}$, $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$, $V_{SS} = 0\text{ V}$) *¹, *², *¹⁹

Test Conditions

- Input rise and fall time: 2 ns
- Input pulse levels: $V_{IL} = 0\text{ V}$, $V_{IH} = 3.0\text{ V}$
- Input timing reference levels: 0.8 V, 2.0 V
- Output timing reference levels: 0.8 V, 2.0 V
- Output load: 1 TTL gate + C_L (100 pF) (Including scope and jig)

Read, Write, Read-Modify-Write and Refresh Cycles (Common parameters)

		HM5164805/HM5165805					
Parameter	Symbol	-5		-6		Unit	Notes
		Min	Max	Min	Max		
Random read or write cycle time	t _{RC}	84	—	104	—	ns	
$\overline{\text{RAS}}$ precharge time	t _{RP}	30	—	40	—	ns	
$\overline{\text{CAS}}$ precharge time	t _{CP}	8	—	10	—	ns	
$\overline{\text{RAS}}$ pulse width	t _{RAS}	50	10000	60	10000	ns	
$\overline{\text{CAS}}$ pulse width	t _{CAS}	8	10000	10	10000	ns	
Row address setup time	t _{ASR}	0	—	0	—	ns	
Row address hold time	t _{RAH}	8	—	10	—	ns	
Column address setup time	t _{ASC}	0	—	0	—	ns	
Column address hold time	t _{CAH}	8	—	10	—	ns	
$\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ delay time	t _{RCD}	12	37	14	45	ns	3
$\overline{\text{RAS}}$ to column address delay time	t _{RAD}	10	25	12	30	ns	4
$\overline{\text{RAS}}$ hold time	t _{RSH}	13	—	15	—	ns	
$\overline{\text{CAS}}$ hold time	t _{CSH}	35	—	40	—	ns	
$\overline{\text{CAS}}$ to $\overline{\text{RAS}}$ precharge time	t _{CRP}	5	—	5	—	ns	
$\overline{\text{OE}}$ to Din delay time	t _{OED}	13	—	15	—	ns	5
$\overline{\text{OE}}$ delay time from Din	t _{DZO}	0	—	0	—	ns	6
$\overline{\text{CAS}}$ delay time from Din	t _{DZC}	0	—	0	—	ns	6
Transition time (rise and fall)	t _T	2	50	2	50	ns	7

HM5164805 Series, HM5165805 Series

Read Cycle

		HM5164805/HM5165805					
		-5		-6			
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
Access time from $\overline{\text{RAS}}$	t_{RAC}	—	50	—	60	ns	8, 9
Access time from $\overline{\text{CAS}}$	t_{CAC}	—	13	—	15	ns	9, 10, 17
Access time from address	t_{AA}	—	25	—	30	ns	9, 11, 17
Access time from $\overline{\text{OE}}$	t_{OEA}	—	13	—	15	ns	9
Read command setup time	t_{RCS}	0	—	0	—	ns	
Read command hold time to $\overline{\text{CAS}}$	t_{RCH}	0	—	0	—	ns	12
Read command hold time from $\overline{\text{RAS}}$	t_{RCHR}	50	—	60	—	ns	
Read command hold time to $\overline{\text{RAS}}$	t_{RRH}	0	—	0	—	ns	12
Column address to $\overline{\text{RAS}}$ lead time	t_{RAL}	25	—	30	—	ns	
Column address to $\overline{\text{CAS}}$ lead time	t_{CAL}	15	—	18	—	ns	
$\overline{\text{CAS}}$ to output in low-Z	t_{CLZ}	0	—	0	—	ns	
Output data hold time	t_{OH}	3	—	3	—	ns	21
Output data hold time from $\overline{\text{OE}}$	t_{OHO}	3	—	3	—	ns	
Output buffer turn-off time	t_{OFF}	—	13	—	15	ns	13, 21
Output buffer turn-off to $\overline{\text{OE}}$	t_{OEZ}	—	13	—	15	ns	13
$\overline{\text{CAS}}$ to Din delay time	t_{CDD}	13	—	15	—	ns	5
Output data hold time from $\overline{\text{RAS}}$	t_{OHR}	3	—	3	—	ns	21
Output buffer turn-off to $\overline{\text{RAS}}$	t_{OFR}	—	13	—	15	ns	13, 21
Output buffer turn-off to $\overline{\text{WE}}$	t_{WEZ}	—	13	—	15	ns	13
$\overline{\text{WE}}$ to Din delay time	t_{WED}	13	—	15	—	ns	
$\overline{\text{RAS}}$ to Din delay time	t_{RDD}	13	—	15	—	ns	

HM5164805 Series, HM5165805 Series

Write Cycle

		HM5164805/HM5165805					
		-5	-6				
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
Write command setup time	t _{WCS}	0	—	0	—	ns	14
Write command hold time	t _{WCH}	8	—	10	—	ns	
Write command pulse width	t _{WP}	8	—	10	—	ns	
Write command to $\overline{RAS}$ lead time	t _{RWL}	13	—	15	—	ns	
Write command to $\overline{CAS}$ lead time	t _{CWL}	8	—	10	—	ns	
Data-in setup time	t _{DS}	0	—	0	—	ns	15
Data-in hold time	t _{DH}	8	—	10	—	ns	15

Read-Modify-Write Cycle

		HM5164805/HM5165805					
		-5		-6			
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
Read-modify-write cycle time	t _{RWC}	116	—	140	—	ns	
$\overline{\text{RAS}}$ to $\overline{\text{WE}}$ delay time	t _{RWD}	67	—	79	—	ns	14
$\overline{\text{CAS}}$ to $\overline{\text{WE}}$ delay time	t _{CWD}	30	—	34	—	ns	14
Column address to $\overline{\text{WE}}$ delay time	t _{AWD}	42	—	49	—	ns	14
$\overline{\text{OE}}$ hold time from $\overline{\text{WE}}$	t _{OEH}	13	—	15	—	ns	

Refresh Cycle

		HM5164805/HM5165805					
		-5	-6				
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
CAS setup time (CBR refresh cycle)	t _{CSR}	5	—	5	—	ns	
CAS hold time (CBR refresh cycle)	t _{CHR}	8	—	10	—	ns	
WE setup time (CBR refresh cycle)	t _{WRP}	0	—	0	—	ns	
WE hold time (CBR refresh cycle)	t _{WRH}	8	—	10	—	ns	
RAS precharge to CAS hold time	t _{RPC}	5	—	5	—	ns	

HM5164805 Series, HM5165805 Series

EDO Page Mode Cycle

		HM5164805/HM5165805					
		-5		-6			
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
EDO page mode cycle time	t _{HPC}	20	—	25	—	ns	20
EDO page mode $\overline{RAS}$ pulse width	t _{RASP}	—	100000	—	100000	ns	16
Access time from $\overline{CAS}$ precharge	t _{CPA}	—	28	—	35	ns	9, 17
$\overline{RAS}$ hold time from $\overline{CAS}$ precharge	t _{CPRH}	28	—	35	—	ns	
Output data hold time from $\overline{CAS}$ low	t _{DOH}	3	—	3	—	ns	9, 22
$\overline{CAS}$ hold time referred $\overline{OE}$	t _{COL}	8	—	10	—	ns	
$\overline{CAS}$ to $\overline{OE}$ setup time	t _{COP}	5	—	5	—	ns	
Read command hold time from $\overline{CAS}$ precharge	t _{RCHC}	28	—	35	—	ns	
Write pulse width during $\overline{CAS}$ precharge	t _{WPE}	8	—	10	—	ns	
$\overline{OE}$ precharge time	t _{OEP}	8	—	10	—	ns	

EDO Page Mode Read-Modify-Write Cycle

		HM5164805/HM5165805					
		-5		-6			
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
EDO page mode read-modify-write cycle time	t _{HPRWC}	57	—	68	—	ns	
$\overline{WE}$ delay time from $\overline{CAS}$ precharge	t _{CPW}	45	—	54	—	ns	14

Refresh (HM5164805 Series)

Parameter	Symbol	Max	Unit	Notes
Refresh period	t_{REF}	64	ms	8192 cycles
Refresh period (L-version)	t_{REF}	128	ms	8192 cycles

Refresh (HM5165805 Series)

Parameter	Symbol	Max	Unit	Notes
Refresh period	t_{REF}	64	ms	4096 cycles
Refresh period (L-version)	t_{REF}	128	ms	4096 cycles

HM5164805 Series, HM5165805 Series

Self Refresh Mode (L-version)

		HM5164805L/HM5165805L					
		-5		-6			
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
$\overline{\text{RAS}}$ pulse width (self refresh)	t_{RASS}	100	—	100	—	μs	26
$\overline{\text{RAS}}$ precharge time (self refresh)	t_{RPS}	90	—	110	—	ns	26
$\overline{\text{CAS}}$ hold time (self refresh)	t_{CHS}	−50	—	−50	—	ns	


- Notes:
1. AC measurements assume $t_T = 2 \text{ ns}$.
 2. An initial pause of 200 μs is required after power up followed by a minimum of eight initialization cycles (any combination of cycles containing RAS-only refresh or CAS-before-RAS refresh).
 3. Operation with the t_{RCD} (max) limit insures that t_{RAC} (max) can be met, t_{RCD} (max) is specified as a reference point only; if t_{RCD} is greater than the specified t_{RCD} (max) limit, then the access time is controlled exclusively by t_{CAC} .
 4. Operation with the t_{RAD} (max) limit insures that t_{RAC} (max) can be met, t_{RAD} (max) is specified as a reference point only; if t_{RAD} is greater than the specified t_{RAD} (max) limit, then access time is controlled exclusively by t_{AA} .
 5. Either t_{OED} or t_{CDD} must be satisfied.
 6. Either t_{DZO} or t_{DZC} must be satisfied.
 7. V_{IH} (min) and V_{IL} (max) are reference levels for measuring timing of input signals. Also, transition times are measured between V_{IH} (min) and V_{IL} (max).
 8. Assumes that $t_{\text{RCD}} \leq t_{\text{RCD}}$ (max) and $t_{\text{RAD}} \leq t_{\text{RAD}}$ (max). If t_{RCD} or t_{RAD} is greater than the maximum recommended value shown in this table, t_{RAC} exceeds the value shown.
 9. Measured with a load circuit equivalent to 1 TTL loads and 100 pF.
 10. Assumes that $t_{\text{RCD}} \geq t_{\text{RCD}}$ (max) and $t_{\text{RCD}} + t_{\text{CAC}}$ (max) $\geq t_{\text{RAD}} + t_{\text{AA}}$ (max).
 11. Assumes that $t_{\text{RAD}} \geq t_{\text{RAD}}$ (max) and $t_{\text{RCD}} + t_{\text{CAC}}$ (max) $\leq t_{\text{RAD}} + t_{\text{AA}}$ (max).
 12. Either t_{RCH} or t_{RRH} must be satisfied for a read cycles.
 13. t_{OFF} (max), t_{OEZ} (max), t_{WEZ} (max) and t_{OFR} (max) define the time at which the outputs achieve the open circuit condition and are not referred to output voltage levels.
 14. t_{WCS} , t_{RWD} , t_{CWD} , t_{AWD} and t_{CPW} are not restrictive operating parameters. They are included in the data sheet as electrical characteristics only; if $t_{\text{WCS}} \geq t_{\text{WCS}}$ (min), the cycle is an early write cycle and the data out pin will remain open circuit (high impedance) throughout the entire cycle; if $t_{\text{RWD}} \geq t_{\text{RWD}}$ (min), $t_{\text{CWD}} \geq t_{\text{CWD}}$ (min), and $t_{\text{AWD}} \geq t_{\text{AWD}}$ (min), or $t_{\text{CWD}} \geq t_{\text{CWD}}$ (min), $t_{\text{AWD}} \geq t_{\text{AWD}}$ (min) and $t_{\text{CPW}} \geq t_{\text{CPW}}$ (min), the cycle is a read-modify-write and the data output will contain data read from the selected cell; if neither of the above sets of conditions is satisfied, the condition of the data out (at access time) is indeterminate.
 15. t_{DS} and t_{DH} are referred to $\overline{\text{CAS}}$ leading edge in early write cycles and to $\overline{\text{WE}}$ leading edge in delayed write or read-modify-write cycles.
 16. t_{RASP} defines $\overline{\text{RAS}}$ pulse width in EDO page mode cycles.
 17. Access time is determined by the longest among t_{AA} , t_{CAC} and t_{CPA} .
 18. In delayed write or read-modify-write cycles, $\overline{\text{OE}}$ must disable output buffer prior to applying data to the device.
 19. When output buffers are enabled once, sustain the low impedance state until valid data is obtained. When output buffer is turned on and off within a very short time, generally it causes large $V_{\text{CC}}/V_{\text{SS}}$ line noise, which causes to degrade V_{IH} min/ V_{IL} max level.

HM5164805 Series, HM5165805 Series


20. t_{HPC} (min) can be achieved during a series of EDO page mode write cycles or EDO page mode read cycles. If both write and read operation are mixed in a EDO page mode $\overline{RAS}$ cycle (EDO page mode mix cycle (1), (2)), minimum value of $\overline{CAS}$ cycle ($t_{CAS} + t_{CP} + 2 t_T$) becomes greater than the specified t_{HPC} (min) value. The value of $\overline{CAS}$ cycle time of mixed EDO page mode is shown in EDO page mode mix cycle (1) and (2).
21. Data output turns off and becomes high impedance from later rising edge of $\overline{RAS}$ and $\overline{CAS}$. Hold time and turn off time are specified by the timing specifications of later rising edge of $\overline{RAS}$ and $\overline{CAS}$ between t_{OHR} and t_{OH} and between t_{OFF} and t_{OFF} .
22. t_{DOH} defines the time at which the output level go cross. $V_{OL} = 0.8 V$, $V_{OH} = 2.0 V$ of output timing reference level.
23. Before and after self refresh mode, execute CBR refresh to all refresh addresses in or within 64 ms period on the condition a and b below.
- Enter self refresh mode within 15.6 μs after either burst refresh or distributed refresh at equal interval to all refresh addresses are completed.
 - Start burst refresh or distributed refresh at equal interval to all refresh addresses within 15.6 μs after exiting from self refresh mode.
24. In case of entering from $\overline{RAS}$ -only-refresh, it is necessary to execute CBR refresh before and after self refresh mode according as note 23.
25. For L-version, it is available to apply each 128 ms and 31.2 μs instead of 64 ms and 15.6 μs at note 23.
26. At $t_{RASS} > 100 \mu s$, self refresh mode is activated, and not activated at $t_{RASS} < 10 \mu s$. It is undefined within the range of $10 \mu s \leq t_{RASS} \leq 100 \mu s$. For $t_{RASS} \geq 10 \mu s$, it is necessary to satisfy t_{RPS} .
27. XXX: H or L (H: $V_{IH} (\min) \leq V_{IN} \leq V_{IH} (\max)$, L: $V_{IL} (\min) \leq V_{IN} \leq V_{IL} (\max)$)
/////: Invalid Dout
When the address, clock and input pins are not described on timing waveforms, their pins must be applied V_{IH} or V_{IL} .

HM5164805 Series, HM5165805 Series

Early Write Cycle




Delayed Write Cycle*¹⁸




HM5164805 Series, HM5165805 Series

Read-Modify-Write Cycle^{*18}




$\overline{\text{RAS}}$ -Only Refresh Cycle




HM5164805 Series, HM5165805 Series

$\overline{\text{CAS}}$ -Before- $\overline{\text{RAS}}$ Refresh Cycle




Hidden Refresh Cycle




HM5164805 Series, HM5165805 Series

EDO Page Mode Read Cycle (1)



HM5164805 Series, HM5165805 Series


EDO Page Mode Early Write Cycle






EDO Page Mode Read-Modify-Write Cycle*¹⁸





HM5164805 Series, HM5165805 Series

Self Refresh Cycle (L-version)* 23, 24, 25, 26




HM5164805 Series, HM5165805 Series

Package Dimensions

HM5164805J/ LJ Series

HM5165805J/ LJ Series (CP-32DC)

Unit: mm




Dimension including the plating thickness
Base material dimension

Hitachi Code	CP-32DC
JEDEC	—
EIAJ	Conforms
Weight (reference value)	1.2 g

HM5164805 Series, HM5165805 Series

HM5164805TT/LTT Series
HM5165805TT/LTT Series (TTP-32DC)



HM5164805 Series, HM5165805 Series

When using this document, keep the following in mind:

1. This document may, wholly or partially, be subject to change without notice.
2. All rights are reserved: No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without Hitachi's permission.
3. Hitachi will not be held responsible for any damage to the user that may result from accidents or any other reasons during operation of the user's unit according to this document.
4. Circuitry and other examples described herein are meant merely to indicate the characteristics and performance of Hitachi's semiconductor products. Hitachi assumes no responsibility for any intellectual property claims or other problems that may result from applications based on the examples described herein.
5. No license is granted by implication or otherwise under any patents or other rights of any third party or Hitachi, Ltd.
6. **MEDICAL APPLICATIONS:** Hitachi's products are not authorized for use in MEDICAL APPLICATIONS without the written consent of the appropriate officer of Hitachi's sales company. Such use includes, but is not limited to, use in life support systems. Buyers of Hitachi's products are requested to notify the relevant Hitachi sales offices when planning to use the products in MEDICAL APPLICATIONS.

HITACHI

Hitachi, Ltd.

Semiconductor & IC Div.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100, Japan
Tel: Tokyo (03) 3270-2111
Fax: (03) 3270-5109

For further information write to:

Hitachi America, Ltd.
Semiconductor & IC Div.
2000 Sierra Point Parkway
Brisbane, CA. 94005-1835
U S A
Tel: 415-589-8300
Fax: 415-583-4207

Hitachi Europe GmbH
Electronic Components Group
Continental Europe
Dornacher Straße 3
D-85622 Feldkirchen
München
Tel: 089-9 91 80-0
Fax: 089-9 29 30 00

Hitachi Europe Ltd.
Electronic Components Div.
Northern Europe Headquarters
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA
United Kingdom
Tel: 0628-585000
Fax: 0628-778322

Hitachi Asia Pte. Ltd.
16 Collyer Quay #20-00
Hitachi Tower
Singapore 0104
Tel: 535-2100
Fax: 535-1533

Hitachi Asia (Hong Kong) Ltd.
Unit 706, North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon
Hong Kong
Tel: 27359218
Fax: 27306071

HM5164805 Series, HM5165805 Series

Revision Record

Rev.	Date	Contents of Modification	Drawn by	Approved by
0.0	Jul. 23, 1997	Initial issue	J. Miyake	M. Saeki
0.1	Nov. 1997	Change of Subtitle Timing waveforms Correct errors of EDO mix cycle (1)	J. Miyake	Y. Takahashi
1.0	Feb. 27, 1998	Deletion of Preliminary		