


HIGH VOLTAGE RECTIFIER ASSEMBLIES, Standard Recovery

ISI Part Number	Average Rectified Current at T _a =50°C	Peak Reverse Voltage	Max Forward Voltage @ Rated I _a and T _a =25°C	Peak Forward Surge Current @ 8.3ms Superimposed	Max Reverse Current @ Rated PIV & T _a =25°C	Max Reverse Current @ Rated PIV & T _a =100°C	Case Dimensions (Inches)			Outline		
	I _o (mA)	PRV (Volts)	V _{rr} (Volts)	I _{rrs} (Amps)	I _r (uA)	I _r (uA)	L	D (H)	W			
HVD08 HVD10 HVD12 HVD15 HVD20 HVD25 HVD30 HVD35 HVD40	25	8,000 10,000 12,000 15,000 20,000 25,000 30,000 35,000 40,000	30 60 90	3.0	1.0	40	1.0 2.0 3.1	0.260 0.305		 H.V. Cartridge		
HVC08 HVC10 HVC12 HVC15 HVC20 HVC25 HVC30 HVC35 HVC40 HVC45 HVC50		13 13 13 20 26 33 40 46 53 60 66	1.00 1.00 1.00 1.63 2.13 2.63 3.13 3.63 4.13 4.63 5.13									
HVHC08 HVHC10 HVHC12 HVHC15 HVHC20 HVHC25 HVHC30 HVHC35 HVHC40 HVHC45 HVHC50		12 15 18 24 30 38 45 54 60 70 76	10				2.0				100	1.00 1.25 1.50 2.00 2.50 2.50 3.00 3.75 4.00 5.00 6.25 6.25
HV5 HV7.5 HV10 HV12.5 HV15 HV20 HV25 HV30		6 9 12 15 17 22 28 34										1.00 1.63 2.00 2.50 2.50 3.20 4.50 4.50
HVA25 HVA28 HVA210 HVA212 HVA215	5,000 8,000 10,000 12,000 15,000	6 11 13 15 18		50	1.0	100		3.00 3.00 3.00 3.00 3.00	0.75			0.75
HVA15 HVA18 HVA110 HVA112 HVA115	5,000 8,000 10,000 12,000 15,000	6 11 13 15 18						3.00 3.00 3.00 3.00 3.00				