Intel[®] Media Switch IXE5416 16-port Gigabit Device

Product Description

The Intel® Media Switch IXE5416 16-port Gigabit Device facilitates the design of high port density, high-performance, and mediaready 10/100/1000 switching systems. The IXE5416 is a single-chip 16-port Gigabit device for Layer 2 and Layer 3 Gigabit Ethernet switching and routing. The IXE5416 enables you to design systems that deliver high-bandwidth applications at wire speed for voice, video and data to the desktop.

The IXE5416 supports wire-speed switching and IP routing, along with traffic classification, Quality of Service (QoS), filtering, and prioritization based on Layer 2/3/4 information. The IXE5416 offers non-blocking performance on all ports, switching packets at the rate of 24 Mpps (64-byte packet size).

This device is suited for standalone switch/routers and stackable solutions when combined with other Intel Media Switch Devices—offering solutions for workgroup, enterprise, campus backbone switching/routing, Storage Area Networks, and edge-to-core router interconnects. A CPU and physical interfaces/transceivers are the only additional components you need to deliver a wire-speed 16-port Gigabit Ethernet switch/router with classification, prioritization and guaranteed



bandwidth. Optional Intel® Media Switch IXE5417 Content-Addressable Memory (CAM) device is available for extending the address table size.


Applications

Key applications for the the IXE5416 include:

- 16–24 port Gigabit Layer 2 workgroup switch
- 16–24 port Gigabit Layer 2/3/4 workgroup switch
- Daisy chain or Star stackable 10/100/1000
 Layer 2/3/4 switch
- High port count Layer 2/3/4 switch/router solution suitable for stackable and chassis switches. (Can be incorporated into stacking solutions with the Intel® Media Switch IXE2424 10/100+Gigabit L2/3/4 Advanced Device)



developer.intel.com



Features	Benefits	
■ Single-chip, 16-port Gigabit switch/router with Layer 2/3/4 support	 High integration, compact footprint, and low power dissipation enable the design of high port density systems at low per-port cost 	
■ Integrated 10/100/1000 Ethernet MACs	■ Enables easy migration from 10/100 to Gigabit	
 Wire-speed performance across all ports in switching or IP routing modes 	 Delivers congestion-free performance through enterprise switches during peak load periods 	
■ Link aggregation	 Enables meshed configurations with redundant paths for fail-safe networks 	
 Advanced traffic prioritization, QoS, and bandwidth management capabilities Enables the convergence of voice, video, and traffic over Ethernet/IP networks 		
 VLAN support according to IEEE 802.1Q standards, ports, and protocol 	 Enables flat plug-and-play networks that are easy to maintain 	
 Advanced multicast, broadcast, and filtering capabilities 	 Enables video and voice multicasting over IP networks Protects from broadcast storms Enables high-performance intranet firewalls 	

Support Collateral/Tools

Item	Description	Order Number
Manuals	Intel® Media Switch IXE5416 16-port Gigabit Switch Device Developer's Manual	Contact local sales rep
	 Intel® Media Switch IXE5417 Content-Addressable Memory Developer's Manual 	Contact local sales rep

Intel in Communications

Intel is a leading supplier of communications building blocks, adding value at many levels of integration. Through continuous innovation and advancements in Ethernet connectivity and processing in the network, Intel is delivering, along with its customers and developer community, a wide choice of solutions that enable faster time-to-market, longer time-in-market, and increased revenue opportunity.

Intel Access

Developer's Site	http://developer.intel.com
Networking Components Home Page	http://developer.intel.com/design/network
Other Intel Support: Intel Literature Center	http://developer.intel.com/design/litcentr (800) 548-4725 7 a.m. to 7 p.m. CST (U.S. and Canada) International locations please contact your local sales office.
General Information Hotline	(800) 628-8686 or (916) 356-3104 5 a.m. to 5 p.m. PST



*Other brands and names are the property of their respective owners.
Intel and the Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right. Intel products are not intended for use in medical, life-saving or life-sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice.

Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

UNITED STATES AND CANADA EUROPE Intel Corporation Robert Noyce Bldg. 2200 Mission College Blvd. P.O. Box 58119 Santa Clara, CA 95052-8119 UK LISA

Intel Corporation (UK) Ltd. Pipers Way Swindon Wiltshire SN3 1RJ

ASIA-PACIFIC Intel Semiconductor Ltd. 32/F Two Pacific Place 88 Queensway, Central Hong Kong

IAPAN Tokodai Tsukuba-shi 300-2635 Ibaraki-ken

SOUTH AMERICA Intel Japan (Tsukuba HQ) Intel Semicondutores do Brasil Ltda Av. Dr. Chucri Zaidan, 940-10° andar 04583-904 São Paulo, SP Brazil