

Single Event Radiation Hardened High Speed, Current Mode PWM



The IS-1845ASRH is designed to be used in switching power supplies operating in current-mode. The rising edge of the on-chip oscillator


turns on the output. Turn-off is controlled by the current sense comparator and occurs when the sensed current reaches a peak controlled by the error amplifier. The error amplifier output is the difference between the sampled voltage and V_{REF} .

Constructed with Intersil's Rad Hard Silicon Gate (RSG) dielectrically isolated BiCMOS process, these devices are immune to single event latch-up and have been specifically designed to provide a high level of immunity to single event transients. All specified parameters are guaranteed and tested for 300krad(Si) total dose performance.


Detailed Electrical Specifications for these devices are contained in SMD 5962-01509. A "hot-link" is provided on our homepage for downloading the SMD.
www.intersil.com/spacedefense/spacenewprod.asp

Pinout

IS7-1845ASRH (CDIP2-T8 SBDIP)
TOP VIEW



IS9-1845ASRH (FLATPACK)
TOP VIEW



NOTE: Grounding the Comp pin does not inhibit the output. The output may be inhibited by applying $>1.2V$ to the ISENSE pin.

Features

- Electrically Screened to DSCC SMD # 5962-01509
- QML Qualified per MIL-PRF-38535 Requirements
- Radiation Environment
 - Total Dose 300 krad(Si) (Max)
 - SEL Immune Dielectrically Isolated
 - SEU Immune 35MeV/mg/cm²
 - SEU Cross-Section at 89MeV/mg/cm² 5 x 10⁻⁶cm²
- Low Start-up Current 100μA (Typ)
- Fast Propagational Delay 80ns (Typ)
- Supply Voltage Range 12V to 20V
- High Output Drive 1A (Peak, Typ)
- Under Voltage Lockout. . 8.8V Start (Typ), 8.2V Stop (Typ)
- 2.5V Voltage Reference (VREF)
- Switching Frequencies to 500kHz

Applications

- Current-Mode Switching Power Supplies
- Control of High Current FET Drivers
- Motor Speed and Direction Control

Ordering Information

ORDERING NUMBER	INTERNAL MKT. NUMBER	TEMP. RANGE (°C)
5962F0150901VPC	IS7-1845ASRH-Q	-50 to 125
5962F0150901QPC	IS7-1845ASRH-8	-50 to 125
5962F0150901VXC	IS9-1845ASRH-Q	-50 to 125
5962F0150901QXC	IS9-1845ASRH-8	-50 to 125
IS7-1845ASRH/Proto	IS1-1845ASRH/Proto	-50 to 125
IS9-1845ASRH/Proto	IS9-1845ASRH/Proto	-50 to 125

Die Characteristics

DIE DIMENSIONS

3090 μ m x 4080 μ m (121.6 mils x 159.0 mils)
Thickness: 483 μ m \pm 25.4 μ m (19 mils \pm 1 mil)

INTERFACE MATERIALS

Glassivation

Type: Phosphorus Silicon Glass (PSG)
Thickness: 8.0kÅ \pm 1.0kÅ

Top Metallization

Type: AlSiCu
Thickness: 16.0kÅ \pm 2kÅ

Substrate

Radiation Hardened Silicon Gate,
Dielectric Isolation

Backside Finish

Silicon

ASSEMBLY RELATED INFORMATION

Substrate Potential

Unbiased (DI)

ADDITIONAL INFORMATION


Worst Case Current Density

$<2.0 \times 10^5$ A/cm²

Transistor Count

582

Metallization Mask Layout



NOTES:

1. Both the GND pads must be bonded to ground.
2. The OUT double-sized bond pad must be double bonded for current sharing purposes.
3. The OSCGND double-sized bond pad must be double bonded to ground for current sharing purposes.

All Intersil products are manufactured, assembled and tested utilizing ISO9000 quality systems.

Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com

Sales Office Headquarters

NORTH AMERICA

Intersil Corporation
7585 Irvine Center Drive
Suite 100
Irvine, CA 92618
TEL: (949) 341-7000
FAX: (949) 341-7123

Intersil Corporation
2401 Palm Bay Rd.
Palm Bay, FL 32905
TEL: (321) 724-7000
FAX: (321) 724-7946

EUROPE

Intersil Europe Sarl
Ave. C - F Ramuz 43
CH-1009 Pully
Switzerland
TEL: +41 21 7293637
FAX: +41 21 7293684

ASIA

Intersil Corporation
Unit 1804 18/F Guangdong Water Building
83 Austin Road
TST, Kowloon Hong Kong
TEL: +852 2723 6339
FAX: +852 2730 1433