


SP4T SWITCH WITH DIRECT TTL CONTROL AND SINGLE POSITIVE SUPPLY ITT401AC

ADVANCED INFORMATION

FEATURES

- Single Positive Supply (+8V)
- Direct TTL input
- On-Chip Decoder Logic
- Low Power Consumption
- Non-Reflective Ports



DESCRIPTION

This is a low-loss SP4T, single-supply switch in a narrow body SOIC-14 lead package. The switch can be controlled using direct TTL logic and incorporates an on-chip 2:4 decoder.

MAXIMUM RATINGS (T_A = 25 °C unless otherwise noted)

Rating	Symbol	Value	Unit
RF input power	J _{1,2,3}		
Control Voltage	V _{1,2}		
Junction Temperature	T _J	+150	°C
Storage Temperature	T _{STG}	-40 to +150	°C

ELECTRICAL SPECIFICATIONS AT 25 DEGREES C

Parameter	Frequency	Min.	Typ.	Max.	Unit
Insertion Loss	DC-0.5 GHz		0.8	1.1	dB
	DC-1.0 GHz		1.0	1.4	dB
	DC-2.0 GHz		1.3	1.6	dB
Isolation	DC-0.5 GHz	40	43		dB
	DC-1.0 GHz	34	37		dB
	DC-2.0 GHz	24	27		dB
VSWR	DC-0.5 GHz		1.3:1	1.5:1	
	DC-1.0 GHz		1.5:1	1.7:1	
	DC-2.0GHz		1.7:1	1.9:1	

OPERATING CHARACTERISTICS AT 25 DEGREES C

Parameter	Condition	Freq.	Min.	Typ.	Max.	Unit
Switching Characteristics	Rise, Fall (10/90% or 90/10% RF)			15		nS
	On, Off (50% CTL to 90/10% RF)			35		nS
	Video Feedthru			30		mV
Input Power for 1 dB Compression		0.50-3.0 GHz		+24		dBm
		0.05 GHz		+16		dBm
Intermodulation Intercept Point (IP3)	For Two-tone Input Power +5 dBm	0.50-3.0 GHz		+40		V
		0.05 GHz		+29		V



Advanced Information - Specifications Subject to Change Without Notice

902394 --, March 1999



GaAsTEK
5310 Valley Park Drive
Roanoke, VA 24019 USA
www.gaastek.com
Tel: 1-540-563-3949
1-888-563-3949 (USA)
Fax: 1-540-563-8616