

June, 1998 Preliminary

AMI 0.6 micron CMOS
Single Poly

Comparator


Schematic Symbol

Description

PECL input comparator cell. Receives 5v PECL input levels. Digital model is designed for a differential input.

TRUTH TABLE

PD	PADM	VREF	QC
1	X	X	0
0	0	0	X
0	0	1	0
0	1	0	1
0	1	1	X



PIN DESCRIPTION

NAME	TYPE	DESCRIPTION
PADM	Analog input	Positive Comparator Input
VREF	Analog input	Negative Comparator Input
PD	Digital input	Power Down Input
QC	Digital output	Comparator Output
AVDD	Analog supply	VDD
AVSS	Analog supply	VSS

AC ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITION	MIN	TYP	MAX	UNITS
delay	Propagation delay	1.95pf load		2.25		ns
T	Temperature		-40	25	85	°C
Vdd	Supply Voltage		4.5		5.5	V
Ivdd	Supply Current		3.8	7.0	12.1	mA
GBW	Gain Bandwidth		650	1247	2130	MHz
Gain	DC Gain		61	76	85	dB
Vos	Input Offset		-7.5	-1.2	2.2	mV
CMR	Input Common Mode Range		1.75	2.5	3.5	V
Voh	Output high		VDD			V
Vol	Output low				VSS	V



IBEXX3

June, 1998 Preliminary

**AMI 0.6 micron CMOS
Single Poly**

Cload	Capacitive load		0.046	1.17	2.34	pf
-------	-----------------	--	-------	------	------	----