


# HiPerFAST™ IGBT


**IXSH 24N60**  
**IXSH 24N60A**

| $V_{CES}$ | $I_{C25}$ | $V_{CE(sat)}$ |
|-----------|-----------|---------------|
| 600 V     | 48 A      | 2.2 V         |
| 600 V     | 48 A      | 2.7 V         |

## Short Circuit SOA Capability



TO-247 AD



G = Gate, C = Collector,  
E = Emitter, TAB = Collector

| Symbol  | Test Conditions  | Maximum Ratings                  |                  |  |
|---|--|----------------------------------|------------------|--|
| $V_{CES}$   | $T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$  | 600                              | V                |  |
| $V_{CGR}$   | $T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$ ; $R_{GE} = 1 \text{ M}\Omega$   | 600                              | V                |  |
| $V_{GES}$   | Continuous   | $\pm 20$                         | V                |  |
| $V_{GEM}$   | Transient  | $\pm 30$                         | V                |  |
| $I_{C25}$   | $T_C = 25^\circ\text{C}$   | 48                               | A                |  |
| $I_{C90}$   | $T_C = 90^\circ\text{C}$   | 24                               | A                |  |
| $I_{CM}$  | $T_C = 25^\circ\text{C}$ , 1 ms  | 96                               | A                |  |
| <b>SSOA<br/>(RBSOA)</b>   | $V_{GE} = 15 \text{ V}$ , $T_J = 125^\circ\text{C}$ , $R_G = 10 \Omega$<br>Clamped inductive load, $L = 100 \mu\text{H}$ | $I_{CM} = 48$<br>@ 0.8 $V_{CES}$ | A                |  |
| <b>t<sub>sc</sub><br/>(SCSOA)</b>   | $V_{GE} = 15 \text{ V}$ , $V_{CE} = 360 \text{ V}$ , $T_J = 125^\circ\text{C}$<br>$R_G = 82 \Omega$ , non repetitive     | 10                               | $\mu\text{s}$    |  |
| $P_c$   | $T_C = 25^\circ\text{C}$   | 150                              | W                |  |
| $T_J$   |  | -55 ... +150                     | $^\circ\text{C}$ |  |
| $T_{JM}$  |  | 150                              | $^\circ\text{C}$ |  |
| $T_{stg}$   |  | -55 ... +150                     | $^\circ\text{C}$ |  |
| $M_d$   | Mounting torque  | 1.13/10                          | Nm/lb.in.        |  |
| <b>Weight</b>   |  | 6                                | g                |  |
| Maximum lead temperature for soldering<br>1.6 mm (0.062 in.) from case for 10 s |  | 300                              | $^\circ\text{C}$ |  |

| Symbol        | Test Conditions  | Characteristic Values                                    |      |                           |
|---------------|--|--|------|---------------------------|
|               |  | ( $T_J = 25^\circ\text{C}$ , unless otherwise specified) |      |                           |
|               |  | min.   | typ. | max.                      |
| $BV_{CES}$    | $I_C = 250 \mu\text{A}$ , $V_{GE} = 0 \text{ V}$       | 600  |      | V                         |
| $V_{GE(th)}$  | $I_C = 1.5 \text{ mA}$ , $V_{CE} = V_{GE}$             | 3.5  |      | 6.5 V                     |
| $I_{CES}$     | $V_{CE} = 0.8 \cdot V_{CES}$<br>$V_{GE} = 0 \text{ V}$ | $T_J = 25^\circ\text{C}$<br>$T_J = 125^\circ\text{C}$    |      | 200 $\mu\text{A}$<br>1 mA |
| $I_{GES}$     | $V_{CE} = 0 \text{ V}$ , $V_{GE} = \pm 20 \text{ V}$   |  |      | $\pm 100$ nA              |
| $V_{CE(sat)}$ | $I_C = I_{C90}$ , $V_{GE} = 15 \text{ V}$              | IXSH 24N60<br>IXSH 24N60A                                |      | 2.2 V<br>2.7 V            |

## Features

- International standard package JEDEC TO-247 AD
- High frequency IGBT with guaranteed Short Circuit SOA capability
- 2nd generation HDMOS™ process
- Low  $V_{CE(sat)}$ 
  - for low on-state conduction losses
- MOS Gate turn-on
  - drive simplicity

## Applications


- AC motor speed control
- DC servo and robot drives
- DC choppers
- Uninterruptible power supplies (UPS)
- Switch-mode and resonant-mode power supplies

## Advantages

- Easy to mount with 1 screw (isolated mounting screw hole)
- Switching speed for high frequency applications
- High power density

| Symbol       | Test Conditions  | Characteristic Values                                    |      |      |      |
|--------------|--|--|------|------|------|
|              |  | ( $T_J = 25^\circ\text{C}$ , unless otherwise specified) | min. | typ. | max. |
| $g_{fs}$     | $I_C = I_{C90}$ ; $V_{GE} = 10 \text{ V}$ ,<br>Pulse test, $t \leq 300 \mu\text{s}$ , duty cycle $\leq 2 \%$   | 9  | 13   | S    |      |
| $I_{C(on)}$  | $V_{GE} = 15 \text{ V}$ , $V_{CE} = 10 \text{ V}$  |  | 65   | A    |      |
| $C_{ies}$    | $V_{CE} = 25 \text{ V}$ , $V_{GE} = 0 \text{ V}$ , $f = 1 \text{ MHz}$   | 1800   |      | pF   |      |
| $C_{oes}$    |  | 160  |      | pF   |      |
| $C_{res}$    |  | 45   |      | pF   |      |
| $Q_g$        | $I_C = I_{C90}$ , $V_{GE} = 15 \text{ V}$ , $V_{CE} = 0.5 V_{CES}$   | 75   | 90   | nC   |      |
| $Q_{ge}$     |  | 20   | 30   | nC   |      |
| $Q_{gc}$     |  | 35   | 50   | nC   |      |
| $t_{d(on)}$  | <b>Inductive load, <math>T_J = 25^\circ\text{C}</math></b><br>$I_C = I_{C90}$ , $V_{GE} = 15 \text{ V}$ , $L = 100 \mu\text{H}$ ,<br>$V_{CE} = 0.8 V_{CES}$ , $R_G = 10 \Omega$  | 100  |      | ns   |      |
| $t_{ri}$     |  | 200  |      | ns   |      |
| $t_{d(off)}$ |  | 450  |      | ns   |      |
| $t_{fi}$     |  | 24N60  | 500  | ns   |      |
|              |  | 24N60A   | 275  | ns   |      |
| $E_{off}$    |  | 24N60A   | 2.0  | mJ   |      |
| $t_{d(on)}$  | <b>Inductive load, <math>T_J = 125^\circ\text{C}</math></b><br>$I_C = I_{C90}$ , $V_{GE} = 15 \text{ V}$ , $L = 100 \mu\text{H}$ ,<br>$V_{CE} = 0.8 V_{CES}$ , $R_G = 10 \Omega$ | 100  |      | ns   |      |
| $t_{ri}$     |  | 200  |      | ns   |      |
| $E_{on}$     |  | 1.2  |      | mJ   |      |
| $t_{d(off)}$ |  | 475  |      | ns   |      |
| $t_{fi}$     |  | 24N60  | 600  | ns   |      |
| $E_{off}$    |  | 24N60A   | 450  | ns   |      |
|              |  | 24N60  | 4    | mJ   |      |
|              |  | 24N60A   | 3    | mJ   |      |
| $R_{thJC}$   |  |  |      | 0.83 | K/W  |
| $R_{thCK}$   |  |  | 0.25 |      | K/W  |

TO-247 AD (IXSH) Outline



| Dim. | Millimeter<br>Min. | Millimeter<br>Max. | Inches<br>Min. | Inches<br>Max. |
|------|--------------------|--------------------|----------------|----------------|
| A    | 19.81              | 20.32              | 0.780          | 0.800          |
| B    | 20.80              | 21.46              | 0.819          | 0.845          |
| C    | 15.75              | 16.26              | 0.610          | 0.640          |
| D    | 3.55               | 3.65               | 0.140          | 0.144          |
| E    | 4.32               | 5.49               | 0.170          | 0.216          |
| F    | 5.4                | 6.2                | 0.212          | 0.244          |
| G    | 1.65               | 2.13               | 0.065          | 0.084          |
| H    | -                  | 4.5                | -              | 0.177          |
| J    | 1.0                | 1.4                | 0.040          | 0.055          |
| K    | 10.8               | 11.0               | 0.426          | 0.433          |
| L    | 4.7                | 5.3                | 0.185          | 0.209          |
| M    | 0.4                | 0.8                | 0.016          | 0.031          |
| N    | 1.5                | 2.49               | 0.087          | 0.102          |