



A-3形外壳尺寸



B-6形外壳尺寸



技术参数:

△工作电压:	7-30Vdc
△最大波纹:	10%
△空载电流:	10mA
△电压降:	1.5V
△工作温度:	-25-70°C
△最大温度漂移:	±10%
△重复精度:	2%
△开关迟滞:	10%
△防护等级:	IP67
△开关状态显示	黄色LED
△电缆内芯截面积	0.15mm ² (4线)
	0.22mm ² (3线)
	有
	有
	符合EN60947-5-2
	符合IEC68-2-27IEC68-2-6
材质:	
△电缆:	2m PVC CE120-22II; 90°C;300V;0.R
△传感器:	不锈钢
△感应面:	塑料



直径	M8X1
螺 型号	SW13
母 厚度	4mm
最大扭矩	10Nm

外形类型	齐平	非齐平	L1	L2	L3	L5	电缆直径	外壳直径	感应距离	频率	工作电流	型号及接线图		
			mm	mm	mm	mm	mm	mm	mm	KHz	mA	PNP常开	PNP常闭	PNP常开+常闭
A-3	△		--	45	--	45	3.5	6.5	1.5	4	200	IH06-OPY-F1,5C	IH06-CPY-F1,5C	IH06-RPY-F1,5C
A-3		△	5	40	--	45	3.5	6.5	2.5	3	200	IH06-OPY-N2,5C	IH06-CPY-N2,5C	IH06-RPY-N2,5C
A-3	△		--	45	--	45	3.5	8	1.5	4	200	IH08-OPY-F1,5C	IH08-CPY-F1,5C	IH08-RPY-F1,5C
B-6	△		--	40	5	45	3.5	M8x1	1.5	4	200	IM08-OPY-F1,5C	IM08-CPY-F1,5C	IM08-RPY-F1,5C
B-6		△	--	40	20	60	3.5	M8x1	1.5	4	200	IM08-OPY-F1,5C/Sh/Nl	IM08-CPY-F1,5C/Sh/Nl	IM08-RPY-F1,5C/Sh/Nl
A-3		△	5	40	--	45	3.5	8	2.5	3	200	IH08-OPY-N2,5C	IH08-CPY-N2,5C	IH08-RPY-N2,5C
B-6	△		5	35	5	45	3.5	M8x1	2.5	3	200	IM08-OPY-N2,5C	IM08-CPY-N2,5C	IM08-RPY-N2,5C
B-6		△	5	40	20	65	3.5	M8x1	2.5	3	200	IM08-OPY-N2,5C/Sh/Nl	IM08-CPY-N2,5C/Sh/Nl	IM08-RPY-N2,5C/Sh/Nl
												NPN常开	NPN常闭	NPN常开+常闭
												NPN	NPN	NPN

注:表格中所列型号为PNP型,把中间字母"P"改为"N"即为NPN型