




B-2形外壳尺寸




C形外壳尺寸



D-1形外壳尺寸



H形外壳尺寸



技术参数:

- △工作电压:
- △最大波纹:
- △空载电流:
- △电压降:
- △工作温度:
- △最大温度漂移:
- △重复精度:
- △开关迟滞;
- △防护等级:
- △开关状态显示
- △短路及过载保护:
- △反向连接保护
- △电脉冲抑制(EMC):
- △允许冲击和震动:

材质:

- △传感器:
- △感应面:

7-30Vdc

10%

10mA

1.5V

-25-70°C

±10%

2%

10%

IP67

黄色LED

有

有

符合EN60947-5-2

符合IEC68-2-27IEC68-2-6

不锈钢

塑料




直径	M5x0.5	M8x1
螺 型号	SW7	SW13
母 厚度	2.5mm	4mm
最大扭矩	2Nm	10Nm

外形类型	齐平	非齐平	L1	L2	L3	L4	L5	出线方式	外壳直径	感应距离	频率	工作电流	型号及接线图	
													PNP常开	PNP常闭
			mm	mm	mm	mm	mm		mm	mA	KHz	mA		
I-3	△	--	22	12	5.5	39.5	M8x1接插件	4	1	5	200		IH04-OPY-F001Q8	-----
I-3	△	3	19	12	5.5	39.5	M8x1接插件	4	1.4	5	200		IH04-OPY-N1,4Q8	-----
I-4	△	--	22	12	5.5	39.5	M8x1接插件	M5x0.5	1	5	200		IM05-OPY-F001Q8	-----
I-4	△	3	19	12	5.5	39.5	M8x1接插件	M5x0.5	1.4	5	200		IM05-OPY-N1,4Q8	-----
I-5	△	--	46	--	8	54	M8x1接插件	6.5	1.5	4	200		IH06-OPY-F1,5Q8	IH06-CPY-F1,5Q8
I-5	△	5	41	--	8	54	M8x1接插件	6.5	2.5	3	200		IH06-OPY-N2,5Q8	IH06-CPY-F1,5Q8
I-10	△	--	40	6	8	54	M8x1接插件	M8x1	1.5	4	200		IM08-OPY-F1,5Q8	IM08-CPY-F1,5Q8
I-10	△	5	35	6	8	54	M8x1接插件	M8x1	2.5	3	200		IM08-OPY-N2,5Q8	IM08-CPY-N2,5Q8

注:表格中所列型号为PNP型,把中间字母"P"改为"N"即为NPN型

NPN常开



NPN常闭

