





Surface Mount LED J Series for low current or superbright use, 0678 Series Top LED



The 0678 series lamps are miniature chip type designed for surface mounting. These lamps are the so-called "Top LED" type, measuring approximately 2.8 x 3.6 mm. These lamps are in EIA481 tape and reel packaging with approximately 2000 pcs per reel.



Cathode (except for ISRC0678 & IURC0678
where polarity is reversed)



Recommended
reflow
solder pattern

GENERAL INFORMATION

Operating Temperature Range	-40 °C to +85 °C
Storage Temperature Range	-40 °C to +90 °C
Reflow Soldering Temperature	260 °C for 5 sec max

Part No.	Emitted Color	Peak	$\Delta\lambda$	Absolute Maximum Ratings					E/O Characteristics					
		λ		Pd	If (mA)		Ir	Vr	Iv (mcd) @ If=20mA			Vf (V) @ If=20mA		$2\theta_{1/2}$
		(nm)			dc	1/10 duty @ 1 kHz			2mA	Min	Typ	Min	Typ	
JRC0678	Red	632	20	60	25	160	10	5	4	25	61	2.0	2.4	120
JGC0678	Green	575	20	60	25	160	10	5	1	17	25	2.0	2.4	120
JYC0678	Yellow	591	15	60	25	160	10	5	4	25	62	2.0	2.4	120
JOC0678	Orange	621	18	60	25	160	10	5	4	25	62	2.0	2.4	120
JEC0678	OrRed	639	20	60	25	160	10	5	3	23	49	2.0	2.4	120
JYOC0678	YelOrng	611	17	60	25	160	10	5	4	25	62	2.0	2.4	120

Specifications subject to change without notice. Dimensions are in mm±0.3 unless stated otherwise.

IDEA, Inc., 1300-B Pioneer St., Brea, CA 92821

Ph:562-697-4332, 800-LED-IDEA; Fax: 562-690-1352 013S-J0678