

VARIABLE CAPACITANCE DIODE

FEATURES

- Excellent Linearity (CV Curve)
- large Capacitance Ratio ($A = 2.00$ minimum) with Very Low Series Resistance
- Two Diodes in a Miniature Package (SOT23C-3)
- Very Small Capacitance Deviation at Tape/Reel

APPLICATIONS

- FM Radio
- Voltage Controlled Oscillator

DESCRIPTION

The KV1720R is specially made to be used as a tuning element in radio cassettes, stereos, car radios, and other consumer radios.

The KV1720R minimizes cross modulation, allowing good signal-to-noise ratio in the overall design.

The KV1720R is available in the miniature SOT23C-3 surface mount package.

CLASSIFICATION

(Unit: pF)

C \ RANK		1	2	3	4
C ₂	MIN	41.17	42.33	43.52	44.75
	MAX	42.76	43.96	45.20	46.48

Note: Rank is determined after testing and marked on the reel. All the diodes on a reel have the same rank, but rank can not be specified when ordering.


ORDERING INFORMATION

KV1720R□□

Tape/Reel Code

TAPE/REEL CODE
TL: Tape Left

KV1720R



KV1720R

ABSOLUTE MAXIMUM RATINGS

Reverse Voltage	18V	Storage Temperature Range	-55 to +150 °C
Forward Current	50 mA	Operating Temperature Range	-55 to +85 °C
Power Dissipation	100 mW	Lead Soldering Temperature (10 s)	235 °C

ELECTRICAL CHARACTERISTICS

Test conditions: $T_A = 25\text{ °C}$







SYMBOL	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
V_{REV}	Reverse Voltage	$I_{REV} = 10\text{ }\mu\text{A}$	12			V
I_{REV}	Reverse Current	$V_{REV} = 10\text{ V}$			10	nA
C_2	Diode Capacitance 2	$V_{REV} = 2.0\text{ V}$, $f = 1\text{ MHz}$	41.17		46.48	pF
C_8	Diode Capacitance 8	$V_{REV} = 8.0\text{ V}$, $f = 1\text{ MHz}$	16.00		21.34	pF
R_S	Series Resistance	$V_{REV} = 1.0\text{ V}$, $f = 100\text{ MHz}$			0.3	Ω
A	Capacitance Ratio	C_2 / C_8	2.00		2.60	

Note 1: Diode Capacitance measured with HP 4279A or equivalent instruments (at OSC level 20 mVrms, $\pm 5\text{ mVrms}$).

Note 2: Series Resistance measured with HP 4291B or equivalent instruments.




Note 3: The tolerance of two adjacent parts on a reel is within 3% at C2, C5, and C8.

TYPICAL PERFORMANCE CHARACTERISTICS



PACKAGE OUTLINE

SOT23C-3



Dimensions are shown in millimeters
Tolerance: x.x = ± 0.2 mm (unless otherwise specified)

Marking Information

Product Code C2



Toko America, Inc. Headquarters
1250 Feehanville Drive, Mount Prospect, Illinois 60056
Tel: (847) 297-0070 Fax: (847) 699-7864

TOKO AMERICA REGIONAL OFFICES

Midwest Regional Office
Toko America, Inc.
1250 Feehanville Drive
Mount Prospect, IL 60056
Tel: (847) 297-0070
Fax: (847) 699-7864

Western Regional Office
Toko America, Inc.
2480 North First Street, Suite 260
San Jose, CA 95131
Tel: (408) 432-8281
Fax: (408) 943-9790

Semiconductor Technical Support
Toko Design Center
4755 Forge Road
Colorado Springs, CO 80907
Tel: (719) 528-2200
Fax: (719) 528-2375

Visit our Internet site at <http://www.tokoam.com>

The information furnished by TOKO, Inc. is believed to be accurate and reliable. However, TOKO reserves the right to make changes or improvements in the design, specification or manufacture of its products without further notice. TOKO does not assume any liability arising from the application or use of any product or circuit described herein, nor for any infringements of patents or other rights of third parties which may result from the use of its products. No license is granted by implication or otherwise under any patent or patent rights of TOKO, Inc.