



SINGLE COLOR LED


4mm Round Shape



KR4305S

HIGH BRIGHTNESS COLOR

Outline Dimensions



Absolute Maximum Ratings

(Ta=25°C)

Item	Symbol	Red	Units
		KR	
Power Dissipation	Pd	125	mW
Forward Current	If	50	mA
Peak Forward Current	IFM	300	mA
Reverse Voltage	VR	4	V
Operating Temperature	Topr	-30 to +85	°C
Storage Temperature	Tstg	-30 to +100	°C
Derating (DC)*	If	0.67	mA/°C


* Ta=25°C, IFM applies for the pulse width 1msec, and duty cycle 1/20
The current derating for operation applies when the temperature is above 25°C

Electro-Optical Characteristics

*The viewing angle is an average and will vary by color (Ta=25°C)

Part No.	Material	Emitted Color	Lens Color	Luminous Intensity IV			Wavelength				Forward Voltage VF			Reverse Current IR		Viewing Angle (2 1/2)
				MIN.	TYP.	IF	Peak P TYP.	Dominant d TYP.	Spectral Line Half Width TYP.	IF	TYP.	MAX.	IF	MAX.	VR	
KR4305X	GaAlAs	Red	Water Clear	100	200	20	660	647	25	20	1.8	2.5	20	100	4	30°
Units				mcd		mA	nm				V		mA	μA	V	Deg.

Spatial Distribution (x)



Operation Current Derating Chart

