



NO. : QB/SPS 73 PS 2055A

SPECIFICATIONS

NAME: Φ 1.9 DOT MATRIX

TYPE: LDM0788SRA

**SHENZHEN DITELONG INDUSTRIAL CO.,LTD.
SHENZHEN CANDELA ELECTRONIC CO.,LTD.
SHENZHEN SUCCESS PHOTOELECTRONICS CO.,LTD**

SHENZHEN OFFICE

Add: Room 1911,Zhongwin Science & Techn.Bldg,Bagua 3th Rd.Bagualing Industry Zone Shenzhen,China

Tel: 86-755-25884151

Fax: 86-755-25884659

Post Code: 518029

E-mail: ditelong@asiansources.com

[Http://www.asia_globalsources.com/ditelong.co](http://www.asia_globalsources.com/ditelong.co)

[Http://www.ditelong.com](http://www.ditelong.com)

SHENZHEN FACTORY

Add:4/F Ranbao Bldg,NO. 189 Industrial Zone,Henggang,ShenZhen,china

Tel:86-755-28630148 28630040

Fax:86-755-28631216


Post Code:518115

LDM—0788SRA**1. FEATURES**


- High quality and low cost
- High reliable and intensity
- Low power requirement
- I.C compatible

2. DESCRIPTION

- 8×8 dot matrix displays.
- $\Phi 1.9$ mm dot and pitch 2.54 mm
- Black face
- White diffusion dots.

3. PACKAGE DIMENSIONS**NOTES:**

1. All dimensions are in millimeters.
2. Tolerance are ± 0.25 mm unless otherwise noted.

4. CIRCUIT DIAGRAM

5. ABSOLUTE MAXIMUM RATINGS Ta=25°C

ITEMS	SYMBOL	Red		UNIT
Power Dissipation Per Dot	PD	60		mw
Forward Current Per Dot*	IF	20		mA
Peak Forward Current Per Dot**	IFP	80		mA
Reverse Voltage Per Dot	VR	5		V
Operation Temperature Range	Topr	-30~+80		°C
Storage Temperature Range	Tstg	-35~+85		°C
Soldering Temperature	Tsol	≤260°C/3 sec		

NOTES:

* We advise average forward current is 15mA

** pulse width=10ms, duty=1/8

6. ELECTRICAL/OPTICAL CHARACTERISTICS Ta=25°C

PARAMETER	SYMBOL	TEST CONDITIONS	PART NO	RATING			UNIT
				MIN	TYP	MAX	
Forward voltage per dot	VF	IF=20mA	Red		1.85	2.0	V
Reverse current per dot	IR	VR=5V	Red			50	μA
Luminous intensity per dot	IV	IFP=40mA 1/8 duty	Red		9		mcd
Peak emission wavelength per dot	λP	IF=20mA	Red		640		nm
Spectral line wavelength per dot	△λ	IF=20mA	Red		35		nm

7. CAUTIONS:

- When being used, do not be over the corresponding limited scale and note in our specification.
- For some products with the static electricity mark, please operate refer to the rules of static electricity fence.
- When designing, please consider the factor of heat, and taking keep away measure to avoid high temperature.
- Do not clean the product with organic impregnate as some of them may damage the product.