


L-4F3XD series ... **2.0x5.0x9.6mm Rectangular LED LAMP**

MAIN FEATURES :


- ⊙ 2.0x5.0x9.6mm Rectangular LED LAMP
- ⊙ STANDARD 1" LEAD
- ⊙ I.C. COMPATIBLE
- ⊙ LONG LIFE-SOLID STATE RELIABILITY
- ⊙ LOW POWER CONSUMPTION

◆ **PACKAGE DIMENSIONS**



Notes:

1. All Dimension are in millimeter.
2. Tolerance is $\pm 0.25\text{mm}(0.010")$ unless otherwise specified.
3. Protruded resin under flange is 1.5mm(0.59") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specification are subject to change without notice.



◆ **SELECTION GUIDE AND APPLICATION INFORMATION (RATINGS AT 25°C AMBIENT)**

Part No.	Chip			Wave Length λ p(nm)	Absolute Maximum Ratings				Electro-Optical Characteristics						View Angle (deg)
	Raw Material	Emitted Color	Lens Color		Δ λ nm	Pd mW	If mA	If (Peak)	Vf(V)			If (Rec)	Iv (mcd)		
									Min.	Typ.	Max.		Min.	Typ.	
L-4F3HD	GaAsP/GaP	Hi.effi Red	Red Diffused	700	90	45	15	50	1.5	1.7	2.8	5~10	0.6	2.0	130
L-4F3ED	GaAsP/GaP	Hi.effi Red	Red Diffused	635	45	100	30	160	1.7	2.0	2.8	10~20	2.5	8.0	130
L-4F3ED-E	GaAsP/GaP	Orange	Orange Diffused	635	45	100	30	160	1.7	2.0	2.8	10~20	2.5	8.0	130
L-4F3GD	GaP	Green	Green Diffused	565	30	100	30	160	1.7	2.1	2.8	10~20	1.5	6.0	130
L-4F3YD	GaAsP/GaP	Yellow	Yellow Diffused	585	30	100	30	160	1.7	2.1	2.8	10~20	1.5	6.0	130
L-4F3AD	GaAsP/GaP	Amber	Amber Diffused	585	30	100	30	160	1.7	2.1	2.8	10~20	1.5	6.0	130
L-4F3I D	GaAlAs	Hi.effi Red	Red Diffused	625	20	60	20	160	1.6	1.8	2.1	10~20	8.0	20.0	130
L-4F3SRD	GaAlAs	Super Red	Red Diffused	660	20	60	20	160	1.6	1.8	2.1	10~20	20.0	50.0	130
L-4F3LRD	GaAlAs	Super Red	Red Diffused	660	20	60	20	160	1.6	1.8	2.1	10~20	50.0	100	130
L-4F3URD	GaAlAs	Super Red	Red Diffused	660	20	60	20	160	1.6	1.8	2.1	10~20	100	150	130

◆ **ABSOLUTE MAXIMUN RATING: (Ta=25°C)**

Reverse Voltage	: 5 Volt
Reverse Current(Vr = 5V)	: 10 μ A
Operating Temperature Range	: -40°C to +85°C
Storage Temperature Range	: -40°C to +100°C
Lead Soldering Temperature	: 260°C for 5 Seconds
(1.6mm(1/16inch) from body)	

◆ **ELECTRO-OPTICAL CHARACTERISTICS: (Ta=25°C)**

Para meter Description	Symbol	Unit
Spectral Line half-Width	$\Delta \lambda$	nm
Power Dissipation	Pd	mW
Peak Forward Current (Duty 1/10,@KHz)	If(Peak)	mA
Recommended Operation Current	If(Rec)	mA
Average Luminuous intensity (If = 10mA)	Iv	mcd