


L-4H4XD series ... **2.0x4.0x7.0mm Rectangular LED LAMP**

MAIN FEATURES :


- ⊙ 2.0x4.0x7.0mm Rectangular LED LAMP
- ⊙ STANDARD 1" LEAD
- ⊙ I.C. COMPATIBLE
- ⊙ LONG LIFE-SOLID STATE RELIABILITY
- ⊙ LOW POWER CONSUMPTION

◆ PACKAGE DIMENSIONS



Notes:

1. All Dimension are in millimeter.
2. Tolerance is $\pm 0.25\text{mm}(0.010")$ unless otherwise specified.
3. Protruded resin under flange is is 1.5mm(0.59") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specification are subject to change without notice.



◆ SELECTION GUIDE AND APPLICATION INFORMATION (RATINGS AT 25°C AMBIENT)

Part No.	Chip			Wave Length λ p(nm)	Absolute Maximum Ratings				Electro-Optical Characteristics						View Angle (deg)
	Raw Material	Emitted Color	Lens Color		$\Delta \lambda$ nm	Pd mW	If mA	If (Peak)	Vf(V)			If Iv (mcd)			
									Min.	Typ.	Max.	(Rec)	Min.	Typ.	
L-4H4RD	GaAsP/GaP	Hi.effi Red	Red Diffused	655	40	110	40	200	1.5	1.7	2.0	10~20	0.4	1.2	120
L-4H4HD	GaAsP/GaP	Hi.effi Red	Red Diffused	700	90	45	15	50	1.5	1.7	2.8	5~10	0.6	1.8	120
L-4H4ED	GaAsP/GaP	Hi.effi Red	Red Diffused	635	45	100	30	160	1.7	2.0	2.8	10~20	2.5	8.0	120
L-4H4ED-E	GaAsP/GaP	Orange	Orange Dffused	635	45	100	30	160	1.7	2.0	2.8	10~20	2.5	8.0	120
L-4H4GD	GaP	Green	Green Diffused	565	30	100	30	160	1.7	2.1	2.8	10~20	1.5	6.0	120
L-4H4YD	GaAsP/GaP	Yellow	Yellow Diffused	585	30	100	30	160	1.7	2.1	2.8	10~20	1.5	6.0	120
L-4H4AD	GaAsP/GaP	Amber	Amber Diffused	585	30	100	30	160	1.7	2.1	2.8	10~20	1.5	6.0	120
L-4H4I D	GaAlAs	Hi.effi Red	Red Diffused	625	20	60	20	160	1.6	1.8	2.1	10~20	8.0	20.0	120
L-4H4SRD	GaAlAs	Super Red	Red Diffused	660	20	60	20	160	1.6	1.8	2.1	10~20	20.0	50.0	120
L-4H5LRD	GaAlAs	Super Red	Red Diffused	660	20	60	20	160	1.6	1.8	2.1	10~20	50.0	100	120
L-4H4URD	GaAlAs	Super Red	Red Diffused	660	20	60	20	160	1.6	1.8	2.1	10~20	100	150	120

◆ ABSOLUTE MAXIMUM RATING: (Ta=25°C)

Reverse Voltage	: 5 Volt
Reverse Current(Vr = 5V)	: 10 μ A
Operating Temperature Range	: -40°C to +85°C
Storage Temperature Range	: -40°C to +100°C
Lead Soldering Temperature	: 260°C for 5 Seconds
(1.6mm(1/16inch) from body)	

◆ ELECTRO-OPTICAL CHARACTERISTICS: (Ta=25°C)

Para meter Description	Symbol	Unit
Spectral Line half-Width	$\Delta\lambda$	nm
Power Dissipation	Pd	mW
Peak Forward Current (Duty 1/10,@KHz)	If(Peak)	mA
Recommended Operation Current	If(Rec)	mA
Average Luminuous intensity (If = 10mA)	Iv	mcd