


Preliminary

Features

- Differential or single-ended Input and Output.
- Gain: 40 dB @ 2.5 GHz (typ.).
- Large dynamic range: > 50 dB
- Large output swing: 0 – 1 V_{PP} adjustable
- Rise/Fall times, typ.: 38 ps (20 - 80%)
- Sensitivity: 2 × 5 mV_{PP} (10 mV_{PP} single ended) with good SNR into GD16584, GD16588, or LXT16742 DeMUX.
- Single power supply: –5.2 V
- Low power consumption: 260 mW (typ.); 800 mW (max.)
- Package: 16 pin Ceramic QFP (5.8 × 5.8 mm)

Applications

- Telecommunications systems:
 - SDH STM-64
 - SONET OC-192
- WDM systems
- 10 Gbit/s receivers
- 10 Gbit/s with 7% FEC



Application Information

Inputs


The inputs of LXT19908 may be either AC or DC coupled. In either case input termination is made through the pins VINREF/ VINREFN which must be terminated through the external resistors (R1 and R2) and de-coupled to ground with capacitors (C5 and C6), as shown in the Figure 1.

If the inputs are AC coupled LXT19908 features an internal offset cancelling DC feedback. Because of the voltage division between the capacitors C3 and C1, (which must have the same value) on VIN / VINREF and C4 and C2 (which also must have the same value) on VVINN / VINREFN, the lower cut-off frequency is in the kHz range. Notice that the offset cancellation will only work if VINREF and VINREFN are not shorted together, and if the inputs are AC coupled, as shown in the Figure 1.

$$\begin{aligned} R1 &= R1 = 10 \Omega \\ C3 &= C4 = C5 = C6 = 100 \text{ nF} \end{aligned}$$

When single-ended input is required, the unused input should be terminated with 50Ω to ground. Figure 3 shows set-ups for DC and AC- coupled inputs.

For optimum sensitivity of the decision circuit following LXT19908 external offset control can be applied as shown in Figure 4. This scheme can be applied on DC and AC- coupled inputs as well as single-ended and differential.



$$\begin{aligned} V_{diff} &= |V_{IN} - V_{VINN}| \\ V_{CM} &= \frac{V_{IN} + V_{VINN}}{2} \end{aligned}$$

Figure 1. AC coupled input




Figure 2. DC coupling for large input amplitude




Figure 3. Single-ended input.
Use optional capacitors ($C1$ and $C2$) for AC-coupled inputs.




Figure 4. External offset.

Outputs

The outputs have $50\ \Omega$ termination internally and can be AC- or DC coupled.

When used with GD16584, GD16588, or LXT16742 (all versions) best sensitivity is obtained with adjustable output set to approximately 400 mV amplitude (or 600 mV_{PP}). LXT19908 can be coupled directly to above mentioned devices as shown in Figure 5.




Figure 5. Using LXT19908 as pre-amplifier to GD16584, GD16588, or LXT16742 (all versions) CDR/DeMUX

Pin List

Mnemonic:	Pin No.:	Pin Type:	Description:
VIN, VINN	14, 15	Analog Input	Differential Data Input
VOUT, VOUTN	7, 6	Analog Output	Differential Data Output
VSET	11	Analog Input	Output Swing Control
VINREF, VINREFN	12, 1	Analog Input	Input Voltage References
VEE	2, 3	PWR	Negative Supply Rail
GND	4, 5, 8, 9, 13, 16	PWR	Ground
NC	10		Reserved for future use. Do not connect.

Package Pinout




Figure 6. Package pinout. Top View

Maximum Ratings

Symbol:	Characteristics:	Conditions:	MIN.:	TYP.:	MAX.:	Units
V_{EE}	Negative supply		-6.5		0	V
$T_J MAX$	Maximum junction temperature		-		150	°C
T_S	Storage temperature		-65		+125	°C
$VSET$	Input level		-6.5		+0.5	V
$V_{IN, INN MAX}$	Input level	Note 1	-3		+0.5	V

Note1: With VINREF and VINREFN open.

Environmental

ESD: >500 V, input protected to <100 V only.

DC Characteristics

The following data specifies the DC characteristics of the limiting amplifier IC over the operating temperature range from 0 to 70 °C case temperature, $V_{EE} = -5.2$ V.

Symbol:	Characteristics:	Conditions:	MIN.:	TYP.:	MAX.:	Units:
V_{EE}	Supply voltage		-4.9	-5.2	-5.5	V
I_{EE}	Negative supply current			50	155	mA
P_{DISS}	Power dissipation			260	800	mW
V_{DIN}, V_{DINN}	Quiescent input voltages	Note 4		-1.6		V
V_{OUT}, V_{OUTN}	Quiescent output voltages	Note 4		-0.5		V
$V_{INOFFSET}$	Input offset	Note 1		0		mV
$V_{OUTOFFSET}$	Output offset	Note 2		0		mV
V_{SET}	VSET control line	Note 3	-2.5		0.0	V

Note 1: DC difference between VIN & VINN for zero output offset, @ maximum gain. AC-coupled I/O's.

Note 2: DC difference between VOUT & VOUTN with zero input offset, @ maximum gain. AC-coupled I/O's.

Note 3: VSET = -2.5 V ($V_{EE} + 2.6$ V) or VSET open gives minimum output. VSET = 0 V gives maximum output.

Note 4: I/O's open.

AC Characteristics

The following data specifies the DC characteristics of the limiting amplifier IC over the operating temperature range from 0 to 70 °C case temperature, $V_{EE} = -5.2$ V.

Symbol:	Characteristics	Conditions:	MIN.:	TYP.:	MAX.:	UNIT:
NF	Noise figure	2.5 GHz			15	dB
ΔG	Gain flatness	DC - 6 GHz		2		dB
$GAIN MAX$	AC gain (S21)	@ 2.5 GHz VSET = 0 V		40		dB
	S22	DC - 6 GHz		-10		dB
	S11	DC - 6 GHz		-10		dB
$V_{IN, P-P}$	Input peak-to-peak swing	Differential			2.0	V _{p-p}
$V_{OUT, P-P}$	Output peak-to-peak swing	Single-ended		1.0		V _{p-p}
t_R/t_F	Rise/Fall time	20 - 80% Limiting Operation		38		ps

Package Outline




Figure 7. Package Outline. All dimensions are in mm.

Device Marking




Figure 8. Device Marking. Top View.

Ordering Information

To order, please specify as shown below.

Part Number:	Package Type:	Case Temperature Range:	Options:
LXT19908- PG	16 pin Ceramic QFP	0...70°C	



an Intel company

Mileparken 22, DK-2740 Skovlunde
Denmark
Phone : +45 7010 1062
Fax : +45 7010 1063
E-mail : sales@giga.dk
Web site : <http://www.giga.dk>

*Please check our Internet web site
for latest version of this data sheet.*

The information herein is assumed to be reliable. GIGA assumes no responsibility for the use of this information, and all such information shall be at the users own risk. Prices and specifications are subject to change without notice. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. GIGA does not authorise or warrant any GIGA Product for use in life support devices and/or systems.

Distributor:

Copyright © 2001 GIGA ApS
An Intel company
All rights reserved

LXT19908, Data Sheet Rev.: 06 - Date: 20 April 2001