

160 School House Road, Souderton, PA 18964-9990 USA Phone 215-723-8181•FAX 215-723-5688 MODEL LN1G11 Low Noise Pre-Amp 1.0 – 11.0GHz with Versions M1-M3

The Model LN1G11 is a broadband, self-contained linear amplifier for laboratory applications requiring instantaneous bandwidth and low noise.

The LN1G11 is useful for amplifying low level signals to more useful levels for driving power amplifiers and other similar applications. In addition, with its low noise figure it can be used to increase the sensitivity of receivers with relatively high noise figures.

The LN1G11 contains an internal power supply which automatically adjusts for the AC input voltage. The AC input connector is an IEC 320 type located on the rear panel

The LN1G11 can be supplied in a benchtop cabinet with the RF connectors located on the front panel or the rear panel. The LN1G11 can also be supplied without the cabinet for rack mounting, front or rear RF connectors.

## SPECIFICATIONS Model LN1G11

POWER OUTPUT+10 dBm at less than 1 dB gain compression
FREQUENCY RESPONSE 1.0 – 11.0 GHz
INPUT FOR RATED OUTPUT16 dBm maximum
GAIN
GAIN FLATNESS ±1.5 dB
NOISE FIGURE 6.5 dB typical
INPUT IMPEDANCE
OUTPUT IMPEDANCE
MISMATCH TOLERANCE
MODULATION CAPABILITY Will faithfully reproduce AM, FM, or pulse modulation appearing on the input signal
HARMONIC DISTORTION20 dBc maximum at +10 dBm output
THIRD ORDER INTERCEPT POINT+20 dBm typical
PRIMARY POWER (selected automatically)

## **MODEL CONFIGURATIONS**

MODEL	CONNECTORS	STYLE	SIZE	WEIGHT
	TYPE/LOCATION		WxHxD	
LN1G11	NFront	Benchtop	26.0 x 11.7 x 21.6 cm	4.5 kg
			10.3 x 4.6 x 8.5 in	10.0 lbs
LN1G11M1	N Rear	Benchtop	26.0 x 11.7 x 21.6 cm	4.5 kg
			10.3 x 4.6 x 8.5 in	10.0 lbs
LN1G11M2	NFront	Rack mount	24.1 x 8.9 x 20.3 cm	1.8 kg
			9.5 x 3.5 x 8.0 in	4.0 lbs
LN1G11M3	N Rear	Rack mount	24.1 x 8.9 x 20.3 cm	1.8 kg
			9.5 x 3.5 x 8.0 in	4.0 lbs