

CCIR REC.601 FILTERS

SINGLE IN LINE

Designed to meet the CCIR Recommendation 601 for 4:2:2 studio systems, these filters are for use in Y.U.V. format Component processing.

Using specially written software and careful attention to component layout, the very stringent parameters for pre and post filtering have been achieved in a Single In Line encapsulated module.

The latest state-of-the-art network analysers are used to align the filters and to ensure the highest quality control in order to meet the specifications. This range also provides integer number of clock cycle between luminance and chrominance filters with reconstruction delay accounted for to assist in equalisation of delay between channels.

	<i>PRE FILTER</i>	<i>POST FILTER</i>
LUMINANCE	LT601F0575	LT601S0575
<i>End Of Passband</i>	5.75 MHz	5.75 MHz
<i>Passband Amplitude Ripple</i>	0.05 dB to 5.5 MHz	0.05 dB to 5.5 MHz ¹
> 12 dB wrt 100 kHz at	0.1 dB to 5.75 MHz	0.1 dB to 5.75 MHz ¹
> 40 dB wrt 100 kHz at	6.75 MHz	6.75 MHz ¹
<i>Group Delay Ripple wrt delay at 200 kHz</i>	8.0 MHz	8.0 MHz
<i>Insertion Loss at 100 kHz</i>	± 3 ns to 5.75 MHz	± 3 ns to 5.75 MHz
<i>Delay Time at 200 kHz</i>	< 1.5 dB	< 4.5 dB
<i>Impedance</i>	760 ns ± 5 ns	758 ns ± 5 ns
<i>Package</i>	75 ohms	75 ohms
	DR00075B	DR00075B

¹ measured against $\sin x/x$ roll off for a 13.5 MHz sampling frequency.

COLOUR DIFFERENCE	LT601F0275	LT601S0275
<i>End Of Passband</i>	2.75 MHz	2.75 MHz
<i>Passband Amplitude Ripple</i>	0.1 dB to 2.75 MHz	0.1 dB to 2.75 MHz ²
> 6 dB wrt 100 kHz at	3.375 MHz	3.375 MHz ²
> 40 dB wrt 100 kHz at	4.0 MHz	4.0 MHz
<i>Group Delay Ripple wrt delay at 200 kHz</i>	± 6 ns to 2.75 MHz	± 6 ns to 2.75 MHz
<i>Insertion Loss at 100 kHz</i>	< 1.5 dB	< 4.5 dB
<i>Delay Time at 200 kHz</i>	1500 ns ± 5 ns	1461 ns ± 5 ns
<i>Impedance</i>	75 ohms	75 ohms
<i>Package</i>	DR00075B	DR00075B

² measured against $\sin x/x$ roll off for a 6.75 MHz sampling frequency.

PACKAGE DETAIL

