

Ceramic

Low Pass Filter

New!
LPCH-600

DC to 575 MHz

Features

- excellent rejection, 40 dB at 1.4 f_3 dB
- excellent power handling, 10W
- low height
- 9 sections

Applications

- harmonic rejection
- VHF/UHF transmitters/receivers
- lab use



BLUE CELL™

CASE STYLE: BJ850

PRICE: \$5.95 ea. QTY.: (10-49)

(Patent pending)

Electrical Specifications ($T_{AMB} = -55^{\circ}\text{C}$ to 100°C)

MODEL NO.	PASSBAND (MHz) (loss < 1 dB) Min.	fco, MHz Nom. (loss 3 dB) Typ.	STOP BAND (MHz)		VSWR (:1)	
			(loss > 20dB) Min.	(loss > 35dB) Min.	Passband Typ.	Stopband Typ.
LPCH-600	DC-575	890	1080-1175	1175-3000	1.2	20

Pin Connections


IN	1
OUT	5
GROUND	2,3,4,6,7,8
DEMO BOARD	TB-189

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input	10W* max. at 25°C

*derate linearly to 3W at 100°C


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	wt.
.320	.700	—	.110	.070	.050	.200	.047	.065	.090	.400	grams
8.13	17.87	—	2.79	1.78	1.27	5.08	1.19	1.65	2.29	10.16	1.0

Suggested PCB Layout (PL-047)





NOTES:

1. TRACE WIDTH IS SHOWN FOR ROGERS R04350 WITH DIELECTRIC THICKNESS $0.020" \pm 0.0015"$, COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. IF YOUR PCB DESIGN RULES ALLOW, GROUND VIAS SHOULD BE PLACED UNDER THE LAND PATTERN FOR BETTER RF PERFORMANCE. OTHERWISE GROUND VIAS SHOULD BE PLACED AS CLOSE TO LAND PATTERN AS POSSIBLE.

- DENOTES LAND PATTERN
 DENOTES PCB LAYOUT

Typical Performance Data at 25°C

Freq. (MHz)	Ins. Loss (dB)	VSWR (:1)
20.00	0.13	1.04
100.00	0.23	1.09
575.00	0.66	1.17
700.00	0.84	1.06
900.00	5.12	4.45
1100.00	31.97	28.03
1150.00	37.71	29.46
1300.00	62.75	31.60
2000.00	55.18	32.18
3000.00	35.32	34.07



Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

ISO 9001 CERTIFIED

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

REV. B
M82241
ED-8923/12
LPCH-600
AD/RS/CP
020716