


Property of LITE-ON Only

Features

- * Package In 8mm Tape On 7" Diameter Reels.
- * Compatible With Automatic Placement Equipment.
- * Compatible With Infrared And Vapor Phase Reflow Solder Process.
- * EIA STD Package.
- * I.C. compatible.

Package Dimensions



Part No.	Lens Color	Source Color
LTST-T675GEKT	Water Clear	Orange / Green


Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ± 0.2 mm (.008") unless otherwise noted.

Absolute Maximum Ratings at Ta=25°C

PARAMETER	Green	Orange	UNIT
Power Dissipation	100	100	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	120	120	mA
Continuous Forward Current	30	30	mA
Derating Linear From 50°C	0.6	0.6	mA/°C
Reverse Voltage	5	5	V
Operating Temperature Range	-55°C to + 100°C		
Storage Temperature Range	-55°C to + 100°C		
Infrared Soldering Cndition	265°C For 5 Seconds		
Vapor Phase Soldering Condition	215°C For 3 Minutes		
Wave Soldering Temperature	260°C For 5 Seconds		

Suggest IR Reflow Condition :



Electrical / Optical Characteristics at Ta=25°C

PARAMETER	SYMBOL	PART NO. LTST-T675GEKT	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Luminous Intensity	IV	Green Orange	3.7 2.8	8.0 8.0		mcd	IF = 10mA/Chip Note 1
Viewing Angle	2θ _{1/2}	Green Orange		120 120		deg	Note 2 (Fig.6)
Peak Emission Wavelength	λ _P	Green Orange		565 630		nm	Measurement @Peak (Fig.1)
Dominant Wavelength	λ _d	Green Orange		570 621		nm	Note 3
Spectral Line Half-Width	Δλ	Green Orange		30 40		nm	
Forward Voltage	V _F	Green Orange		2.1 2.0	2.6 2.6	V	IF = 20mA
Reverse Current	I _R	Green Orange			100 100	μ A	VR = 5V
Capacitance	C	Green Orange		35 20		PF	V _F =0, f=1MHZ

NOTE: 1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.

2. θ 1/2 is the off-axis angle at which the luminous intensity is half the axial luminous intensity.

3. The dominant wavelength, λ d is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.

4. The Iv data did not including ±15% testing tolerance.

Typical Electrical / Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.1 RELATIVE INTENSITY VS. WAVELENGTH




Fig.2 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.3 FORWARD CURRENT DERATING CURVE




Fig.4 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. AMBIENT TEMPERATURE.





Fig.6 SPATIAL DISTRIBUTION

User Guide


Cleaning

Do not use unspecified chemical liquid to clean LED they could harm the package.
If cleaning is necessary, immerse the LED in ethyl alcohol or isopropyl alcohol at normal temperature for less one minute.

Recommend Printed Circuit Board Attachment Pad




Package Dimensions of Tape



Note:

1.All dimensions are in millimeters (inches).

Package Dimensions of Reel



Notes:

1. Empty component pockets sealed with top cover tape.
2. 7 inch reel-2000 pieces per reel.
3. The maximum number of consecutive missing lamps is two.
4. In accordance with ANSI/EIA RS-481 specifications.