Features

* Designed for ease in circuit board assembly.
* Black case enhance contrast ratio.
* Solid state light source.
* Reliable and rugged.

Package Dimensions



Part No. LTL-	Lens	Source Color
10233WP	Green Diffused	Green

Notes:
1. All dimensions are in millimeters (inches).
2. Tolerance is ± 0.25mm(.010") unless otherwise noted.
3. The holder color is black.
4. The holder raw material is PC.
5. The LED lamp is LTL-10233WP.

Absolute Maximum Ratings at Ta=25℃

Parameter	Maximum Rating	Unit
Power Dissipation	100	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	120	mA
Continuous Forward Current	30	mA
Derating Linear From 50℃	0.4	mA/℃
Reverse Voltage	5	V
Operating Temperature Range	-55℃ to + 100℃	
Storage Temperature Range	-55℃ to + 100℃	
Lead Soldering Temperature [1.6mm(.063") From Body]	260℃ for 5 Seconds	

Electrical Optical Characteristics at Ta=25℃

Parameter	Symbol	Part No. LTL-	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I_V	533-11P	12.6	40		mcd	I_F = 10mA Note 1,4
Viewing Angle	$2\theta_{1/2}$	533-11P		60		deg	Note 2 (Fig.6)
Peak Emission Wavelength	λp	533-11P		565		nm	Measurement @Peak (Fig.1)
Dominant Wavelength	λd	533-11P		569		nm	Note 3
Spectral Line Half-Width	$\Delta\lambda$	533-11P		30		nm	
Forward Voltage	V_F	533-11P		2.1	2.6	V	I_F = 20mA
Reverse Current	I_R	533-11P			100	μA	V_R = 5V
Capacitance	C	533-11P		35		pF	V_F = 0 , f = 1MHz

Note: 1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.

2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.

3. The dominant wavelength, λd is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.

4. Iv needs ±15% additionary for guaranteed limits.

Typical Electrical / Optical Characteristics Curves

(25℃ Ambient Temperature Unless Otherwise Noted)



Fig.1 Relative Intensity vs. Wavelength



Fig.2 Forward Current vs. Forward Voltage



Fig.3 Forward Current Derating Curve



Fig.4 Relative Luminous Intensity vs. Forward Current



Fig.5 Luminous Intensity vs. Ambient Temperature



Fig.6 Spatial Distribution