



SEMCO LASER TECHNOLOGY*

18007 Cortney Court, City of Industry, CA 91706, U.S.A. • Tel: (626) 581-0211 • Fax: (626) 581-0511

LD- 505A

Visible Laser Diode Technical Data

ABSOLUTE MAXIMUM RATINGS (Tc=25°C)


- Index Guided MQW Structure
- Wavelength : 655 nm (Typ.)
- Optical Power : 5 mW CW
- Threshold Current : 25 mA (Typ.)
- Standard Package : 5.6 mm Ø

DESCRIPTION	SYMBOL	RATED VALUE
Optical power (mW)	PO	5
Operation Temperature (°C)	Top	-10 to +50
Storage Temperature (°C)	Tstg	-40 to +85
LD reverse voltage (V)	VLDR	2
PD reverse voltage (V)	VPDR	30


OPTICAL AND ELECTRICAL CHARACTERISTICS (Tc=25°C)

DESCRIPTION	SYMBOL	MIN.	TYPICAL	MAX.	TEST CONDITION
Lasing Wavelength (nm)	λ_p	645	655	665	Po=5mW
Threshold Current (mA)	I _{th}	15	25	35	Po=5mW
Operation Current (mA)	I _{op}	20	30	45	Po=5mW
Operation Voltage (V)	V _{op}	2.0	2.4	2.7	Po=5mW
Monitor Current (mA)	I _m	0.3	—	0.2	Po=5 mW, Vr=5V
Slope Efficiency (mW/mA)	ζ	0.4	0.5	0.7	***
Beam Divergence // (°)	$\theta_{//}$	8	10	11	Po=5mW
Beam Divergence $\perp$ (°)	$\theta_{\perp}$	25	31	40	Po=5mW
Astigmatism (μm)	A _s	***	11	***	Po=5mW, NA=0.4

Bottom View Pin Location



PIN CONNECTION



1. Laser diode cathode

2. Laser diode anode
photodiode cathode

3. Photodiode anode

case and pin no. 2 are in common