







CLASSIFICATION			SLOT AND SPECIAL PROXIMITY SWITCH				
CHRACTERISTICS			It could be installed side by side and the slot could be installed seperately.				
SERIES NEMBER			LL	LUB	LVA	LG	LQ
SIZE							
DETECT DISTANCE			8mm	Width: 5mm	Width:4mm	4mm	Width:3mm
RATED VOLTAGE			10-30V DC 90-250V AC	10-30V DC 90-250V AC	10-30V DC	10-30V DC 90-250V AC	10-30V DC 90-250V AC
CURRENT CONSUMED	DC		≤8mA	≤8mA	≤8mA	≤8mA	≤8mA
	AC		≤2.5mA	≤2.5mA	≤2.5mA	≤2.5mA	≤2.5mA
DETECTABLE OBJECTS			METAL	METAL	METAL	METAL	METAL
SUITABLE OUTPUT			 300mA 300mA	 300mA 300mA	 300mA 300mA	 300mA 300mA	 300mA 300mA
RESPONDED FREQUENCY			450HZ、20HZ	600HZ、20HZ	600HZ、400HZ	500HZ、20HZ	500HZ、20HZ
CRUST MATERIALS			Plastic	Plastic	Plastic	Plastic	Plastic
TEMPRETURE			-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃
SAFTY GRADE I E C			IP67	IP67	IP67	IP67	IP67
INSULATING RESISTANCE			Above 50M Ω	Above 50M Ω	Above 50M Ω	Above 50M Ω	Above 50M Ω
TYPE DC	N P N	OPEN	LL-0824NA	LUB-0524NA	LVA-0424NA	LG-0424NA	LQ-0324NA
		CLOSED	LL-0824NB	LUB-0524NB	LVA-0424NB	LG-0424NB	LQ-0324NB
		OPEN AND CLOSED	LL-0824NC	LUB-0524NC	LVA-0424NC	LG-0424NC	LQ-0324NC
	P N P	OPEN	LL-0824PA	LUB-0524PA	LVA-0424PA	LG-0424PA	LQ-0324PA
		CLOSED	LL-0824PB	LUB-0524PB	LVA-0424PB	LG-0424PB	LQ-0324PB
		OPEN AND CLOSED	LL-0824PC	LUB-0524PC	LVA-0424PC	LG-0424PC	LQ-0324PC
	TWO THREADS	OPEN	LL-0824LA	LUB-0524LA	LVA-0424LA	LG-0424LA	LQ-0324LA
		CLOSED	LL-0824LB	LUB-0524LB	LVA-0424LB	LG-0424LB	LQ-0324LB
TYPE AC	TWO THREADS OPEN		LL-0822KA	LUB-0522KA		LG-0422KA	LQ-0322KA
	TWO THREADS CLOSED		LL-0822KB	LUB-0522KB		LG-0422KB	LQ-0322KB
	THREE THREADSOPEN AND CLOSED		LL-0822KC				