





CLASSIFICATION			PLUG PROXIMITY SWITCH				
CHRACTERISTICS			With special plugs and diversified installment				
SERIES NEMBER			LCA	LCB	LCC	LCE	LCF
SIZE							
DETECT DISTANCE			4mm	4mm	4mm	25mm	3mm
RATED VOLTAGE			10-30V DC	7-15 DC	10-30V DC	10-30V DC 90-250V AC	10-30V DC 90-250V AC
CURRENT CONSUMED	DC		----	----	----	≤8mA	≤8mA
	AC		≤2.5mA	≤2.5mA	≤2.5mA	≤2.5mA	≤2.5mA
DETECTABLE OBJECTS			METAL	METAL	METAL	METAL	METAL
SUITABLE OUTPUT			 300mA	 300mA	 300mA	 300mA 300mA	 300mA 300mA
RESPONDED FREQUENCY			500HZ	500HZ	500HZ	200HZ	500HZ
CRUST MATERIALS			Plastic	Plastic	Plastic	Plastic	Plastic
TEMPRETURE			-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃
SAFTY GRADE I E C			IP67	IP67	IP67	IP67	IP67
INSULATING RESISTANCE			Above 50M Ω	Above 50M Ω	Above 50M Ω	Above 50M Ω	Above 50M Ω
TYPE DC	N P N	OPEN	LCA-0424NA		LCC-0424NA	LCE-M2524NA	LCF-0324NA
		CLOSED	LCA-0424NB		LCC-0424NB	LCE-M2524NB	LCF-0324NB
		OPEN AND CLOSED				LCE-M2524NC	LCF-0324NC
	P N P	OPEN	LCA-0424PA		LCC-0424PA	LCE-M2524PA	LCF-0324PA
		CLOSED	LCA-0424PB		LCC-0424PB	LCE-M2524PB	LCF-0324PB
		OPEN AND CLOSED				LCE-M2524PC	LCF-0324PC
	TWO THREADS	OPEN				LCE-M2524LA	LCF-0324LA
		CLOSED		LCB-0412LB		LCE-M2524LB	LCF-0324LB
TYPE AC	TWO THREADS OPEN					LCE-M2524KA	LCF-0324KA
	TWO THREADS CLOSED					LCE-M2524KB	LCF-0324KB
	THREE THREADSOPEN AND CLOSED					LCE-M2524KC	