













CLASSIFICATION			PLANE INSTALLED PROXIMITY SWITCH					
CHRACTERISTICS			Long detect distance, steady power, high tempreture -proof and wide range of voltage					
SERIES NEMBER			LYA	LY	LYE	LR	LRA	LRB
SIZE								
DETECT DISTANCE			Type noninsert: 15mm	Type noninsert: 20mm	Type noninsert: 25mm	Type noninsert: 0-50mm	Type noninsert: 0-50mm	Type noninsert: 0-60mm
RATED VOLTAGE			10-30V DC 90-250V AC	10-30V DC 90-250V AC	10-30V DC 90-250V AC	10-30V DC 90-250V AC	10-30V DC 90-250V AC	10-30V DC 90-250V AC
CURRENT CONSUMED	DC		≤8mA	≤8mA	≤8mA	≤8mA	≤8mA	≤8mA
	AC		≤2.5mA	≤2.5mA	≤2.5mA	≤2.5mA	≤2.5mA	≤2.5mA
DETECTABLE OBJECTS			METAL	METAL	METAL	METAL	METAL	METAL
SUITABLE OUTPUT			 300mA 300mA	 300mA 300mA	 300mA 300mA	 300mA 300mA	 300mA 300mA	 300mA 300mA
RESPONDED FREQUENCY			200HZ、20HZ	150HZ、20HZ	150KHZ、20HZ	100HZ、15HZ	100HZ、10HZ	100HZ、10HZ
CRUST MATERIALS			Plastic	Plastic	Plastic	Plastic、GLASS STEEL	Plastic、GLASS STEEL	Plastic、GLASS STEEL
TEMPRETURE			-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃	-25℃ ~ 85℃
SAFTY GRADE I E C			IP67	IP67	IP67	IP67	IP67	IP67
INSULATING RESISTANCE			Above 50MΩ	Above 50MΩ	Above 50MΩ	Above 50MΩ	Above 50MΩ	Above 50MΩ
TYPE DC	N P N	OPEN	LYA-M1524NA	LY-M2024NA	LYE-M2524NA	LR-M5024NA	LRA-M5024NA	LRB-M6024NA
		CLOSED	LYA-M1524NB	LY-M2024NB	LYE-M2524NB	LR-M5024NB	LRA-M5024NB	LRB-M6024NB
		OPEN AND CLOSED	LYA-M1524NC	LY-M2024NC	LYE-M2524NC	LR-M5024NC	LRA-M5024NC	LRB-M6024NC
	P N P	OPEN	LYA-M1524PA	LY-M2024PA	LYE-M2524PA	LR-M5024PA	LRA-M5024PA	LRB-M6024PA
		CLOSED	LYA-M1524PB	LY-M2024PB	LYE-M2524PB	LR-M5024PB	LRA-M5024PB	LRB-M6024PB
		OPEN AND CLOSED	LYA-M1524PC	LY-M2024PC	LYE-M2524PC	LR-M5024PC	LRA-M5024PC	LRB-M6024PC
	TWO THREADS	OPEN	LYA-M1524LA	LY-M2024LA	LYE-M2524LA	LR-M5024LA	LRA-M5024LA	LRB-M6024LA
		CLOSED	LYA-M1524LB	LY-M2024LB	LYE-M2524LB	LR-M5024LB	LRA-M5024LB	LRB-M6024LB
TYPE AC	TWO THREADS OPEN		LYA-M1522KA	LY-M2022KA	LYE-M2522KA	LR-M5022KA	LRA-M5022KA	LRB-M6022KA
	TWO THREADS CLOSED		LYA-M1522KB	LY-M2022KB	LYE-M2522KB	LR-M5022KB	LRA-M5022KB	LRB-M6022KB
	THREE THREADSOPEN AND CLOSED			LY-M2022KC	LYE-M2522KC	LR-M5022KC	LRA-M5022KC	LRB-M6022KC