

NT511740C0J

Data Sheet

NT511740C0J

4,194,304-word x 4-bit

Dynamic RAM : Fast Page Mode



1. DESCRIPTION

The NT511740C0J is a 4,194,304-word x 4-bit dynamic RAM fabricated in NTC's CMOS silicon gate technology. The NT511740C0J achieves high integration , high-speed operation , and low-power consumption due to quadruple polysilicon double metal CMOS. The NT511740C0J is available in a 26/24-pin plastic SOJ.

2. FEATURES

- 4,194,304-word x 4-bit configuration
- Single 5V power supply, $\pm 10\%$ tolerance
- Input :TTL compatible , low input capacitance
- Output :TTL compatible , 3-state
- Refresh :2048 cycles/32 ms
- Fast page mode , read modify write capability
- CAS before RAS refresh, hidden refresh, RAS-only refresh capability
- Multi-bit test mode capability
- Package options:


26/24-Pin 300 mil plastic SOJ (SOJ26/24-P300) (Product:NT511740C0J-XX)

XX indicates speed rank.

3. PRODUCT FAMILY

Family	Access Time (Max.)				Cycle Time (Min.)	Power Dissipation	
	t _{RAC}	t _{AA}	t _{CAC}	t _{OEa}		Operation (Max.)	Standby (Max.)
NT511740C0J-50	50 ns	25 ns	13 ns	13 ns	90 ns	660 mW	5.5 mW
NT511740C0J-60	60 ns	30 ns	15 ns	15 ns	110 ns	605 mW	
NT511740C0J-70	70 ns	35 ns	20 ns	20 ns	130 ns	550 mW	


4. PIN CONFIGURATION (TOPVIEW)



Pin Name	Function
A0-A10	Adress input
$\overline{\text{RAS}}$	Row Address Strobe
$\overline{\text{CAS}}$	Column Address Strobe
DQ1-DQ4	Data Input/Data Output
$\overline{\text{OE}}$	Output Enable
$\overline{\text{WE}}$	Write Enable
Vcc	Power Supply (5v)
Vss	Ground(0V)
NC	No Connection

Note:The same power supply voltage must be provided to every Vcc pin , and the same GND voltage level must be provided to every Vss pin.

5. BLOCK DIAGRAM



6. ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Voltage on Any Pin Relative to VSS	V_{IN}, V_{OUT}	-0.3 to $V_{CC}+0.3$	V
Voltage on V_{CC} Supply Relative to VSS	V_{CC}	-0.5 to 7	V
Short Circuit Output Current	I_{OS}	50	mA
Power Dissipation	P_D^*	1	W
Operation Temperature	T_{opr}	0 to 70	°C
Storage Temperature	T_{stg}	-55 to 150	°C

*: $T_a = 25^{\circ}\text{C}$

Recommended Operating Conditions

($T_a = 0^{\circ}\text{C}$ to 70°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Power Supply Voltage	V_{CC}	4.5	5.0	5.5	V
	V_{SS}	0	0	0	V
Input High Voltage	V_{IH}	2.4	-	$V_{CC}+0.3$	V
Input Low Voltage	V_{IL}	-0.3	-	0.8	V

Capacitance

($V_{CC} = 5V \pm 10\%$, $T_a = 25^{\circ}\text{C}$, $f = 1\text{ MHz}$)

Parameter	Symbol	Typ.	Max.	Unit
Input Capacitance (A0-A10)	C_{IN1}	-	5	pF
Input Capacitance (RAS, CAS, WE, OE)	C_{IN2}	-	7	pF
Output Capacitance (DQ1-DQ4)	$C_{I/O}$	-	7	pF

7. DC Characteristics

(V_{CC}=5V±10% , T_a=0°C to 70°C)

Parameter	Symbol	Condition	NT511740C 0J-50		NT511740C 0J-60		NT511740C 0J-70		Unit	Note
			Min.	Max.	Min.	Max.	Min.	Max.		
Output High Voltage	V _{OH}	I _{OH} = -5.0 mA	2.4	V _{CC}	2.4	V _{CC}	2.4	V _{CC}	V	
Output LOW Voltage	V _{OL}	I _{OL} = 4.2 mA	0	0.4	0	0.4	0	0.4	V	
Input Leakage Current	I _{L1}	0V ≤ V _I ≤ 6.5V; All other pins not under test = 0V	-10	10	-10	10	-10	10	μA	
Output Leakage Current	I _{L0}	DQ disable 0V ≤ V _O ≤ 5.5V	-10	10	-10	10	-10	10	μA	
Average Power Supply Current (Operating)	I _{CC1}	RAS, CAS cycling, t _{RC} = Min.	-	120	-	110	-	100	mA	1,2
Power Supply Current (Standby)	I _{CC2}	RAS, CAS=V _{IH}	-	2	-	2	-	2	mA	1
		RAS, CAS ≥ V _{CC} -0.2V	-	1	-	1	-	1		
Average Power Supply Current (RAS-only Refresh)	I _{CC3}	RAS cycling, CAS = V _{IH} , t _{RC} =Min.	-	120	-	110	-	110	mA	1,2
Power Supply Current (Standby)	I _{CC5}	RAS= V _{IH} , CAS= V _{IL} , DQ = enable	-	5	-	5	-	5	mA	1
Average Power Supply Current (CAS before RAS Refresh)	I _{CC6}	RAS cycling, CAS before RAS	-	120	-	110	-	100	mA	1,2
Average Power Supply Current (Fast Page Mode)	I _{CC7}	RAS=V _{IL} , CAS cycling t _{PC} =Min.	-	100	-	90	-	80	mA	1,3

Notes:

1. ICC Max. is specified as I_{CC} for output open condition.
2. Address can be changed once or less while $\overline{\text{RAS}}=V_{\text{IL}}$.
3. Address can be changed once or less while $\text{CAS}=V_{\text{IH}}$.

NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode



8. AC Characteristics (1/3)

(V_{CC}=5V±10% ,T_a=0°C to 70°C) Note:1,2,3,11,12

Parameter	Symbol	NT511740C0J - 50		NT511740C0J - 60		NT511740C0J - 70		Unit	Note
		Min.	Max.	Min.	Max.	Min.	Max.		
Random Read or Write Cycle Time	t _{RC}	90	-	110	-	130	-	ns	
Read Modify Write Cycle Time	t _{RWC}	131	-	155	-	185	-	ns	
Fast Page Mode Cycle Time	t _{PC}	35	-	40	-	45	-	ns	
Fast Page Mode Read Modify Write Cycle Time	t _{PRWC}	76	-	85	-	100	-	ns	
Access Time form $\overline{\text{RAS}}$	t _{RAC}	-	50	-	60	-	70	ns	4,5,6
Access Time form $\overline{\text{CAS}}$	t _{CAC}	-	13	-	15	-	20	ns	4,5
Access Time form Column Address	t _{AA}	-	25	-	30	-	35	ns	4,6
Access Time form $\overline{\text{CAS}}$ Precharge	t _{CPA}	-	30	-	35	-	40	ns	4
Access Time form $\overline{\text{OE}}$	t _{OEA}	-	13	-	15	-	20	ns	4
Output Low Impedance Time from $\overline{\text{CAS}}$	t _{CLZ}	0	-	0	-	0	-	ns	4
$\overline{\text{CAS}}$ to Data Output Buffer Turn-off Delay Time	T _{OFF}	0	13	0	15	0	20	ns	7
$\overline{\text{OE}}$ to Data Output Buffer Turn-off Delay Time	t _{OEZ}	0	13	0	15	0	20	ns	7
Transition Time	t _T	3	50	3	50	3	50	ns	3
Refresh Period	t _{REF}	-	32	-	32	-	32	ms	
$\overline{\text{RAS}}$ Precharge Time	t _{RP}	30	-	40	-	50	-	ns	
$\overline{\text{RAS}}$ Pulse Width	t _{RAS}	50	10,000	60	10,000	70	10,000	ns	
$\overline{\text{RAS}}$ Pulse Width (Fast Page Mode)	t _{RASP}	50	100,000	60	100,000	70	100,000	ns	

NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode



AC Characteristics (2/3)

Parameter	Symbol	NT511740C0J - 50		NT511740C0J - 60		NT511740C0J - 70		Unit	Note
		Min.	Max.	Min.	Max.	Min.	Max.		
$\overline{\text{RAS}}$ Hold Time	t_{RSH}	13	-	15	-	20	-	ns	
$\overline{\text{RAS}}$ Hold Time referenced to $\overline{\text{OE}}$	t_{ROH}	13	-	15	-	20	-	ns	
$\overline{\text{CAS}}$ Precharge Time (Fast Page Mode)	t_{CP}	7	-	10	-	10	-	ns	
$\overline{\text{CAS}}$ Pulse Width	t_{CAS}	13	10,000	15	10,000	20	10,000	ns	
$\overline{\text{CAS}}$ Hold Time	t_{CSH}	50	-	60	-	70	-	ns	
$\overline{\text{CAS}}$ to $\overline{\text{RAS}}$ Precharge Time	t_{CRP}	5	-	5	-	5	-	ns	
$\overline{\text{RAS}}$ Hold Time from $\overline{\text{CAS}}$ Precharge Time	t_{RHCP}	30	-	35	-	40	-	ns	
$\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ Delay Time	t_{RCD}	17	37	20	45	20	50	ns	5
$\overline{\text{RAS}}$ to Column Address Delay Time	t_{RAD}	12	25	15	30	15	35	ns	6
Row Address Set-up Time	t_{ASR}	0	-	0	-	0	-	ns	
Row Address Hold Time	t_{RAH}	7	-	10	-	10	-	ns	
Column Address Set-up Time	t_{ASC}	0	-	0	-	0	-	ns	
Column Address Hold Time	t_{CAH}	7	-	15	-	15	-	ns	
Column Address to $\overline{\text{RAS}}$ Lead Time	t_{RAL}	25	-	30	-	35	-	ns	
Read Command Set-up Time	t_{RCS}	0	-	0	-	0	-	ns	
Read Command Hold Time	t_{RCH}	0	-	0	-	0	-	ns	8
Read Command Hold Time referenced to $\overline{\text{RAS}}$	t_{RRH}	0	-	0	-	0	-	ns	8

NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode



AC Characteristics (3/3)

(V_{CC}=5V±10% ,T_a=0°C to 70°C) Note 1,2,3,11,12


Parameter	Symbol	NT511740C0J-50		NT511740C0J-60		NT511740C0J-70		Unit	Note
		Min.	Max.	Min.	Max.	Min.	Max.		
Write Command Set-up Time	t _{WCS}	0	-	0	-	0	-	ns	9
Write Command Hold Time	t _{WCH}	7	-	10	-	15	-	ns	
Write Command Pulse Width	t _{WP}	7	-	10	-	10	-	ns	
OE Command Hold Time	t _{OEH}	13	-	15	-	20	-	ns	
Write Command to $\overline{\text{RAS}}$ Lead Time	t _{RWL}	13	-	15	-	20	-	ns	
Write Command to $\overline{\text{CAS}}$ Lead Time	t _{CWL}	13	-	15	-	20	-	ns	
Data-in Set-up Time	t _{DS}	0	-	0	-	0	-	ns	10
Data-in Hold Time	t _{DH}	7	-	10	-	15	-	ns	10
$\overline{\text{OE}}$ to Data-in Delay Time	t _{OED}	13	-	15	-	20	-	ns	
$\overline{\text{CAS}}$ to $\overline{\text{WE}}$ Delay Time	t _{CWD}	36	-	40	-	50	-	ns	9
Column Address to $\overline{\text{WE}}$ Delay Time	t _{AWD}	48	-	55	-	65	-	ns	9
$\overline{\text{RAS}}$ to $\overline{\text{WE}}$ Delay Time	t _{RWD}	73	-	85	-	100	-	ns	9
$\overline{\text{CAS}}$ Precharge $\overline{\text{WE}}$ Delay Time	t _{CPWD}	53	-	60	-	70	-	ns	9
$\overline{\text{CAS}}$ Active Delay Time from $\overline{\text{RAS}}$ Precharge	t _{RPC}	5	-	5	-	5	-	ns	
$\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ Set-up Time ($\overline{\text{CAS}}$ before $\overline{\text{RAS}}$)	t _{CSR}	10	-	10	-	10	-	ns	
$\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ Hold Time ($\overline{\text{CAS}}$ before $\overline{\text{RAS}}$)	t _{CHR}	10	-	10	-	10	-	ns	
$\overline{\text{WE}}$ to $\overline{\text{RAS}}$ Precharge Time ($\overline{\text{CAS}}$ before $\overline{\text{RAS}}$)	t _{WRP}	10	-	10	-	10	-	ns	
$\overline{\text{WE}}$ Hold Time $\overline{\text{RAS}}$ ($\overline{\text{CAS}}$ before $\overline{\text{RAS}}$)	t _{WRH}	10	-	10	-	10	-	ns	
$\overline{\text{RAS}}$ to $\overline{\text{WE}}$ Set-up Time (Test Mode)	t _{WTS}	10	-	10	-	10	-	ns	
$\overline{\text{RAS}}$ to $\overline{\text{WE}}$ Hold Time (Test Mode)	t _{WTH}	10	-	10	-	10	-	ns	

Notes

1. A start-up delay of 200 μ s is required after power-up ,followed by a minimum of eight initialization cycles (RAS-only refresh or CAS before RAS refresh) before proper device operation is achieved.
2. The AC characteristics assume $t_T = 5$ ns.
3. $V_{IH}(\text{Min.})$ and $V_{IL}(\text{Max.})$ are reference levels for measuring input timing signals. Transition time (t_T) are measured between V_{IH} and V_{IL} .
4. This parameter is measured with a load circuit equivalent to 2 TTL loads and 100 pF.
5. Operation within the $t_{RCD}(\text{Max.})$ limit ensures that $t_{RAC}(\text{Max.})$ can be met.
 $t_{RCD}(\text{Max.})$ is specified as a reference point only . If t_{RCD} is greater than the specified $t_{RCD}(\text{Max.})$ limit, access time is controlled by t_{CAC} .
6. Operation within the $t_{RAD}(\text{Max.})$ limit ensures that $t_{RAC}(\text{Max.})$ can be met.
 $t_{RAD}(\text{Max.})$ is specified as a reference point only . If t_{RAD} is greater than the specified $t_{RAD}(\text{Max.})$ limit, access time is controlled by t_{AA} .
7. $T_{OFF}(\text{Max.})$ and $t_{OEZ}(\text{Max.})$ define the time at which the output achieves the open circuit condition and are not referenced to output voltage levels.
8. t_{RCH} or t_{RRH} must be satisfied for a read cycle.
9. t_{WCS} , t_{CWD} , t_{RWD} , t_{AWD} , and t_{CPWD} are not restrictive operating parameters. They are included in the data sheet as electrical characteristics only . If $t_{WCS} \geq t_{WCS}(\text{Min.})$, the cycle is an early write cycle and the data out will remain open circuit (high impedance) throughout the entire cycle. If $t_{CWD} \geq t_{CWD}(\text{Min.})$, $t_{RWD} \geq t_{RWD}(\text{Min.})$, $t_{AWD} \geq t_{AWD}(\text{Min.})$ and $t_{CPWD} \geq t_{CPWD}(\text{Min.})$, the cycle is a read modify write cycle and data out will contain data read from the selected cell; if neither of the above sets of conditions is satisfied, the condition of the data out (at access time) is indeterminate.
10. These parameters are referenced to CAS leading edge in an early write cycle, and to WE leading edge in an OE control write cycle or a read modify write cycle .
11. The test mode is initiated by performing a WE and CAS before RAS refresh cycle. This mode is latched and remains in effect until the exit cycle is generated. In a test mode CA0 and CA1 are not used and each DQ pin now accesses 8-bit locations. Since all 4 DQ pins are used, a total of 32 data bits can be written in parallel into the memory array. In a read cycle, if 8 data bits are equal the DQ pin will indicate a high level. If the 8 data bits are not equal, the DQ pin will indicate a low level. The test mode is cleared and the memory device returned to its normal operating state by performing a RAS-only refresh cycle or a CAS before RAS refresh cycle.
12. In a test mode read cycle , the value of access time parameters is delayed for 5 ns for the specified value . These parameters should be specified in test mode cycle by adding the above value to the specified value in this data sheet.

9.DRAM AC Timing Waveforms


Read Cycle



NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode




Write Cycle (Early Write)



NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode




Read Modify Write Cycle




NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode




Fast Page Mode Read Cycle



RAS-Only Refresh Cycle




CAS Before RAS Refresh Cycle



NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode




Hidden Refresh Read Cycle



NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode




Hidden Refresh Write Cycle



NT511740C0J
4,194,304-word x 4-bit
Dynamic RAM : Fast Page Mode



Test Mode Initiate Cycle



□ : H" or L"