

Housing LEDs

Shape	Part Number	Emitting Color	Emitting Material	Lens-Color	Wave Length (nm)	Luminous Intensity IF=10mA *20mA(mcd) Min. Max.	Viewing Angle	Figure No.
3mm Right Angle	NN1LUGR86M	Red	GaAsP/GaP	White Diffused	625	*8 - 40	60°	1
		Green	GaP		565	*8 - 40		
	NN1LUYR86M	Red	GaAsP/GaP	White Diffused	625	*8 - 40	60°	
		Yellow	GaAsP/GaP		590	*8 - 40		
	NN1LUGY86M	Green	GaP	White Diffused	565	*8 - 40	60°	
		Yellow	GaAsP/GaP		590	*8 - 40		
3mm Right Angle	VB1LUR32D-1	Red	GaAsP/GaP	Red Diffused	625	8 - 50	60°	2
	VB1LMR32D-1	Red	GaAlAs	Red Diffused	660	*100 - 300	60°	
	VB1LUG32D-1	Green	GaP	Green Diffused	565	8 - 32	60°	
	VB1LUY32D-1	Yellow	GaAsP/GaP	Yellow Diffused	590	8 - 32	60°	
3mm Right Angle	NK1LUR32D	Red	GaAsP/GaP	Red Diffused	625	8 - 50	60°	3
	NK1LMR32D	Red	GaAlAs	Red Diffused	660	*100 - 300	60°	
	NK1LUG32D	Green	GaP	Green Diffused	565	8 - 32	60°	
	NK1LUY32D	Yellow	GaAsP/GaP	Yellow Diffused	590	8 - 32	60°	
3mm Right Angle	NS1LUR32D	Red	GaAsP/GaP	Red Diffused	625	8 - 50	60°	4
	NS1LMR32D	Red	GaAlAs	Red Diffused	660	*100 - 300	60°	
	NS1LUG32D	Green	GaP	Green Diffused	565	8 - 32	60°	
	NS1LUY32D	Yellow	GaAsP/GaP	Yellow Diffused	590	8 - 32	60°	

