

**1 310 nm FOR 156 Mb/s, 622 Mb/s, 1.25 Gb/s  
InGaAsP MQW-FP LASER DIODE****DESCRIPTION**

The NX5304 Series is a 1 310 nm Multiple Quantum Well (MQW) structured Fabry-Perot (FP) laser diodes with InGaAs monitor PIN-PD. These devices are designed for 156 Mb/s: STM-1 (I-1, S-1.1, L-1.1), 622 Mb/s: STM-4 (I-4, S-4.1), Gigabit Ethernet application and ideal for Synchronous Digital Hierarchy (SDH) system.


**FEATURES**

- Optical output power  $P_o = 5.0 \text{ mW}$
- Low threshold current  $I_{th} = 10 \text{ mA}$
- High speed  $t_r = 0.3 \text{ ns MAX.}$   
 $t_f = 0.3 \text{ ns MAX.}$
- Wide operating temperature range  $T_c = -40 \text{ to } +85^\circ\text{C}$
- InGaAs monitor PIN-PD
- CAN package  $\phi 5.6 \text{ mm}$
- Fiber coupling point  $5.8 \text{ mm}$
- Based on Telcordia reliability





The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.  
Not all devices/types available in every country. Please check with local NEC Compound Semiconductor Devices representative for availability and additional information.

PACKAGE DIMENSIONS (UNIT: mm)



**ORDERING INFORMATION**

Part Number	Package	Pin Connections
NX5304EH	4-pin CAN with ball lens cap	
NX5304EK		

- Remarks**
1. The color of ball lens cap might be observed differently from our can package products.
  2. The hermetic test will be performed as AQL 1.0%.


**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Ratings	Unit
Optical Output Power	$P_o$	10	mW
Forward Current of LD	$I_F$	150	mA
Reverse Voltage of LD	$V_R$	2.0	V
Forward Current of PD	$I_F$	10	mA
Reverse Voltage of PD	$V_R$	20	V
Operating Case Temperature	$T_C$	-40 to +85	°C
Storage Temperature	$T_{stg}$	-40 to +85	°C
Assembly Temperature	$T_{asb}$	150 (15 Hr)	°C
Lead Soldering Temperature	$T_{sld}$	350 (3 sec.)	°C
Relative Humidity (noncondensing)	RH	85	%

**ELECTRO-OPTICAL CHARACTERISTICS (T<sub>c</sub> = 25°C, unless otherwise specified)**




Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Operating Voltage	V <sub>op</sub>	P <sub>o</sub> = 5.0 mW, T <sub>c</sub> = -40 to +85°C		1.1	1.5	V
Threshold Current	I <sub>th</sub>			10	15	mA
		T <sub>c</sub> = 85°C		25	30	
Threshold Output Power	P <sub>th</sub>	T <sub>c</sub> = -40 to +85°C, I <sub>F</sub> = I <sub>th</sub>		100	200	μW
Differential Efficiency	η <sub>d</sub>		0.32	0.4		W/A
Temperature Dependence of Differential Efficiency	Δη <sub>d</sub>	Δη <sub>d</sub> = 10 log $\frac{\eta_d (@ 85^\circ\text{C})}{\eta_d (@ 25^\circ\text{C})}$	-3.0	-1.2		dB
Center Wavelength	λ <sub>c</sub>	P <sub>o</sub> = 5.0 mW, RMS (-20 dB) T <sub>c</sub> = -40 to +85°C	1 263		1 360	nm
Temperature Dependence of Center Wavelength	Δλ/ΔT	T <sub>c</sub> = -40 to +85°C		0.4	0.5	nm/°C
Spectral Width	σ	P <sub>o</sub> = 5.0 mW, RMS (-20 dB) T <sub>c</sub> = -40 to +85°C		1.0	2.5	nm
Rise Time	t <sub>r</sub>	10-90%		0.15	0.3	ns
Fall Time	t <sub>f</sub>	90-10%		0.15	0.3	ns
Monitor Current	I <sub>m</sub>	V <sub>R</sub> = 5 V, P <sub>o</sub> = 5.0 mW	200	500	800	μA
Monitor Dark Current	I <sub>D</sub>	V <sub>R</sub> = 5 V		0.1	10	nA
		V <sub>R</sub> = 5 V, T <sub>c</sub> = -40 to +85°C			500	
Monitor PD Terminal Capacitance	C <sub>t</sub>	V <sub>R</sub> = 5 V, f = 1 MHz		6	20	pF
Tracking Error*1	γ	I <sub>m</sub> = const. (@ P <sub>o</sub> = 5.0 mW, T <sub>c</sub> = 25°C) T <sub>c</sub> = -40 to +85°C	-1.0		1.0	dB

\*1 Tracking Error: γ



$$\gamma = \left| 10 \log \frac{P_o}{5.0} \right| \text{ [dB]}$$


★ TYPICAL CHARACTERISTICS ( $T_c = -40$  to  $+85^\circ\text{C}$ , unless otherwise specified)




**Remark** The graphs indicate nominal characteristics.

★ TYPICAL CHARACTERISTICS (T<sub>c</sub> = 25°C, unless otherwise specified)


FORWARD CURRENT vs. FORWARD VOLTAGE




OPTICAL OUTPUT POWER vs. MONITOR CURRENT



SPECTRUM



TOLERANCE OF FIBER COUPLING DISTANCE (Z)



**Remark** The graphs indicate nominal characteristics.

LD CAN PACKAGES FAMILY FOR OPTICAL FIBER COMMUNICATIONS

Part Number	Absolute Maximum Ratings		Electro-Optical Characteristics (T <sub>c</sub> = 25°C)				Application	Package
	T <sub>c</sub> (°C)	T <sub>stg</sub> (°C)	I <sub>th</sub> (mA)	P <sub>o</sub> (mW)	λ (nm)			
			TYP.	TYP.	MIN.	MAX.		
NX5304 Series	-40 to +85	-40 to +85	10	5	1 263	1 360	156 Mb/s: STM-1 (I-1, S-1.1, L-1.1)	CAN
							622 Mb/s: STM-4 (I-4, S-4.1)	
							1.25 Gb/s: GbE	
NX5306 Series	-40 to +85	-40 to +85	10	5	1 263	1 360	156 Mb/s: STM-1 (I-1, S-1.1, L-1.1)	CAN
							622 Mb/s: STM-4 (I-4, S-4.1)	
							1.25 Gb/s: GbE	
NX5307 Series	-40 to +85	-40 to +85	10	10	1 266	1 360	2.5 Gb/s: STM-16	CAN
NX5501 Series	-20 to +85	-40 to +85	8	5	1 480	1 580	For FTTH	CAN
NX5504 Series	-20 to +85	-40 to +85	8	5	1 480	1 580	For FTTH	CAN
NX6306 Series	-40 to +85	-40 to +85	10	5	1 280	1 335	156 Mb/s: STM-1 (I-1, S-1.1, L-1.1)	CAN
							622 Mb/s: STM-4 (I-4, S-4.1, L-4.1)	
							1.25 Gb/s: GbE	
NX6307 Series	-20 to +85	-40 to +85	10	7	1 280	1 335	2.5 Gb/s: STM-16 (S-16.1, L-16.1)	CAN
NX6504 Series	-10 to +85	-40 to +85	12	5	1 530	1 570	156 Mb/s: STM-1	CAN
							622 Mb/s: STM-4	
NX6508 Series	0 to +70	-40 to +85	10	5	λ <sub>p</sub> -3 <sup>11</sup>	λ <sub>p</sub> +3 <sup>11</sup>	For CWDM	CAN
★ NX6509 Series	-20 to +85	-40 to +85	10	5	1 530	1 570	2.5 Gb/s: STM-16 (L-16.2)	CAN

\*1 λ<sub>p</sub> = 1 470, 1 490, 1 510, 1 530, 1 550, 1 570, 1 590, 1 610 nm

**REFERENCE**

Document Name	Document No.
OPTICAL SEMICONDUCTOR DEVICES FOR FIBEROPTIC COMMUNICATIONS SELECTION GUIDE	PL10161E
Opto-Electronics Devices Pamphlet	PX10160E


- **The information in this document is current as of December, 2003. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
  - No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
  - NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
  - Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
  - While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
  - NEC semiconductor products are classified into the following three quality grades:  
 "Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.  
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots  
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)  
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
- The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
- (Note)
- (1) "NEC" as used in this statement means NEC Corporation, NEC Compound Semiconductor Devices, Ltd. and also includes its majority-owned subsidiaries.
  - (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).

M8E 00.4-0110

**SAFETY INFORMATION ON THIS PRODUCT**



**SEMICONDUCTOR LASER**



**AVOID EXPOSURE-Invisible**  
 Laser Radiation is emitted from  
 this aperture

<p><b>Warning</b> Laser Beam</p>	<p>A laser beam is emitted from this diode during operation. The laser beam, visible or invisible, directly or indirectly, may cause injury to the eye or loss of eyesight.</p> <ul style="list-style-type: none"> <li>• Do not look directly into the laser beam.</li> <li>• Avoid exposure to the laser beam, any reflected or collimated beam.</li> </ul>
<p><b>Caution</b> GaAs Products</p>	<p>This product uses gallium arsenide (GaAs). GaAs vapor and powder are hazardous to human health if inhaled or ingested, so please observe the following points.</p> <ul style="list-style-type: none"> <li>• Follow related laws and ordinances when disposing of the product. If there are no applicable laws and/or ordinances, dispose of the product as recommended below.                     <ol style="list-style-type: none"> <li>1. Commission a disposal company able to (with a license to) collect, transport and dispose of materials that contain arsenic and other such industrial waste materials.</li> <li>2. Exclude the product from general industrial waste and household garbage, and ensure that the product is controlled (as industrial waste subject to special control) up until final disposal.</li> </ol> </li> <li>• Do not burn, destroy, cut, crush, or chemically dissolve the product.</li> <li>• Do not lick the product or in any way allow it to enter the mouth.</li> </ul>

► For further information, please contact

**NEC Compound Semiconductor Devices, Ltd.** <http://www.ncsd.necel.com/>  
 E-mail: salesinfo@ml.ncsd.necel.com (sales and general)  
 techinfo@ml.ncsd.necel.com (technical)  
 5th Sales Group, Sales Division TEL: +81-44-435-1588 FAX: +81-44-435-1579

**NEC Compound Semiconductor Devices Hong Kong Limited**  
 E-mail: ncsd-hk@elhk.nec.com.hk (sales, technical and general)  
 Hong Kong Head Office TEL: +852-3107-7303 FAX: +852-3107-7309  
 Taipei Branch Office TEL: +886-2-8712-0478 FAX: +886-2-2545-3859  
 Korea Branch Office TEL: +82-2-558-2120 FAX: +82-2-558-5209

**NEC Electronics (Europe) GmbH** <http://www.ee.nec.de/>  
 TEL: +49-211-6503-01 FAX: +49-211-6503-487

**California Eastern Laboratories, Inc.** <http://www.cel.com/>  
 TEL: +1-408-988-3500 FAX: +1-408-988-0279