

InGaAsP MQW DC-PBH PULSED LASER DIODE MODULE
1 625 nm OTDR APPLICATION


DESCRIPTION

The NX7661JB-BC is a 1 625 nm Multiple Quantum Well (MQW) structure pulsed laser diode DIP module with single mode fiber and internal thermoelectric cooler. It is designed for light sources of optical measurement equipment (OTDR).

FEATURES

- High output power $P_r = 120 \text{ mW MIN. @ } I_{FP} = 1\,000 \text{ mA, PW} = 10 \mu\text{s, Duty} = 1\%$
- Long wavelength $\lambda_c = 1\,625 \text{ nm}$
- Internal thermoelectric cooler, thermistor
- Hermetically sealed 14-pin Dual-In-Line Package
- Single mode fiber pigtail

★ PACKAGE DIMENSIONS (UNIT: mm)



The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all devices/types available in every country. Please check with local NEC Compound Semiconductor Devices representative for availability and additional information.

★ ORDERING INFORMATION

Part Number	Available Connector
NX7661JB-BC	With FC-UPC Connector

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Ratings	Unit
Pulsed Forward Current ^{*1}	I _{FP}	1.2	A
Reverse Voltage	V _R	2.0	V
Cooler Current	I _C	1.0	A
Cooler Voltage	V _C	2.0	V
Thermistor Current	I _t	0.5	mA
Thermistor Voltage	V _t	12.0	V
Operating Case Temperature	T _C	−20 to +65	°C
Storage Temperature	T _{stg}	−40 to +70	°C
Lead Soldering Temperature	T _{sld}	260 (10 sec)	°C

*1 Pulse conditions: Pulse width (PW) = 10 μs, Duty = 1%

ELECTRO-OPTICAL CHARACTERISTICS (T_{LD} = 25°C, T_C = -20 to +65°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Forward Voltage	V _{FP}	CW, I _F = 30 mA			4.0	V
Threshold Current	I _{th}	CW		30	70	mA
Optical Output Power from Fiber	P _r	I _{FP} = 1 000 mA, PW = 10 μs, Duty = 1%	120			mW
Center Wavelength	λ _c	RMS, I _{FP} = 1 000 mA, PW = 10 μs, Duty = 1%	1 615	1 625	1 635	nm
Spectral Width	σ	RMS, I _{FP} = 1 000 mA, PW = 10 μs, Duty = 1%		7.0	15	nm
Rise Time	t _r	10-90%			2.0	ns
Fall Time	t _f	90-10%			2.0	ns

ELECTRO-OPTICAL CHARACTERISTICS


(Applicable to Thermistor and TEC: T_{LD} = 25°C, T_C = -20 to +65°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Thermistor Resistance	R	T _{LD} = 25°C	9.5	10.0	10.5	kΩ
B Constant	B		3 350	3 450	3 550	K
Cooler Current	I _c	ΔT = 40°C		0.6	0.8	A
Cooler Voltage	V _c	ΔT = 40°C		1.1	1.5	V
Cooling Capacity	ΔT ^{*1}	I _c = 0.8 A	40			°C


***1** $\Delta T = |T_C - T_{LD}|$

★ TYPICAL CHARACTERISTICS (T_c = 25°C, unless otherwise specified)


OPTICAL OUTPUT POWER FROM FIBER vs.
PULSED FORWARD CURRENT



SPECTRUM



THERMISTOR RESISTANCE vs.
CASE TEMPERATURE



Remark The graphs indicate nominal characteristics.

★ OTDR LD FAMILY

Part Number	Electro-Optical Characteristics (T _c = 25°C)			Conditions			Application	Package
	λ_c (nm)	P _f (mW)		I _{FP} (mA)	PW (μ s)	Duty (%)		
	TYP.	MIN.	TYP.					
NX7327BF-AA	1 310	110	180	1 000	10	1	OTDR	4-pin coax. with SMF
NX7328BF-AA	1 310	70	110	400	10	1	OTDR	4-pin coax. with SMF
NX7329BB-AA	1 310	25	50	400	10	1	OTDR	4-pin coax. with SMF
NX7361JB-BC	1 310	150	–	1 000	10	1	OTDR	14-pin DIP with SMF
NX7526BF-AA	1 550	95	145	1 000	10	1	OTDR	4-pin coax. with SMF
NX7527BF-AA	1 550	120	145	1 000	10	1	OTDR	4-pin coax. with SMF
NX7528BF-AA	1 550	60	80	400	10	1	OTDR	4-pin coax. with SMF
NX7529BB-AA	1 550	20	40	400	10	1	OTDR	4-pin coax. with SMF
NX7561JB-BC	1 550	135	–	1 000	10	1	OTDR	14-pin DIP with SMF
NX7661JB-BC	1 625	120	–	1 000	10	1	OTDR	14-pin DIP with SMF

REFERENCE

Document Name	Document No.
Optical semiconductor devices for fiberoptic communications Selection Guide	P12480E
Opto-Electronics Devices Pamphlet	P13623E
Opto-Electronics Devices (CD-ROM)	P12944X
NEC semiconductor device reliability/quality control system ^{*1}	C11159E
Quality grades on NEC semiconductor devices ^{*1}	C11531E
SEMICONDUCTOR SELECTION GUIDE –Products and Packages– ^{*1}	X13769E


^{*1} Published by NEC Corporation

The export of this product from Japan is prohibited without governmental license. To export or re-export this product from a country other than Japan may also be prohibited without a license from that country.
Please call an NEC Compound Semiconductor Devices sales representative.


- **The information in this document is current as of May, 2002. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
- NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
- NEC semiconductor products are classified into the following three quality grades:
 "Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
 The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
 (Note)
 (1) "NEC" as used in this statement means NEC Corporation, NEC Compound Semiconductor Devices, Ltd. and also includes its majority-owned subsidiaries.
 (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).

M8E 00.4-0110

SAFETY INFORMATION ON THIS PRODUCT



SEMICONDUCTOR LASER



Warning	Laser Beam	A laser beam is emitted from this diode during operation. The laser beam, visible or invisible, directly or indirectly, may cause injury to the eye or loss of eyesight. - Do not look directly into the laser beam. - Avoid exposure to the laser beam, any reflected or collimated beam.
Caution	GaAs Products	The product contains gallium arsenide, GaAs. GaAs vapor and powder are hazardous to human health if inhaled or ingested. - Do not destroy or burn the product. - Do not cut or cleave off any part of the product. - Do not crush or chemically dissolve the product. - Do not put the product in the mouth. Follow related laws and ordinances for disposal. The product should be excluded from general industrial waste or household garbage.
Caution	Optical Fiber	A glass-fiber is attached on the product. Handle with care. When the fiber is broken or damaged, handle carefully to avoid injury from the damaged part or fragments.

► Business issue

NEC Compound Semiconductor Devices, Ltd.

5th Sales Group, Sales Division TEL: +81-3-3798-6372 FAX: +81-3-3798-6783 E-mail: salesinfo@csd-nec.com

NEC Compound Semiconductor Devices Hong Kong Limited

Hong Kong Head Office TEL: +852-3107-7303 FAX: +852-3107-7309
 Taipei Branch Office TEL: +886-2-8712-0478 FAX: +886-2-2545-3859
 Korea Branch Office TEL: +82-2-528-0301 FAX: +82-2-528-0302

NEC Electron Devices European Operations <http://www.nec.de/>

TEL: +49-211-6503-101 FAX: +49-211-6503-487

California Eastern Laboratories, Inc. <http://www.cel.com/>

TEL: +1-408-988-3500 FAX: +1-408-988-0279

► Technical issue

NEC Compound Semiconductor Devices, Ltd. <http://www.csd-nec.com/>

Sales Engineering Group, Sales Division
 E-mail: techinfo@csd-nec.com FAX: +81-44-435-1918