



WIRELESS COMPONENTS


Model OSC1605A Cosmic - Technical Data

Features:

- Stable frequency over temperature
- Good SSBN Noise performance
- Surface mountable package

Description and Applications:

Surface mount 3.2 x 5 mm Voltage Control Temperature Compensated Crystal Oscillator (VCTCXO) for use in 3G, GSM, TDMA, CDMA, PDAs, Satellite handsets, 2-way radios, Pagers, Analog applications, and other portable electronics requiring a stable frequency source.



Electrical Specifications:

OSC1605A	Specification
Nominal Frequency	19.2 MHz
Supply Voltage (Vdd)	2.75 V $\pm$ 0.1 V
Frequency Stability over Temperature	$\pm$ 2.5 PPM (-30 C to 80C)
RF output (AC Coupled)	1.0 Vpp (minimum) Clipped Sinewave
Current Drain	2.5 mA maximum
Frequency Adjust Method	Analog DC Frequency Adjust
Frequency Adjust Center Voltage (Vcc)	1.50 VDC
Frequency Adjust Range	$\pm$ 6.50 PPM to $\pm$ 11.0 PPM (1.50 V $\pm$ 1.0 V)
SSBN @ 16.8MHz at 10kHz offset	-140dBc/Hz Typical
Aging	$\pm$ 1PPM/Yr @25C

Model: OSC1605A

Technical Data

Mechanical Dimensions (mm):

