

OD SERIES

VIDEO OVERSAMPLING SMD FILTERS

- Surface mount compatibility
- Flat or Sinx/x versions
- Small size, low cost
- Luminance and Chrominance versions

With reduced analogue filter costs resulting from oversampling techniques, there is an increased need for manufacturing facilities to avoid the large production costs associated with the presently available through hole packages. The Faraday OD range of oversampling filters can be used in surface mount assembly lines allowing vacuum pick up and reflow.

This range of analogue filters has been designed for use in conjunction with a half band interpolating/decimating filter such as the TRW2242 or with the many encoder chips available which employ digital filtering and an output D to A converter. This type of digital filtering has good attenuation between the frequencies of $F_s/4$ and $3F_s/4$ where F_s is the Master Clock rate. When the normal clock rate of 27 MHz is used for the luminance channel the signal can be expected to have insignificant energy between 6.75 MHz and 20.25 MHz.

In order to preserve the integrity of the signal these filters have a good amplitude and group delay characteristics in the passband, similar to the requirements of CCIR601 but due to the above considerations do not have significant attenuation below 21 MHz.

Order code:	ODYSA	ODYFA	ODCSA	ODCFA
<i>Impedance</i>	150Ω	150Ω	150Ω	150Ω
<i>Sinx/x correction</i>	Yes	No	Yes	No
<i>Sampling Freq.</i>	27.0 MHz	27.0 MHz	13.5 MHz	13.5 MHz
<i>End of Passband</i>	5.75 MHz	5.75 MHz	2.75 MHz	2.75 MHz
<i>Amp. ripple</i>	< 0.25 dB	< 0.12 dB	< 0.30 dB	< 0.12 dB
<i>G.D. ripple</i>	< 10 ns	< 6 ns	< 20 ns	< 12 ns
<i>Start of stopband</i>	21.5 MHz	21.5 MHz	10.75 MHz	10.75 MHz
<i>Stopband atten. wrt 100 kHz</i>	> 40 dB	> 40 dB	> 40 dB	> 40 dB
<i>Delay time nom. at 200 kHz</i>	27 ns	30 ns	50 ns	58 ns
<i>Package</i>	DR00171A	DR00171A	DR00171A	DR00171A

PACKAGE DETAIL

