


ORD 9402 SERIES


3mm LED INTERLOCKING ASSEMBLY

The ORD-9402 series is a family of devices using a black Nylon 6 Vo UL rated housing for 1 or 2 LED's at right angles to the PCB. A unique interlocking feature enables packages to be stacked up to 32 Way long with ready insertion into a 0.1" pitch PCB layout. The pin outs are accurately positioned with a locating base plug. The LED's are lumenous intensity a matched in any one batch.

- Precision Interlock
- Precision Pin Out Positions
- Matched LEDs
- Any colour combination, polarity or low current LEDs.



MECHANICAL DATA



BEDFORD OPTO TECHNOLOGY LTD
LINDSAYLANDS, BIGGAR, LANARKSHIRE ML12 6NR
Tel: +44 (0) 1899 221221 Fax: +44 (0) 1899 221009

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C)

Parameter	Red	Green	Yellow	Orange
Forward Current	15mA	30mA	20mA	30mA
Power Dissipation	40mW	100mW	60mW	100mW
Reverse Current @ 5V	10mA	10mA	10mA	10mA
Operating Temperature	-40°C to +85°C			
Storage Temperature	-40°C to 100°C			
Lead Soldering Temperature for 5sec (2.0mm from Body)	260°C			

OPTO ELECTRONIC DATA (T_a = 25°C)

COLOUR		Luminous Intensity If = 10mA mcd	Peak Wave-length nm	Viewing Angle Degrees	Forward Voltage If = 20mA volts
RED	min	2.0	-	-	1.7
	typ	4.2	697	50	-
	ma	-	-	-	2.8
YELLOW	min	7.5	-	-	1.7
	typ	12	585	50	-
	ma	-	-	-	2.8
GREEN	min	9.0	-	-	1.7
	typ	15	565	50	-
	ma	-	-	-	2.8
ORANGE	min	7.5	-	-	1.7
	typ	12	635	50	-
	ma	-	-	-	2.8

ORDERING INFORMATION

Dual LED - **ORD 9402XY** X = Top LED
Y = Bottom LED

Single LED- **ORE 9401X** X = Bottom LED

Indicate colour by using R = Red
O = Orange
Y = Yellow
G = Green

OPTO ELECTRONIC SOLUTIONS

BEDFORD OPTO TECHNOLOGY LTD
LINDSAYLANDS, BIGGAR, LANARKSHIRE ML12 6NR

Tel: +44 (0) 1899 221221 Fax: +44 (0) 1899 221009

Website: bot.co.uk E-mail: bill@bot.co.uk