


ORT 2200 SERIES


1.8mm LED 2 TIER CIRCUIT BOARD INDICATOR

A two tier 1.8mm assembly compatible with the 3 & 4 tier ORT9303/2400 series. Moulded in Black Zytel with 1mm min wall thickness to suit I.S. applications. A baseplate & locating pin ensure secure accurate board positioning.

- Low Profile/High Density.
- Locating Pin + Baseplate for accurate location.
- Suitable for I.S. applications.
- +/-20 deg viewing angle



MECHANICAL DATA



BEDFORD OPTO TECHNOLOGY LTD
LINDSAYLANDS, BIGGAR, LANARKSHIRE ML12 6NR
Tel: +44 (0) 1899 221221 Fax: +44 (0) 1899 221009
Website: bot.co.uk E-mail: bill@bot.co.uk

ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

REVERSE VOLTAGE		6 Volts
CONTINUOUS FORWARD CURRENT	Red Others	50 mA 30 mA
POWER DISSIPATION Ta < 55 C		100 mW
JUNCTION TEMP	100°C	
STORAGE TEMP	-55 to +100°C	
THERMAL RESISTANCE	450 K/W	

OPTO ELECTRONIC DATA (Ta = 25°C)

COLOUR		Luminous Intensity If = 10mA mcd	Peak Wavelength nm	Forward Voltage If = 20mA volts
RED	min	1	-	-
	typ	1.5	660	1.6
	ma	-	-	2
ORANGE	min	4	-	-
	typ	5	630	2
	ma	-	-	3
YELLOW	min	2.5	-	-
	typ	8	585	2.4
	ma	-	-	3
GREEN	min	4	-	-
	typ	12	565	2.4
	ma	-	-	3

ORDERING INFORMATION

ORT 2200 X - - - - - Y

Top Position Bottom Position

X OR Y = R = Red

O = Orange

Y = Yellow

G = Green

B = Blank

Custom part numbers will be allocated to describe

OPTO ELECTRONIC SOLUTIONS

BEDFORD OPTO TECHNOLOGY LTD
LINDSAYLANDS, BIGGAR, LANARKSHIRE ML12 6NR

Tel: +44 (0) 1899 221221 Fax: +44 (0) 1899 221009

Website: bot.co.uk E-mail: bill@bot.co.uk