



# PHOTONIC DETECTORS INC.

## Silicon Photodiode, Blue Enhanced Photoconductive Type PDB-C156 , with daylight filter Type PDB-C156F



### PACKAGE DIMENSIONS INCH [mm]



### FEATURES

- Large active area
- High speed
- Low cost
- 25 MHz bandwidth

**DESCRIPTION:** The **PDB-C156** detector is a 8.02 mm<sup>2</sup> planar pin photodiode housed in a water clear plastic sidelooker package. Designed for high speed, low capacitance, photoconductive applications. The **PDB-C156F** includes a daylight filter.

### APPLICATIONS


- Smoke detectors
- Light dimmers
- TV & VCR remotes
- IR DATA LINKS

### ABSOLUTE MAXIMUM RATING (TA=25°C unless otherwise noted)

SYMBOL	PARAMETER	MIN	MAX	UNITS
V <sub>BR</sub>	Reverse Voltage		50	V
T <sub>STG</sub>	Storage Temperature	-40	+100	°C
T <sub>O</sub>	Operating Temperature Range	-40	+80	°C
T <sub>S</sub>	Soldering Temperature*		+260	°C
I <sub>L</sub>	Light Current		0.5	mA

\*1/16 inch from case for 3 secs max

### SPECTRAL RESPONSE



### ELECTRO-OPTICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I <sub>SC</sub>	Short Circuit Current	H = 100 fc, 2850 K	70	90		μA
I <sub>D</sub>	Dark Current	H = 0, V <sub>R</sub> = 10 V		2	15	nA
R <sub>SH</sub>	Shunt Resistance	H = 0, V <sub>R</sub> = 10 mV	100	150		MΩ
TCR <sub>SH</sub>	RSH Temp. Coefficient	H = 0, V <sub>R</sub> = 10 mV		-8		% / °C
C <sub>J</sub>	Junction Capacitance	H = 0, V <sub>R</sub> = 10 V*		10	15	pF
λrange	Spectral Application Range	(without daylight filter)**	400		1100	nm
λp	Spectral Response - Peak			950		nm
V <sub>BR</sub>	Breakdown Voltage	I = 10 μA	30	75		V
NEP	Noise Equivalent Power	V <sub>R</sub> = 10 V @ Peak		4.4x10 <sup>-14</sup>		W/ √Hz
tr	Response Time	RL = 1 KΩ V <sub>R</sub> = 10 V		15		nS

Information in this technical data sheet is believed to be correct and reliable. However, no responsibility is assumed for possible inaccuracies or omission. Specifications are subject to change without notice. \*f = 1 MHz, \*\* daylight filter= 700 - 1100 nm

[FORM NO. 100-PDB-C156 REV A]